

A LENS BARREL
INCORPORATING A ROTATABLE RING

BACKGROUND OF THE INVENTION

5 1. Field of the Invention

 The present invention relates to a lens barrel such as a photographing (imaging) lens which incorporates a rotatable ring performing an advancing/retracting operation in which the rotatable ring rotates while moving
10 along an optical axis, and a fixed-position rotating operation in which the rotatable ring rotates at an axial fixed position without moving along the optical axis.

 2. Description of the Related Art

 Retractable photographing lenses in which a
15 rotatable ring such as a cam ring advances along an optical axis while rotating from a fully retracted position toward a ready-to-photograph position (e.g., zooming range of zoom lens) upon power being turned ON and in which the cam ring stops advancing upon reaching the ready-to-
20 photograph position to be rotatable at an axial fixed position on the optical axis without rotating are known in the art. In such known retractable photographing lenses, a drive mechanism for driving the rotatable ring is generally complicated and large in size.

SUMMARY OF THE INVENTION

The present invention provides a lens barrel incorporating a rotatable ring which is provided with a simple, small and low-cost drive mechanism for driving
5 the rotatable ring to perform the aforementioned rotating-advancing/rotating-retracting operation and the aforementioned fixed-position rotating operation.

According to an aspect of the present invention, a lens barrel is provided, including a rotatable ring
10 rotatable about a rotational axis extending in a direction of an optical axis, an outer annular member which is non-rotatable and supports the rotatable ring inside the outer annular member, and at least one optical element movable along the optical axis by a rotation of the
15 rotatable ring, the lens barrel including an advancing/retracting mechanism, provided between an outer peripheral surface of the rotatable ring and an inner peripheral surface of the outer annular member, configured to move the rotatable ring along the optical
20 axis between front and rear movement limits of the rotatable ring in the optical axis direction relative to the outer annular member, when the rotatable ring is rotated; at least one circumferential groove located on one of the inner peripheral surface of the outer annular
25 member and the outer peripheral surface of the rotatable

ring; and at least one rotation-guiding projection located on the other of the inner peripheral surface of the outer annular member and the outer peripheral surface of the rotatable ring. The at least one rotation-guiding projection is engaged in the at least one circumferential groove such that the rotatable ring is rotatable at an axial fixed position without moving along the optical axis when the rotatable ring is moved to the front movement limit by the advancing/retracting mechanism.

The at least one rotation-guiding projection and the at least one circumferential groove can be formed on the outer peripheral surface of the rotatable ring and the inner peripheral surface of the outer annular member, respectively.

The advancing/retracting mechanism can include a male helicoid located on the outer peripheral surface of the rotatable ring, and a female helicoid located on the inner peripheral surface of the outer annular member, the female helicoid engageable with the male helicoid, wherein the female helicoid and the male helicoid are disengaged from each other when the at least one rotation-guiding projection is engaged in the at least one circumferential groove.

The lens barrel can further include at least one non-threaded portion on the one of the inner peripheral

surface of the outer annular member and the outer peripheral surface of the rotatable ring, on which the at least one circumferential groove is formed, in an area thereon in which one of the male helicoid and the female helicoid is formed, the non-threaded portion generally extending parallel to threads of the one of the male helicoid and the female helicoid to communicate with the at least one circumferential groove, wherein the at least one rotation-guiding projection is positioned to be associated with the at least one non-threaded portion when the male helicoid and the female helicoid are engaged with each other.

It is desirable for an amount of projection of the at least one rotation-guiding projection in a radial direction is greater than a tooth depth of the one of the male helicoid and the female helicoid. The at least one non-threaded portion can include at least one inclined groove extending generally parallel to the threads of the one of the male helicoid and the female helicoid, the at least one inclined groove communicating with the at least one circumferential groove, the at least one rotation-guiding projection entering the at least one inclined groove when the male helicoid and the female helicoid are engaged with each other.

It is desirable for the at least one rotation-

guiding projection to come into contact with one of two
opposed surfaces in the at least one inclined groove such
that the male helicoid and the female helicoid are engaged
with each other by a relative sliding movement between
5 the at least one rotation-guiding projection and the one
of two opposed surfaces, when the at least one
rotation-guiding projection is moved from the
circumferential groove to the inclined groove by a
rotation of the rotatable ring.

10 It is desirable for the at least one rotation-
guiding projection and the at least one circumferential
groove to be located in front of the male helicoid and
the female helicoid in the optical axis direction on the
outer peripheral surface of the rotatable ring and the
15 inner peripheral surface of the outer annular member,
respectively.

The at least one rotation-guiding projection can
include a plurality of rotation-guiding projections
located at different circumferential positions. The
20 circumferential groove can be a plurality of
circumferential grooves located at different
circumferential positions.

The lens barrel can further include a linearly
movable ring configured to be guided linearly along the
25 optical axis and moved together with the rotatable ring

along the optical axis, while allowing the rotatable ring to rotate relative to the linearly movable ring; a cam ring rotatable together with the rotatable ring, and including at least one cam groove configured to move the
5 at least one optical element along the optical axis by rotation of the cam ring; and a cam-ring guide, located between the linearly movable ring and the cam ring, configured to move the cam ring along the optical axis relative to the linearly movable ring by the rotation of
10 the cam ring when the rotatable ring performs the advancing/retracting operation via the advancing/retracting mechanism, and configured to rotate the cam ring at an axial fixed position without moving the cam ring along the optical axis relative to the
15 linearly movable ring when the rotatable ring performs the fixed-position rotating operation.

The optical element can be at least two optical elements movable along the optical axis while changing a distance therebetween and varying a focal length by the
20 rotation of the rotatable ring.

The rotatable ring can include a circumferential gear formed on threads of the male helicoid. The lens barrel can further include a drive gear supported by the outer annular member and rotatable about an axis of the
25 drive gear, the drive gear remaining in mesh with the

circumferential gear so as to rotate the rotatable ring when the rotatable ring performs one of the advancing/retracting operation via the male helicoid and the female helicoid and the fixed-position rotating operation via the rotation-guiding projection and the circumferential groove.

The at least one rotation-guiding projection and the at least one circumferential groove can be located on the outer peripheral surface of the rotatable ring and the inner peripheral surface of the outer annular member, respectively. The drive gear is supported by the outer annular member and is rotatable on an axis of the drive gear at a position different from a position of the circumferential groove in the optical axis direction.

The lens barrel can further include at least one non-threaded portion on the inner peripheral surface of the outer annular member, in an area thereon in which and the female helicoid is located. The at least one non-threaded portion extends generally parallel to threads of the female helicoid and communicates with the at least one circumferential groove. It is desirable for the rotation-guiding projection to be associated with the at least one non-threaded portion when the male helicoid and the female helicoid are engaged with each other. The drive gear can be supported by the outer annular member

and is rotatable at a position different from a position of the at least one non-threaded portion in a circumferential direction of the outer annular member.

The lens barrel can be incorporated in a camera, and
5 the outer annular member can be a stationary barrel fixed to a camera body of the camera.

In another embodiment, a lens barrel is provided, including a rotatable ring rotatable about a rotational axis extending in a direction of an optical axis, an outer
10 annular member which is non-rotatable and supports the rotatable ring inside the outer annular member, and at least one optical element which moves along the optical axis by a rotation of the rotatable ring, the lens barrel including a male helicoid located on an outer peripheral
15 surface of the rotatable ring; a female helicoid located on an inner peripheral surface of the outer annular member to be engageable with the male helicoid, wherein the female helicoid and the male helicoid are engaged with and disengaged from each other in accordance with
20 variations in relative position in the optical axis direction between the rotatable ring and the outer annular member; at least one circumferential groove located on one of the inner peripheral surface of the outer annular member and the outer peripheral surface of the rotatable
25 ring, at a position different from positions of the male

helicoid and the female helicoid in the optical axis direction; and at least one rotation-guiding projection located on the other of the inner peripheral surface of the outer annular member and the outer peripheral surface of the rotatable ring at a position different from the positions of the male helicoid and the female helicoid in the optical axis direction and slidably engageable in the at least one circumferential groove. The at least one rotation-guiding projection is disengaged from the at least one circumferential groove such that the rotatable ring performs an advancing/retracting operation in which the rotatable ring moves along the optical axis direction while rotating relative to the outer annular member due to engagement of the male helicoid with the female helicoid, when the rotatable ring is positioned relative to the outer annular member in the optical axis direction so that the male helicoid and the female helicoid are engaged with each other. The rotation-guiding projection can be engaged in the circumferential groove such that the rotatable ring performs a fixed-position rotating operation in which the rotatable ring rotates at an axial fixed position without moving along the optical axis relative to the outer annular member, when the rotatable ring is positioned relative to the outer annular member in the optical axis

direction so that the male helicoid and the female helicoid are disengaged from each other.

In another embodiment, a lens barrel is provided, including a rotatable ring rotatable about a rotational axis extending in a direction of an optical axis, an outer annular member which is non-rotatable and supports the rotatable ring inside the outer annular member, and at least one optical element which moves along the optical axis by a rotation of the rotatable ring, the lens barrel including a male helicoid located on an outer peripheral surface of the rotatable ring; a female helicoid located on an inner peripheral surface of the outer annular member to be engageable with the male helicoid, wherein the female helicoid and the male helicoid are engaged with and disengaged from each other in accordance with variations in relative position in the optical axis direction between the rotatable ring and the outer annular member; at least one circumferential groove located on the inner peripheral surface of the outer annular member at a position different from a position of the female helicoid in the optical axis direction; at least one rotation-guiding projection located on the outer peripheral surface of the rotatable ring at a position different from a position of the male helicoid in the optical axis direction and slidably engageable in the at

least one circumferential groove, wherein the at least one rotation-guiding projection is disengaged from the at least one circumferential groove when the male helicoid and the female helicoid are engaged with each other, and
5 wherein the at least one rotation-guiding projection is engaged in the at least one circumferential groove when the male helicoid and the female helicoid are disengaged from each other; a circumferential gear located on the outer peripheral surface of the rotatable ring at a
10 position different from a position of the rotation-guiding projection in the optical axis direction; and a drive gear supported by the outer annular member and rotatable on an axis of the drive gear, and which remains in mesh with the circumferential gear and is configured
15 to rotate the rotatable ring in one of the case where the male helicoid and the female helicoid are engaged with each other and the case where the at least one rotation-guiding projection is engaged in the at least one circumferential groove. The drive gear can be
20 supported by the outer annular member and is rotatable at a position different from a position of the at least one circumferential groove in the optical axis direction.

The lens barrel can further include at least one non-threaded portion on the inner peripheral surface of
25 the outer annular member in an area thereon in which and

the female helicoid is formed, wherein the at least one non-threaded portion extends generally parallel to threads of the female helicoid and is configured to communicate with the at least one circumferential groove.

5 The at least one rotation-guiding projection can be configured to be associated with the at least one non-threaded portion when the male helicoid and the female helicoid are engaged with each other. The drive gear can be supported by the outer annular member and is rotatable

10 at a position different from position of the non-threaded portions in a circumferential direction of the outer annular member.

The at least one rotation-guiding projection can include a plurality of rotation-guiding projections

15 formed on the outer peripheral surface of the rotatable ring at different circumferential positions thereon. The at least one circumferential groove can include a plurality of circumferential grooves located on the inner peripheral surface of the outer annular member at

20 different circumferential positions thereon. The at least one non-threaded portion can include a plurality of non-threaded portions located on the inner peripheral surface of the outer annular member at different circumferential positions thereon. The drive gear can

25 be positioned between two adjacent non-threaded portions

of the plurality of non-threaded portions in a circumferential direction of the outer annular member.

It is desirable for an amount of projection of each of the plurality of rotation-guiding projections in a radially outward direction to be greater than a tooth depth of the male helicoid. The plurality of non-threaded portions can include a plurality of inclined grooves, respectively, which extend parallel to the threads of the female helicoid, wherein the plurality of rotation-guiding projections enter the plurality of inclined grooves, respectively, when the male helicoid and the female helicoid are engaged with each other.

The circumferential gear can be formed on threads of the male helicoid.

The optical element can be at least two optical elements movable along the optical axis while changing a distance therebetween and varying a focal length by the rotation of the rotatable ring.

The lens barrel can be incorporated in a camera. The outer annular member can be a stationary barrel fixed to a camera body of the camera.

The present disclosure relates to subject matter contained in Japanese Patent Application Nos. 2002-247338 (filed on August 27, 2002), 2002-298149 (filed on October 11, 2002), and 2002-298150 (filed on October 11, 2002)

which are expressly incorporated herein by reference in its entirety.

BRIEF DESCRIPTION OF THE DRAWINGS

5 The present invention will be described below in detail with reference to the accompanying drawings in which:

Figure 1 is an exploded perspective view of an embodiment of a zoom lens according to the present
10 invention;

Figure 2 is an exploded perspective view of a structure supporting a first lens group of the zoom lens;

Figure 3 is an exploded perspective view of a structure supporting a second lens group of the zoom lens;

15 Figure 4 is an exploded perspective view of a lens barrel advancing-retracting structure of the zoom lens for advancing and retracting a third external barrel from a stationary barrel;

Figure 5 is a perspective view, partly exploded, of
20 the zoom lens, showing a fixing procedure of a viewfinder unit to the zoom lens and a fixing procedure of a gear train to the zoom lens;

Figure 6 is a perspective view of a zoom lens assembly made from the elements shown in Figure 5;

25 Figure 7 is a side elevational view of the zoom lens

assembly shown in Figure 6;

Figure 8 is a perspective view of the zoom lens assembly shown in Figure 6, viewed obliquely from behind;

Figure 9 is an axial cross sectional view of an
5 embodiment of a digital camera incorporating the zoom lens assembly shown in Figures 6 through 8, wherein an upper half above a photographing optical axis and a lower half below the photographing optical axis show a state of the zoom lens at telephoto extremity and a state of the zoom
10 lens at wide-angle extremity, respectively;

Figure 10 is an axial cross sectional view of the digital camera shown in Figure 9 in the retracted state of the zoom lens;

Figure 11 is a developed view of the stationary
15 barrel shown in Figure 1;

Figure 12 is a developed view of a helicoid ring shown in Figure 4;

Figure 13 is a developed view of the helicoid ring shown in Figure 1, showing a structure of the inner
20 peripheral surface thereof by broken lines;

Figure 14 is a developed view of the third external barrel shown in Figure 1;

Figure 15 is a developed view of a first linear guide ring shown in Figure 1;

25 Figure 16 is a developed view of a cam ring shown

in Figure 1;

Figure 17 is a developed view of the cam ring shown in Figure 1, showing a structure of the inner peripheral surface thereof by broken lines;

5 Figure 18 is a developed view of a second linear guide ring shown in Figure 1;

Figure 19 is a developed view of a second lens group moving frame shown in Figure 1;

10 Figure 20 is a developed view of a second external barrel shown in Figure 1;

Figure 21 is a developed view of a first external barrel shown in Figure 1;

15 Figure 22 is a conceptual diagram of elements of the zoom lens, showing the relationship among these elements in relation to the operations thereof;

Figure 23 is a developed view of the helicoid ring, the third external barrel and the stationary barrel, showing the positional relationship thereamong in the retracted state of the zoom lens;

20 Figure 24 is a developed view of the helicoid ring, the third external barrel and the stationary barrel, showing the positional relationship thereamong at the wide-angle extremity the zoom lens;

25 Figure 25 is a developed view of the helicoid ring, the third external barrel and the stationary barrel,

showing the positional relationship among thereamong at
the telephoto extremity the zoom lens;

Figure 26 is a developed view of the helicoid ring,
the third external barrel and the stationary barrel,
5 showing a positional relationship thereof;

Figure 27 is a developed view of the stationary
barrel, showing the positions of a set of rotational
sliding projections of the helicoid ring with respect to
the stationary barrel in the retracted state of the zoom
10 lens;

Figure 28 is a view similar to that of Figure 27,
showing the positions of the set of rotational sliding
projections of the helicoid ring with respect to the
stationary barrel at the wide-angle extremity of the zoom
15 lens;

Figure 29 is a view similar to that of Figure 27,
showing the positions of the set of rotational sliding
projections of the helicoid ring with respect to the
stationary barrel at the telephoto extremity of the zoom
20 lens;

Figure 30 is a view similar to that of Figure 27,
showing the positions of the set of rotational sliding
projections of the helicoid ring with respect to the
stationary barrel;

25 Figure 31 is a cross sectional view taken along M2-M2

line shown in Figure 27;

Figure 32 is a cross sectional view taken along M1-M1
line shown in Figure 23;

Figure 33 is an enlarged cross sectional view of a
5 portion of the upper half of the zoom lens shown in Figure
9;

Figure 34 is an enlarged cross sectional view of a
portion of the lower half of the zoom lens shown in Figure
9;

10 Figure 35 is an enlarged cross sectional view of a
portion of the upper half of the zoom lens shown in Figure
10;

Figure 36 is an enlarged cross sectional view of a
portion of the lower half of the zoom lens shown in Figure
15 10;

Figure 37 is an enlarged perspective view of a
portion of the connecting portion between the third
external barrel and the helicoid ring;

Figure 38 is a view similar to that of Figure 37,
20 showing a state where a stop member has been removed;

Figure 39 is a view similar to that of Figure 38,
showing a state where the third external barrel and the
helicoid ring have been disengaged from each other in the
optical axis direction from the state shown in Figure 38;

25 Figure 40 is a perspective view of a portion of the

stationary barrel, the stop member and a set screw therefor, showing a state where the stop member and the set screw have been removed from the stationary barrel;

Figure 41 is a perspective view similar to that shown in Figure 40, showing a state where the stop member is properly fixed the stationary barrel via the set screw;

Figure 42 is an enlarged developed view of a portion of helicoid ring in relation to a corresponding portion of the stationary barrel;

Figure 43 is a view similar to that of Figure 42, showing the positional relationship between the specific rotational sliding projection of the helicoid ring and the circumferential groove of the stationary barrel;

Figure 44 is a developed view of the third external barrel and the first linear guide ring in relation to a set of roller followers fixed to the cam ring, showing the positional relationship between the helicoid ring and the stationary barrel in the retracted state of the zoom lens;

Figure 45 is a view similar to that of Figure 44, showing the positional relationship between the helicoid ring and the stationary barrel at the wide-angle extremity of the zoom lens;

Figure 46 is a view similar to that of Figure 44, showing the positional relationship between the helicoid

ring and the stationary barrel at the telephoto extremity
of the zoom lens;

Figure 47 is a view similar to that of Figure 44,
showing the positional relationship between the helicoid
5 ring and the stationary barrel;

Figure 48 is a developed view of the helicoid ring
and the first linear guide ring, showing the positional
relationship therebetween in the retracted state of the
zoom lens;

10 Figure 49 is a view similar to that of Figure 48,
showing the positional relationship between the helicoid
ring and the first linear guide ring at the wide-angle
extremity of the zoom lens;

Figure 50 is a view similar to that of Figure 48,
15 showing the positional relationship between the helicoid
ring and the first linear guide ring at the telephoto
extremity of the zoom lens;

Figure 51 is a view similar to that of Figure 48,
showing the positional relationship between the helicoid
20 ring and the first linear guide ring;

Figure 52 is a developed view of the cam ring, the
first external barrel, the second external barrel and the
second linear guide ring, showing the positional
relationship thereamong in the retracted state of the zoom
25 lens;

Figure 53 is a view similar to that of Figure 52, showing the positional relationship among the cam ring, the first external barrel, the second external barrel and the second linear guide ring at the wide-angle extremity
5 of the zoom lens;

Figure 54 is a view similar to that of Figure 52, showing the positional relationship among the cam ring, the first external barrel, the second external barrel and the second linear guide ring at the telephoto extremity
10 of the zoom lens;

Figure 55 is a view similar to that of Figure 52, showing the positional relationship among the cam ring, the first external barrel, the second external barrel and the second linear guide ring;

15 Figure 56 is an exploded perspective view of elements of the zoom lens, showing a state where the third external barrel has been removed from the first linear guide ring;

Figure 57 is an exploded perspective view of
20 elements of the zoom lens, showing a state where the second external barrel and a follower-biasing ring spring have been removed from the block of the zoom lens shown in Figure 56;

Figure 58 is an exploded perspective view of
25 elements of the zoom lens, showing a state where the first

external barrel has been removed from the block of the zoom lens shown in Figure 57;

Figure 59 is an exploded perspective view of elements of the zoom lens, showing a state where the second
5 linear guide ring has been removed from the block of the zoom lens shown in Figure 58 while the set of roller followers have been removed from the cam ring included in the block;

Figure 60 is a developed view of the helicoid ring,
10 the third external barrel, the first linear guide ring and the follower-biasing ring spring in relation to the set of roller followers fixed to the cam ring, showing the positional relationship thereamong in the retracted state of the zoom lens;

15 Figure 61 is a view similar to that of Figure 60, showing the positional relationship among the helicoid ring, the third external barrel and the first linear guide ring at the wide-angle extremity of the zoom lens;

Figure 62 is a view similar to that of Figure 60,
20 showing the positional relationship among the helicoid ring, the third external barrel and the first linear guide ring at the telephoto extremity of the zoom lens;

Figure 63 is a view similar to that of Figure 60, showing the positional relationship among the helicoid
25 ring, the third external barrel and the first linear guide

ring;

Figure 64 is an enlarged developed view of portions of the third external barrel and the helicoid ring in relation to the set of roller followers fixed to the cam ring, viewed from radially inside the third external barrel and the helicoid ring;

Figure 65 is a view similar to that of Figure 64, showing a state where the helicoid ring is rotated in a lens barrel advancing direction thereof;

Figure 66 is an enlarged developed view of portions of the third external barrel and the helicoid ring shown in Figure 64;

Figure 67 is an enlarged developed view of portions of a front ring and a rear ring of a comparative example which are to be compared with the third external barrel and the helicoid ring shown in Figures 64 through 66;

Figure 68 is a view similar to that of Figure 67, showing a state where the rear ring has slightly rotated with respect to the front ring from the state shown in Figure 67;

Figure 69 is a magnified view of a part of the drawing shown in Figure 60 (Figure 44);

Figure 70 is a magnified view of a part of the drawing shown in Figure 61 (Figure 45);

Figure 71 is a magnified view of a part of the drawing

shown in Figure 62 (Figure 46);

Figure 72 is a magnified view of a part of the drawing shown in Figure 63 (Figure 47);

Figure 73 is an axial cross sectional view of an
5 upper half of elements of a linear guide structure of the zoom lens shown in Figures 5 and 10, showing the linear guide structure at the wide-angle extremity of the zoom lens;

Figure 74 is a view similar to that of Figure 73,
10 showing the linear guide structure at the wide-angle extremity of the zoom lens;

Figure 75 is a view similar to that of Figure 74, showing the linear guide structure in the retracted state of the zoom lens;

15 Figure 76 is a perspective view of a subassembly of the zoom lens shown in Figures 5 through 10 which includes the first external barrel, the external barrel, the second linear guide ring, the cam ring and other elements, showing the positional relationship between the first
20 external barrel and the second linear guide ring that are positioned radially inside and outside the cam ring, respectively;

Figure 77 is a perspective view of a subassembly of the zoom lens shown in Figures 5 through 10 which includes
25 all the elements shown in Figure 77 and the first linear

guide ring, showing a state where the first external barrel has been extended forward to its assembling/disassembling position;

Figure 78 is a perspective view of the subassembly shown in Figure 77, viewed obliquely from behind the subassembly;

Figure 79 is a developed view of the cam ring, the second lens group moving frame and the second linear guide ring, showing the positional relationship thereamong in the retracted state of the zoom lens;

Figure 80 is a view similar to that of Figure 79, showing the positional relationship among the cam ring, the second lens group moving frame and the second linear guide ring at the wide-angle extremity of the zoom lens;

Figure 81 is a view similar to that of Figure 79, showing the positional relationship among the cam ring, the second lens group moving frame and the second linear guide ring at the telephoto extremity of the zoom lens;

Figure 82 is a view similar to that of Figure 79, showing a positional relationship among the cam ring, the second lens group moving frame and the second linear guide ring;

Figure 83 is developed view of the cam ring, showing a state where a set of front cam followers of the second lens group moving frame pass through the points of

intersection between a set of front inner cam grooves and
a set of rear inner cam grooves of the cam ring;

Figure 84 is a perspective view of a portion of the
zoom lens shown in Figures 5 through 10 which includes
5 the second lens group moving frame, the second linear
guide ring, a shutter unit and other elements, viewed
obliquely from the front thereof;

Figure 85 is a perspective view of the portion of
the zoom lens in Figure 84, viewed obliquely from behind;

10 Figure 86 is a view similar to that of Figure 84,
showing the positional relationship between the second
lens group moving frame and the second linear guide ring
when the second lens group moving frame is positioned at
its front limit for the axial movement thereof with
15 respect to the second linear guide ring;

Figure 87 is a perspective view of the portion of
the zoom lens in Figure 86, viewed obliquely from behind;

Figure 88 is a front elevational view of the second
linear guide ring;

20 Figure 89 is a rear elevational view of the second
lens group moving frame, the second linear guide ring and
other elements in an assembled state thereof;

Figure 90 is a developed view of the first external
barrel and the cam ring in relation to a set of cam
25 followers of the first external barrel, showing the

positional relationship between the first external barrel and the cam ring in the retracted state of the zoom lens;

Figure 91 is a view similar to that of Figure 90, showing a state where each cam follower of the first external barrel is positioned at the insertion end of the inclined lead section of the associated outer cam groove of a set of outer cam grooves of the cam ring by a rotation of the cam ring in a lens barrel advancing direction thereof;

Figure 92 is a view similar to that of Figure 90, showing the positional relationship between the first external barrel and the cam ring at the wide-angle extremity of the zoom lens;

Figure 93 is a view similar to that of Figure 90, showing the positional relationship between the first external barrel and the cam ring at the telephoto extremity of the zoom lens;

Figure 94 is a view similar to that of Figure 90, showing a positional relationship between the first external barrel and the cam ring;

Figure 95 is a magnified view of a part of the drawing shown in Figure 90;

Figure 96 is a magnified view of a part of the drawing shown in Figure 91;

Figure 97 is view similar to those of Figures 95 and 96, showing a state where each cam follower of the first external barrel are positioned in the inclined lead section of the associated outer cam groove of the cam ring;

5 Figure 98 is a magnified view of a part of the drawing shown in Figure 92;

Figure 99 is a magnified view of a part of the drawing shown in Figure 93;

10 Figure 100 is a magnified view of a part of the drawing shown in Figure 94;

Figure 101 is a view similar to that of Figure 95, showing another embodiment of the structure of the set of outer cam grooves of the cam ring, showing the positional relationship between the first external barrel and the cam ring in the retracted state of the zoom lens;

Figure 102 is an exploded perspective view of a structure of the zoom lens for supporting a second lens frame which holds the second lens group, for retracting the second lens frame to a radially retracted position thereof, and for adjusting the position of the second lens frame;

Figure 103 is a perspective view of the structure for the second lens frame shown in Figure 102 in an assembled state and a position-control cam bar of a CCD

holder, viewed obliquely from the front;

Figure 104 is a perspective view of the structure for the second lens frame and the position-control cam bar shown in Figure 103, viewed obliquely from behind;

5 Figure 105 is a view similar to that of Figure 104, showing a state where the position-control cam bar is in the process of entering the cam-bar insertable hole of a rear second lens frame support plate fixed to the second lens group moving frame;

10 Figure 106 is a front elevational view of the second lens group moving frame;

Figure 107 is a perspective view of the second lens group moving frame;

15 Figure 108 is a perspective view of the second lens group moving frame and the shutter unit fixed thereto, viewed obliquely from front;

Figure 109 is a perspective view of the second lens group moving frame and the shutter unit shown in Figure 108, viewed obliquely from behind;

20 Figure 110 is a front elevational view of the second lens group moving frame and the shutter unit shown in Figure 108;

25 Figure 111 is a rear elevational view of the second lens group moving frame and the shutter unit shown in Figure 108;

Figure 112 is a view similar to that of Figure 111, showing a state where the second lens frame has retracted to the radially retracted position;

Figure 113 is a cross sectional view taken along
5 M3-M3 line shown in Figure 110;

Figure 114 is a front elevational view of the structure for the second lens frame shown in Figures 105 and 108 through 112, showing a state where the second lens frame is held at a photographing position thereof as shown
10 in Figure 110;

Figure 115 is a front elevational view of a portion of the structure for the second lens frame shown in Figure 114;

Figure 116 is a view similar to that of Figure 115
15 in a different state;

Figure 117 is a front elevational view of a portion of the structure for the second lens frame shown in Figures 105 and 108 through 116;

Figure 118 is a front elevational view of a portion
20 of the structure for the second lens frame shown in Figures 105 and 108 through 116, showing the positional relationship between the second lens frame and the position-control cam bar of the CCD holder when the second lens frame is held in a photographing position thereof
25 as shown in Figures 109 and 111;

Figure 119 is a view similar to that of Figure 118, showing a positional relationship between the second lens frame and the position-control cam bar of the CCD holder;

Figure 120 is a view similar to that of 118, showing
5 the positional relationship between the second lens frame and the position-control cam bar of the CCD holder when the second lens frame is held in the radially retracted position as shown in Figure 112;

Figure 121 is a perspective view of an AF lens frame
10 and the CCD holder shown in Figures 1 and 4, showing a state where the AF lens frame is fully retracted to contact with and the CCD holder, viewed obliquely from lower front of the CCD holder;

Figure 122 is a front elevational view of the CCD
15 holder, the AF lens frame and the second lens group moving frame;

Figure 123 is a perspective view of the CCD holder, the AF lens frame, the second lens group moving frame, the second lens frame and other elements;

20 Figure 124 is a view similar to that of Figure 123, showing a state where the second lens frame has fully moved rearward and fully rotated to the radially retracted position;

Figure 125 is an axial cross sectional view of a
25 portion of the upper half of the zoom lens shown in Figure

9, showing a structure wiring a flexible PWB for exposure control in the zoom lens;

Figure 126 is a perspective view of the second lens frame, the flexible PWB and other elements, showing a manner of supporting the flexible PWB by the second lens frame;

Figure 127 is a perspective view of the second lens frame and the AF lens frame, showing a state where the second lens frame has retracted closely to the AF lens frame;

Figure 128 is a side elevational view of the second lens frame and the AF lens frame, showing a state immediately before the second lens frame comes into contact with the AF lens frame;

Figure 129 is a view similar to that of Figure 128, showing a state where the second lens frame is in contact with the AF lens frame;

Figure 130 is a front elevational view of the second lens frame and the AF lens frame, showing a positional relationship therebetween;

Figure 131 is a perspective view of the first external barrel that surrounds the second lens group moving frame, and the first lens frame for the first lens group that is held by the first external barrel;

Figure 132 is a front elevational view of the first

external barrel and the first lens frame;

Figure 133 is a perspective view of the first lens frame, the second lens group moving frame, the AF lens frame and the shutter unit, viewed obliquely from front, showing the positional relationship thereamong at a ready-to-photograph state of the zoom lens;

Figure 134 is a perspective view of the first lens frame, the second lens group moving frame, the AF lens frame and the shutter unit which are shown in Figure 133, viewed obliquely from rear thereof;

Figure 135 is a view similar to that of Figure 133, showing the positional relationship among the first lens frame, the second lens group moving frame, the AF lens frame and the shutter unit, showing the positional relationship thereamong in the retracted state of the zoom lens;

Figure 136 is a perspective view of the first lens frame, the second lens group moving frame, the AF lens frame and the shutter unit which are shown in Figure 135, viewed obliquely from rear thereof;

Figure 137 is a rear elevational view of the first lens frame, the second lens group moving frame, the AF lens frame and the shutter unit which are shown in Figure 135;

Figure 138 is a perspective view, of the first lens

frame, the first external barrel, the second lens group
moving frame, the AF lens frame and the shutter unit in
the retracted state of the zoom lens, showing the
positional relationship thereamong in the retracted
5 state of the zoom lens;

Figure 139 is a front elevational view of the first
lens frame, the first external barrel, the second lens
group moving frame, the AF lens frame and the shutter unit
which are shown in Figure 138;

10 Figure 140 is an exploded perspective view of the
shutter unit of the zoom lens;

Figure 141 is a longitudinal cross sectional view
of a portion of the zoom lens in the vicinity of the first
lens group in the upper half of the zoom lens shown in
15 Figure 9, in which the zoom lens is in a ready-to-
photograph state;

Figure 142 is a view similar to that of Figure 141
and shows the same portion in the upper half of the zoom
lens shown in Figure 10, in which the zoom lens is in the
20 retracted state;

Figure 143 is an exploded perspective view of the
viewfinder unit shown in Figures 5 through 8;

Figure 144 is a developed view, similar to that of
Figure 23, of the helicoid ring and the third external
25 barrel in relation to a zoom gear and a viewfinder drive

gear, showing the positional relationship thereamong in the retracted state of the zoom lens;

Figure 145 is a developed view, similar to that of Figure 24, of the helicoid ring and the stationary barrel in relation to the zoom gear and the viewfinder drive gear, showing the positional relationship thereamong at the wide-angle extremity the zoom lens;

Figure 146 is a perspective view of a power transmission system of the zoom lens for imparting rotation of a zoom motor from the helicoid ring to movable lenses of a viewfinder optical system incorporated in the viewfinder unit;

Figure 147 is a front elevational view of the power transmission system shown in Figure 148;

Figure 148 is a side elevational view of the power transmission system shown in Figure 148;

Figure 149 is an enlarged developed view of the helicoid ring and the viewfinder drive gear, showing a positional relationship therebetween in the middle of rotation of the helicoid ring in the lens barrel advancing direction from the retracted position shown in Figure 144 to the wide-angle extremity shown in Figure 145.

Figure 150 is a view similar to that of Figure 149, showing a state subsequent to the state shown in Figure 149;

Figure 151 is a view similar to that of Figure 149, showing a state subsequent to the state shown in Figure 150;

Figure 152 is a view similar to that of Figure 149, showing a state subsequent to the state shown in Figure 151;

Figure 153 is a front elevational view of the helicoid ring and the viewfinder drive gear which are shown in Figure 150;

Figure 154 is a front elevational view of the helicoid ring and the viewfinder drive gear which are shown in Figure 151;

Figure 155 is a front elevational view of the helicoid ring and the viewfinder drive gear which are shown in Figure 152;

Figure 156 is a developed view of a cam-incorporated gear of the viewfinder unit; and

Figure 157 is a developed view, similar to that of Figure 156, of a comparative example of a cam-incorporated gear incorporating an idle running section which is to be compared with the cam-incorporated gear shown in Figure 156.

DESCRIPTION OF THE PREFERRED EMBODIMENT

In some of the drawings, lines of different

thicknesses and/or different types of lines are used as the outlines of different elements for the purpose of illustration. Additionally, in some cross sectional drawings, several elements are shown on a common plane, though positioned in different circumferential positions, for the purpose of illustration.

In Figure 22, the symbols "(S)", "(L)", "(R)" and "(RL)" which are each appended as a suffix to the reference numeral of some elements of a present embodiment of a zoom lens (zoom lens barrel) 71 (see Figures 5 through 10) indicate that the element is stationary, the element is solely movable linearly along a lens barrel axis Z0 (see Figures 9 and 10) without rotating about the lens barrel axis Z0, the element is rotatable about the lens barrel axis Z0 without moving along the lens barrel axis Z0, and the element is solely movable along the lens barrel axis Z0 while rotating about the lens barrel axis Z0, respectively. Additionally, in Figure 22, the symbol "(R, RL)" which is appended as a suffix to the reference numeral of some elements of the zoom lens 71 indicates that the element rotates about the lens barrel axis Z0 without moving along the lens barrel axis Z0 during a zooming operation and that the element moves along the lens barrel axis Z0 while rotating about the lens barrel axis Z0 during the time the zoom lens 71 advances from or retracts into

a camera body 72 upon power being turned ON or OFF, while the symbol "(S, L)" which is appended as a suffix to the reference numeral of some elements of the zoom lens 71 indicates that the element is stationary when the zoom lens 71 in a zooming range in which a zooming operation is possible and that the element moves linearly along the lens barrel axis Z0 without rotating about the lens barrel axis Z0 during the time the zoom lens 71 advances from or retracts into the camera body 72 upon power being turned ON or OFF.

As shown in Figures 9 and 10, the present embodiment of the zoom lens 71 incorporated in a digital camera 70 is provided with a photographing optical system consisting of a first lens group LG1, a shutter S, an adjustable diaphragm A, a second lens group LG2, a third lens group LG3, a low-pass filter (optical filter) LG4, and a CCD image sensor (solid-state image pick-up device) 60. "Z1" shown in Figures 9 and 10 designates the optical axis of the photographing optical system. The photographing optical axis Z1 is parallel to a common rotational axis (the lens barrel axis Z0) of external barrels which form an outward appearance of the zoom lens 71. Moreover, the photographing optical axis Z1 is positioned below the lens barrel axis Z0. The first lens group LG1 and the second lens group LG2 are driven along

the photographing optical axis Z1 in a predetermined moving manner to perform a zooming operation, while the third lens group L3 is driven along the photographing optical axis Z1 to perform a focusing operation. In the following descriptions, the term "optical axis direction" means a direction parallel to the photographing optical axis Z1 unless there is a different explanatory note on the expression.

As shown in Figures 9 and 10, the camera 70 is provided in the camera body 72 thereof with a stationary barrel 22 fixed to the camera body 72, and a CCD holder 21 fixed to a rear portion of the stationary barrel 22. The CCD image sensor 60 is mounted to the CCD holder 21 to be held thereby via a CCD base plate 62. The low-pass filter LG4 is held by the CCD holder 21 to be positioned in front of the CCD 60 via a filter holder portion 21b and an annular sealing member 61. The filter holder portion 21b is a portion formed integrally with the CCD holder 21. The camera 70 is provided behind the CCD holder 21 with an LCD panel 20 which indicates a live image so that the user can see how the image about to be taken looks before photographing, captured images so that the user can review pictures which he or she has already taken, and also various photographing information.

The zoom lens 71 is provided in the stationary barrel

22 with an AF lens frame (a third lens frame which supports and holds the third lens group LG3) 51 which is guided linearly in the optical axis direction without rotating about the photographing optical axis Z1. Specifically, the zoom lens 71 is provided with a pair of AF guide shafts 52 and 53 which extend parallel to the photographing optical axis Z1 to guide the AF lens frame 51 in the optical axis direction without rotating the AF lens frame 51 about the photographing optical axis Z1. Front and rear ends of each guide shaft of the pair of AF guide shafts 52 and 53 are fixed to the stationary barrel 22 and the CCD holder 21, respectively. The AF lens frame 51 is provided on radially opposite sides thereof with a pair of guide holes 51a and 51b in which the pair of AF guide shafts 52 and 53 are respectively fitted so that the AF lens frame 51 is slidable on the pair of AF guide shafts 52 and 53. In this particular embodiment, the amount of clearance between the AF guide shaft 53 and the guide hole 51b is greater than that between the AF guide shaft 52 and the guide hole 51a. Namely, the AF guide shaft 52 serves as a main guide shaft for achieving a great positioning accuracy, while the AF guide shaft 53 serves as an auxiliary guide shaft. The camera 70 is provided with an AF motor 160 (see Figure 1) having a rotary drive shaft which is threaded to serve as a feed screw shaft, and this

rotary drive shaft is screwed through a screw hole formed on an AF nut 54 (see Figure 1). The AF nut 54 is provided with a rotation-preventing protrusion 54a. The AF lens frame 51 is provided with a guide groove 51m (see Figure 5 127), extending in a direction parallel to the optical axis Z1, in which the rotation-preventing protrusion 54a is slidably fitted. Furthermore, the AF lens frame 51 is provided with a stopper protrusion 51n (see Figure 127) which is positioned behind the AF nut 54. The AF lens 10 frame 51 is biased forward in the optical axis direction by an extension coil spring 55 serving as a biasing member, and the forward movement limit of the AF lens frame 51 is determined via engagement between the stopper protrusion 51n and the AF nut 54. The AF lens frame 51 15 can be moved rearward against the biasing force of the extension coil spring 55 when a rearward force is applied by the AF nut 54. Due to this structure, rotating the rotary drive shaft of AF motor 160 forward and rearward causes the AF lens frame 51 to move forward and rearward 20 in the optical axis direction. In addition, the AF lens frame 51 can be moved rearward against the biasing force of the extension coil spring 55 when a rearward force is directly applied to the AF lens frame 51.

As shown in Figures 5 and 6, the camera 70 is provided 25 above the stationary barrel 22 with a zoom motor 150 and

a reduction gear train box 74 which are mounted on the stationary barrel 22. The reduction gear train box 74 contains a reduction gear train for transferring rotation of the zoom motor 150 to a zoom gear 28 (see Figure 4).
5 The zoom gear 28 is rotatably fitted on a zoom gear shaft 29 extending parallel to the photographing optical axis Z1. Front and rear ends of the zoom gear shaft 29 are fixed to the stationary barrel 22 and the CCD holder 21, respectively. Rotations of the zoom motor 150 and the
10 AF motor 160 are controlled by a control circuit 140 (see Figure 22) via a flexible PWB (printed wiring board) 75 which is partly positioned on an outer peripheral surface of the stationary barrel 22. The control circuit 140 comprehensively controls the overall operation of the
15 camera 70.

As shown in Figure 4, the stationary barrel 22 is provided on an inner peripheral surface thereof with a female helicoid 22a, a set of three linear guide grooves 22b, a set of three inclined grooves 22c, and a set of
20 three rotational sliding grooves 22d. Threads of the female helicoid 22a extend in a direction inclined with respect to both the optical axis direction and a circumferential direction of the stationary barrel 22. The set of three linear guide grooves 22b extend parallel
25 to the photographing optical axis Z1. The set of three

inclined grooves 22c extend parallel to the female helicoid 22a. The set of three rotational sliding grooves 22d are formed in the vicinity of a front end of the inner peripheral surface of the stationary barrel 22 to extend along a circumference of the stationary barrel 22 to communicate the front ends of the set of three inclined grooves 22c, respectively. The female helicoid 22a is not formed on that specific front area (non-helicoid area 22z) of the inner peripheral surface of the stationary barrel 22 which is positioned immediately behind the set of three rotational sliding grooves 22d (see Figures 11, 23 through 26).

The zoom lens 71 is provided in the stationary barrel 22 with a helicoid ring 18. The helicoid ring 18 is provided on an outer peripheral surface thereof with a male helicoid 18a and a set of three rotational sliding projections 18b. The male helicoid 18a is engaged with the female helicoid 22a, and the set of three rotational sliding projections 18b are engaged in the set of three inclined grooves 22c or the set of three rotational sliding grooves 22d, respectively (see Figures 4 and 12). The helicoid ring 18 is provided on threads of the male helicoid 18a with an annular gear 18c which is in mesh with the zoom gear 28. Therefore, when a rotation of the zoom gear 28 is transferred to the annular gear 18c, the

helicoid ring 18 moves forward or rearward in the optical axis direction while rotating about the lens barrel axis Z0 within a predetermined range in which the male helicoid 18a remains in mesh with the female helicoid 22a. A
5 forward movement of the helicoid ring 18 beyond a predetermined point with respect to the stationary barrel 22 causes the male helicoid 18a to be disengaged from the female helicoid 22a so that the helicoid ring 18 rotates about the lens barrel axis Z0 without moving in the optical
10 axis direction relative to the stationary barrel 22 by engagement of the set of three rotational sliding projections 18b with the set of three rotational sliding grooves 22d.

The set of three inclined grooves 22c are formed on
15 the stationary barrel 22 to prevent the set of three rotational sliding projections 18b and the stationary barrel 22 from interfering with each other when the female helicoid 22a and the male helicoid 18a are engaged with each other. To this end, each inclined groove 22c is
20 formed on an inner peripheral surface of the stationary barrel 22 to be positioned radially outwards (upwards as viewed in Figure 31) from the bottom of the female helicoid 22a as shown in Figure 31. A circumferential space between two adjacent threads of the female helicoid 22a
25 between which one of the three inclined grooves 22c is

positioned is greater than that between another two adjacent threads of the female helicoid 22a between which none of the three inclined grooves 22c is positioned. The male helicoid 18a includes three wide threads 18a-W and
5 twelve narrow threads. The three wide threads 18a-W are positioned behind the three rotational sliding projections 18b in the optical axis direction, respectively (see Figure 12). The circumferential width of each of the three wide threads 18a-W is greater than
10 that of each of the twelve narrow threads so that each of the three wide threads 18a-W can be positioned in the associated two adjacent threads of the female helicoid 22a between which one of the three inclined grooves 22c is positioned (see Figures 11 and 12).

15 The stationary barrel 22 is provided with a stop-member insertion hole 22e which radially penetrates through the stationary barrel 22. A stop member 26 having a stop projection 26b is fixed to the stationary barrel 22 by a set screw 67 so that the stop projection 26b can
20 be inserted into and removed from the stop-member insertion hole 22e (see Figures 40 and 41).

As will be appreciated from Figures 9 and 10, the zoom lens 71 of the camera 70 is of a telescoping type having three external telescoping barrels: a first
25 external barrel 12, a second external barrel 13 and a third

external barrel 15 which are concentrically arranged about the lens barrel axis Z0. The helicoid ring 18 is provided, on an inner peripheral surface thereof at three different circumferential positions on the helicoid ring 18, with three rotation transfer recesses 18d (see Figures 4 and 13) front ends of which are open at the front end of the helicoid ring 18, while the third external barrel 15 is provided, at corresponding three different circumferential positions on the third external barrel 15, with three pairs of rotation transfer projections 15a (see Figures 4 and 14) which project rearward from the rear end of the third external barrel 15 to be inserted into the three rotation transfer recesses 18d from the front thereof, respectively. The three pairs of rotation transfer projections 15a and the three rotation transfer recesses 18d are movable relative to each other in a direction of the lens barrel axis Z0, and are not rotatable relative to each other about the lens barrel axis Z0. Namely, the helicoid ring 18 and the third external barrel 15 rotate in one piece. Strictly speaking, the three pairs of rotation transfer projections 15a and the three rotation transfer recesses 18d are slightly rotatable relative to each other about the lens barrel axis Z0 by the amount of clearance between the three pairs of rotation transfer projections 15a and the three rotation

transfer recesses 18d, respectively. This structure will be discussed in detail later.

The helicoid ring 18 is provided, on front faces of the three rotational sliding projections 18b at three
5 different circumferential positions on the helicoid ring 18, with a set of three engaging recesses 18e which are formed on an inner peripheral surface of the helicoid ring 18 to be open at the front end of the helicoid ring 18. The third external barrel 15 is provided, at corresponding
10 three different circumferential positions on the third external barrel 15, with a set of three engaging projections 15b which project rearward from the rear end of the third external barrel 15, and also project radially outwards, to be engaged in the set of three engaging
15 recesses 18e from the front thereof, respectively. The set of three engaging projections 15b, which are respectively engaged in the set of three engaging recesses 18e, are also engaged in the set of three rotational sliding grooves 22d at a time, respectively, when the set
20 of three rotational sliding projections 18b are engaged in the set of three rotational sliding grooves 22d (see Figure 33).

The zoom lens 71 is provided between the third external barrel 15 and the helicoid ring 18 with three
25 compression coil springs 25 which bias the third external

barrel 15 and the helicoid ring 18 in opposite directions away from each other in the optical axis direction. The rear ends of the three compression coil springs 25 are respectively inserted into three spring support holes (non-through hole) 18f which are formed on the front end of the helicoid ring 18, while the front ends of the three compression coil springs 25 are respectively in pressing contact with three engaging recesses 15c formed at the rear end of the third external barrel 15. Therefore, the set of three engaging projections 15b of the third external barrel 15 are respectively pressed against front guide surfaces 22d-A (see Figures 28 through 30) of the rotational sliding grooves 22d by the spring force of the three compression coil springs 25. At the same time, the set of three rotational sliding projections 18b of the helicoid ring 18 are respectively pressed against rear guide surfaces 22d-B (see Figures 28 through 30) of the rotational sliding grooves 22d by the spring force of the three compression coil springs 25.

20 The third external barrel 15 is provided on an inner peripheral surface thereof with a plurality of relative rotation guide projections 15d which are formed at different circumferential positions on the third external barrel 15, a circumferential groove 15e which extends in a circumferential direction about the lens

barrel axis Z0, and a set of three rotation transfer grooves 15f which extend parallel to the lens barrel axis Z0 (see Figures 4 and 14). The plurality of relative rotation guide projections 15d are elongated in a circumferential direction of the third external barrel to lie in a plane orthogonal to the lens barrel axis Z0. As can be seen in Figure 14, each rotation transfer groove 15f intersects the circumferential groove 15e at right angles. The circumferential positions of the three rotation transfer grooves 15f are formed to correspond to those of the three pairs of rotation transfer projections 15a, respectively. The rear end of each rotation transfer groove 15f is open at the rear end of the third external barrel 15. The helicoid ring 18 is provided on an inner peripheral surface thereof with a circumferential groove 18g which extends in a circumferential direction about the lens barrel axis Z0 (see Figures 4 and 13). The zoom lens 71 is provided inside the third external barrel 15 and the helicoid ring 18 with a first linear guide ring 14. The first linear guide ring 14 is provided on an outer peripheral surface thereof with a set of three linear guide projections 14a, a first plurality of relative rotation guide projections 14b, a second plurality of relative rotation guide projections 14c, and a circumferential groove 14d in this

order from rear to front of the first linear guide ring 14 in the optical axis direction (see Figures 4 and 15). The set of three linear guide projections 14a project radially outwards in the vicinity of the rear end of the first linear guide ring 14. The first plurality of relative rotation guide projections 14b project radially outwards at different circumferential positions on the first linear guide ring 14, and are each elongated in a circumferential direction of the first linear guide ring 14 to lie in a plane orthogonal to the lens barrel axis Z0. Likewise, the second plurality of relative rotation guide projections 14c project at different circumferential positions on the first linear guide ring 14, and are each elongated in a circumferential direction of the first linear guide ring 14 to lie in a plane orthogonal to the lens barrel axis Z0. The circumferential groove 14d is an annular groove with its center on the lens barrel axis Z0. The first linear guide ring 14 is guided in the optical axis direction with respect to the stationary barrel 22 by engagement of the set of three linear guide projections 14a with the set of three linear guide grooves 22b, respectively. The third external barrel 15 is coupled to the first linear guide ring 14 to be rotatable about the lens barrel axis Z0 relative to the first linear guide ring 14 by both the

engagement of the second plurality of relative rotation guide projections 14c with the circumferential groove 15e and the engagement of the plurality of relative rotation guide projections 15d with the circumferential groove 14d.

5 The second plurality of relative rotation guide projections 14c and the circumferential groove 15e are engaged with each other to be slightly movable relative to each other in the optical axis direction. Likewise, the plurality of relative rotation guide projections 15d

10 and the circumferential groove 14d are engaged with each other to be slightly movable relative to each other in the optical axis direction. The helicoid ring 18 is coupled to the first linear guide ring 14 to be rotatable about the lens barrel axis Z0 relative to the first linear

15 guide ring 14 by engagement of the first plurality of relative rotation guide projections 14b with the circumferential groove 18g. The first plurality of relative rotation guide projections 14b and the circumferential groove 18g are engaged with each other

20 to be slightly movable relative to each other in the optical axis direction.

The first linear guide ring 14 is provided with a set of three through-slots 14e which radially penetrate the first linear guide ring 14. As shown in Figure 15,

25 each through-slot 14e includes a front circumferential

slot portion 14e-1, a rear circumferential slot portion 14e-2, and an inclined lead slot portion 14e-3 which connects the front circumferential slot portion 14e-1 with the rear circumferential slot portion 14e-2. The front circumferential slot portion 14e-1 and the rear circumferential slot portion 14e-2 extend parallel to each other in a circumferential direction of the first linear guide ring 14. The zoom lens 71 is provided with a cam ring 11 a front portion of which is positioned inside the first external barrel 12. A set of three roller followers 32 fixed to an outer peripheral surface of the cam ring 11 at different circumferential positions thereon are engaged in the set of three through-slots 14e, respectively (see Figure 3). Each roller follower 32 is fixed to the cam ring 11 by set screw 32a. The set of three roller followers 32 are further engaged in the set of three rotation transfer grooves 15f through the set of three through-slots 14e, respectively. The zoom lens 71 is provided between the first linear guide ring 14 and the third external barrel 15 with a follower-biasing ring spring 17. A set of three follower pressing protrusions 17a protrude rearward from the follower-biasing ring spring 17 to be engaged in front portions of the set of three rotation transfer grooves 15f, respectively (see Figure 14). The set of three follower pressing

protrusions 17a press the set of three roller followers 32 rearward to remove backlash between the set of three roller followers 32 and the set of three through-slots 14e when the set of three roller followers 32 are engaged in the front circumferential slot portions 14e-1 of the set of three through-slots 14e, respectively.

Advancing operations of movable elements of the zoom lens 71 from the stationary barrel 22 to the cam ring 11 will be discussed hereinafter with reference to the above described structure of the digital camera 70. Rotating the zoom gear 28 in a lens barrel advancing direction by the zoom motor 150 causes the helicoid ring 18 to move forward while rotating about the lens barrel axis Z0 due to engagement of the female helicoid 22a with the male helicoid 18a. This rotation of the helicoid ring 18 causes the third external barrel 15 to move forward together with the helicoid ring 18 while rotating about the lens barrel axis Z0 together with the helicoid ring 18, and further causes the first linear guide ring 14 to move forward together with the helicoid ring 18 and the third external barrel 15 because each of the helicoid ring 18 and the third external barrel 15 is coupled to the first linear guide ring 14 to make respective relative rotations between the third external barrel 15 and the first linear guide ring 14 and between the helicoid ring 18 and the

first linear guide ring 14 possible and to be movable together along a direction of a common rotational axis (i.e., the lens barrel axis Z0) due to the engagement of the first plurality of relative rotation guide
5 projections 14b with the circumferential groove 18g, the engagement of the second plurality of relative rotation guide projections 14c with the circumferential groove 15e and the engagement of the plurality of relative rotation guide projections 15d with the circumferential groove 14d.
10 Rotation of the third external barrel 15 is transferred to the cam ring 11 via the set of three rotation transfer grooves 15f and the set of three roller followers 32, which are engaged in the set of three rotation transfer grooves 15f, respectively. Since the set of three roller
15 followers 32 are also engaged in the set of three through-slots 14e, respectively, the cam ring 11 moves forward while rotating about the lens barrel axis Z0 relative to the first linear guide ring 14 in accordance with contours of the lead slot portions 14e-3 of the set
20 of three through-slots 14e. Since the first linear guide ring 14 itself moves forward together with the third lens barrel 15 and the helicoid ring 18 as described above, the cam ring 11 moves forward in the optical axis direction by an amount of movement corresponding to the sum of the
25 amount of the forward movement of the first linear guide

ring 14 and the amount of the forward movement of the cam ring 11 by engagement of the set of three roller followers 32 with the lead slot portions 14e-3 of the set of three through-slots 14e, respectively.

5 The above described rotating-advancing operations of the cam ring 11, the third external barrel 15 and the helicoid ring 18 are performed while the set of three rotational sliding projections 18b are moving in the set of three inclined grooves 22c, respectively, only when
10 the male helicoid 18a and the female helicoid 22a are engaged with each other. When the helicoid ring 18 moves forward by a predetermined amount of movement, the male helicoid 18a and the female helicoid 22a are disengaged from each other so that the set of three rotational sliding
15 projections 18b move from the set of three inclined grooves 22c to the set of three rotational sliding grooves 22d, respectively. Since the helicoid ring 18 does not move in the optical axis direction relative to the stationary barrel 22 even if rotating upon the
20 disengagement of the male helicoid 18a from the female helicoid 22a, the helicoid ring 18 and the third external barrel 15 rotate at respective axial fixed positions thereof without moving in the optical axis direction due to the engagement of the set of three rotational sliding
25 projections 18b with the set of three rotational sliding

grooves 22d. Furthermore, at substantially the same time when the set of three rotational sliding projections 18b slide into the set of three rotational sliding grooves 22d from the set of three inclined grooves 22c, respectively, the set of three roller followers 32 enter the front circumferential slot portions 14e-1 of the set of three through-slots 14e, respectively. In this state, since the first linear guide ring 14 stops while the set of three roller followers 32 have respectively moved into the front circumferential slot portions 14e-1, the cam ring 11 is not given any force to make the cam ring 11 move forward. Consequently, the cam ring 11 only rotates at an axial fixed position in accordance with rotation of the third external barrel 15.

Rotating the zoom gear 28 in a lens barrel retracting direction thereof by the zoom motor 150 causes the aforementioned movable elements of the zoom lens 71 from the stationary barrel 22 to the cam ring 11 to operate in the reverse manner to the above described advancing operations. In this reverse operation, the above described movable elements of the zoom lens 71 retract to their respective retracted positions shown in Figure 10 by rotation of the helicoid ring 18 until the set of three roller followers 32 enter the rear circumferential slot portions 14e-2 of the set of three through-slots 14e,

respectively.

The first linear guide ring 14 is provided on an inner peripheral surface thereof with a set of three pairs of first linear guide grooves 14f which are formed at
5 different circumferential positions to extend parallel to the photographing optical axis Z1, and a set of six second linear guide grooves 14g which are formed at different circumferential positions to extend parallel to the photographing optical axis Z1. Each pair of first
10 linear guide grooves 14f are positioned on the opposite sides of the associated linear guide groove 14g (every other linear guide groove 14g) in a circumferential direction of the first linear guide ring 14. The zoom lens 71 is provided inside the first linear guide ring
15 14 with a second linear guide ring 10. The second linear guide ring 10 is provided on an outer edge thereof with a set of three bifurcated projections 10a which project radially outwards from a ring portion 10b of the second linear guide ring 10. Each bifurcated projection 10a is
20 provided at a radially outer end thereof with a pair of radial projections which are respectively engaged in the associated pair of first linear guide grooves 14f (see Figures 3 and 18). On the other hand, a set of six radial projections 13a which are formed on an outer peripheral
25 surface of the second external barrel 13 at a rear end

thereof to project radially outwards (see Figure 3) are engaged in the set of six second linear guide grooves 14g, respectively to be slidable therealong. Therefore, each of the second external barrel 13 and the second linear guide ring 10 is guided in the optical axis direction via the first linear guide ring 14.

The zoom lens 71 is provided inside the cam ring 11 with a second lens group moving frame 8 which indirectly supports and holds the second lens group LG2 (see Figure 3). The first external barrel 12 indirectly supports the first lens group LG1, and is positioned inside the second external barrel 13 (see Figure 2). The second linear guide ring 10 serves as a linear guide member for guiding the second lens group moving frame 8 linearly without rotating the same, while the second external barrel 13 serves as a linear guide member for guiding the first external barrel 12 linearly without rotating the same.

The second linear guide ring 10 is provided on the ring portion 10b with a set of three linear guide keys 10c (specifically two narrow linear guide keys 10c and a wide linear guide key 10c-W) which project forward in parallel to one another (see Figures 3 and 18) from the ring portion 10b. The second lens group moving frame 8 is provided with a corresponding set of three guide grooves 8a (specifically two narrow guide grooves 8a and

a wide guide groove 8a-W) in which the set of three linear guide keys 10c are engaged, respectively. As shown in Figures 9 and 10, a discontinuous outer edge of the ring portion 10b is engaged in a discontinuous circumferential groove 11e formed on an inner peripheral surface of the cam ring 11 at the rear end thereof to be rotatable about the lens barrel axis Z0 relative to the cam ring 11 and to be immovable relative to the cam ring 11 in the optical axis direction. The set of three linear guide keys 10c project forward from the ring portion 10b to be positioned inside the cam ring 11. Opposite edges of each linear guide key 10c in a circumferential direction of the second linear guide ring 10 serve as parallel guide edges which are respectively engaged with circumferentially-opposed guide surfaces in the associated guide groove 8a of the second lens group moving frame 8, which is positioned in the cam ring 11 to be supported thereby, to guide the second lens group moving frame 8 linearly in the optical axis direction without rotating the same about the lens barrel axis Z0.

The wide linear guide key 10c-W has a circumferential width greater than those of the other two linear guide keys 10c to also serve as a support member for supporting a flexible PWB (printed wiring board) 77 (see Figures 84 through 87) used for exposure control.

The wide linear guide key 10c-W is provided thereon with a radial through hole 10d through which the flexible PWB 77 passes (see Figure 18). A portion of the ring portion 10b from which the wide linear guide key 10c-W projects forward is partly cut out so that the rear end of the radial through hole 10d extends through the rear end of the ring portion 10b. As shown in Figures 9 and 125, the flexible PWB 77 for exposure control passes through the radial through hole 10d to extend forward along an outer surface of the wide linear guide key 10c-W from the rear of the ring portion 10b, and subsequently bends radially inwards in the vicinity of the front end of the wide linear guide key 10c-W to extend rearward along an inner surface of the wide linear guide key 10c-W. The wide guide groove 8a-W has a circumferential width greater than those of the other two guide grooves 8a so that the wide linear guide key 10c-W can be engaged in the wide guide groove 8a-W to be slidable therealong. As can be clearly seen in Figure 19, the second lens group moving frame 8 is provided in the wide guide groove 8a-W with a radial recess 8a-Wa in which the flexible PWB 77 can lie and two separate bottom walls 8a-Wb positioned on opposite sides of the radial recess 8a-Wa to support the wide linear guide key 10c-W thereon. Whereas, each of the other two guide grooves 8a is formed as a simple bottomed groove that is

formed on an outer peripheral surface of the second lens group moving frame 8. The second lens group moving frame 8 and the second linear guide ring 10 can be coupled to each other only when the wide linear guide key 10c-W and the wide guide groove 8a-W are aligned in the direction of the lens barrel axis Z0.

The cam ring 11 is provided on an inner peripheral surface thereof with a plurality of inner cam grooves 11a for moving the second lens group LG2. As shown in Figure 17, the plurality of inner cam grooves 11a are composed of a set of three front inner cam grooves 11a-1 formed at different circumferential positions, and a set of three rear inner cam grooves 11a-2 formed at different circumferential positions behind the set of three front inner cam grooves 11a-1. Each rear inner cam groove 11a-2 is formed on the cam ring 11 as a discontinuous cam groove (see Figure 17), the detail thereof will be discussed later.

The second lens group moving frame 8 is provided on an outer peripheral surface thereof with a plurality of cam followers 8b. As shown in Figure 19, the plurality of cam followers 8b include a set of three front cam followers 8b-1 which are formed at different circumferential positions to be respectively engaged in the set of three front inner cam grooves 11a-1, and a set

of three rear cam followers 8b-2 which are formed at different circumferential positions behind the set of three front cam followers 8b-1 to be respectively engaged in the set of three rear inner cam grooves 11a-2.

5 A rotation of the cam ring 11 causes the second lens group moving frame 8 to move in the optical axis direction in a predetermined moving manner in accordance with contours of the plurality of inner cam grooves 11a since the second lens group moving frame 8 is guided linearly
10 in the optical axis direction without rotating via the second linear guide ring 10.

 The zoom lens 71 is provided inside the second lens group moving frame 8 with a second lens frame (radially-retractable lens frame) 6 which supports and
15 holds the second lens group LG2. The second lens frame 6 is pivoted on a pivot shaft 33 front and rear ends of which are supported by front and rear second lens frame support plates (a pair of second lens frame support
20 plates) 36 and 37, respectively (see Figures 3 and 102 through 105). The pair of second lens frame support plates 36 and 37 are fixed to the second lens group moving frame 8 by a set screw 66. The pivot shaft 33 is a
25 predetermined distance away from the photographing optical axis Z1, and extends parallel to the photographing optical axis Z1. The second lens frame 6 is swingable

about the pivot shaft 33 between a photographing position shown in Figure 9 where the optical axis of the second lens group LG2 coincides with the photographing optical axis Z1 and a radially retracted position (retracted away from the optical axis) shown in Figure 10 where the optical axis of the second lens group LG2 is eccentric from the photographing optical axis Z1. A rotation limit shaft 35 which determines the photographing position of the second lens frame 6 is mounted to the second lens group moving frame 8. The second lens frame 6 is biased to rotate in a direction to come into contact with the rotation limit shaft 35 by a front torsion coil spring 39. A compression coil spring 38 is fitted on the pivot shaft 33 to remove backlash of the second lens frame 6 in the optical axis direction.

The second lens frame 6 moves together with the second lens group moving frame 8 in the optical axis direction. The CCD holder 21 is provided on a front surface thereof with a position-control cam bar 21a which projects forward from the CCD holder 21 to be engageable with the second lens frame 6 (see Figure 4). If the second lens group moving frame 8 moves rearward in a retracting direction to approach the CCD holder 21, a retracting cam surface 21c (see Figure 103) formed on a front end surface of the position-control cam bar 21a comes into contact

with a specific portion of the second lens frame 6 to rotate the second lens frame 6 to the radially retracted position.

The second external barrel 13 is provided, on an inner peripheral surface thereof, with a set of three linear guide grooves 13b which are formed at different circumferential positions to extend parallel to one another in the optical axis direction. The first external barrel 12 is provided on an outer peripheral surface at the rear end thereof with a set of three engaging protrusions 12a which are slidably engaged in the set of three linear guide grooves 13b, respectively (see Figures 2, 20 and 21). Accordingly, the first external barrel 12 is guided linearly in the optical axis direction without rotating about the lens barrel axis Z0 via the first linear guide ring 14 and the second external barrel 13. The second external barrel 13 is further provided on an inner peripheral surface thereof in the vicinity of the rear end of the second external barrel 13 with a discontinuous inner flange 13c which extends along a circumference of the second external barrel 13. The cam ring 11 is provided on an outer peripheral surface thereof a discontinuous circumferential groove 11c in which the discontinuous inner flange 13c is slidably engaged so that the cam ring 11 is rotatable about the

lens barrel axis Z0 relative to the second external barrel 13 and so that the second external barrel 13 is immovable in the optical axis direction relative to the cam ring 11. On the other hand, the first external barrel 12 is
5 provided on an inner peripheral surface thereof with a set of three cam followers 31 which projects radially inwards, while the cam ring 11 is provided on an outer peripheral surface thereof with a set of three outer cam grooves 11b (cam grooves for moving the first lens group
10 LG1) in which the set of three cam followers 31 are slidably engaged, respectively.

The zoom lens 71 is provided inside the first external barrel 12 with a first lens frame 1 which is supported by the first external barrel 12 via a first lens
15 group adjustment ring 2. The first lens group LG1 is supported by the first lens frame 1 to be fixed thereto. The first lens frame 1 is provided on an outer peripheral surface thereof with a male screw thread 1a, and the first lens group adjustment ring 2 is provided on an inner
20 peripheral surface thereof with a female screw thread 2a which is engaged with the male screw thread 1a. The axial position of the first lens frame 1 relative to the first lens group adjustment ring 2 can be adjusted via the male screw thread 1a and the female screw thread 2a. A
25 combination of the first lens frame 1 and the first lens

group adjustment ring 2 is positioned inside the first external barrel 12 to be supported thereby and to be movable in the optical axis direction relative to the first external barrel 12. The zoom lens 71 is provided
5 in front of the first external barrel 12 with a fixing ring 3 which is fixed to the first external barrel 12 by two set screws 64 to prevent the first lens group adjustment ring 2 from moving forward and coming off the first external barrel 12.

10 The zoom lens 71 is provided between the first and second lens groups LG1 and LG2 with a shutter unit 76 including the shutter S and the adjustable diaphragm A (see Figures 1, 9 and 10). The shutter unit 76 is positioned in the second lens group moving frame 8 to be
15 supported thereby. The air-distance between the shutter S and the second lens group LG2 is fixed. Likewise, the air-distance between the diaphragm A and the second lens group LG2 is fixed. The zoom lens 71 is provided in front of the shutter unit 76 with a shutter actuator 131 for
20 driving the shutter S, and is provided behind the shutter unit 76 with a diaphragm actuator 132 for driving the diaphragm A (see Figures 140). The flexible PWB 77 extends from the shutter unit 76 to establish electrical connection between the control circuit 140 and each of
25 the shutter actuator 131 and the diaphragm actuator 132.

Note that, in Figure 9, the flexible PWB 77 is shown in a cross sectional view of a lower half portion of the zoom lens 71 below the photographing optical axis Z1 (the zoom lens 71 set at wide-angle extremity) for the purpose of making the relative locations between the flexible PWB 77 and peripheral elements clearly understandable though the flexible PWB 77 is actually disposed only in the space above the photographing optical axis Z1 in the zoom lens 71.

10 The zoom lens 71 is provided at the front end of the first external barrel 12 with a lens barrier mechanism which automatically closes a front end aperture of the zoom lens 71 when the zoom lens 71 is retracted into the camera body 72 to protect the frontmost lens element of the photographing optical system of the zoom lens 71, i.e. the first lens group LG1, from getting stains and scratches thereon when the digital camera 70 is not in use. As shown in Figures 1, 9 and 10, the lens barrier mechanism is provided with a pair of barrier blades 104 and 105. The pair of barrier blades 104 and 105 are rotatable about two pivots projecting rearward therefrom to be positioned on radially opposite sides of the photographing optical axis Z1, respectively. The lens barrier mechanism is further provided with a pair of barrier blade biasing springs 106, a barrier blade drive

25

ring 103, a drive ring biasing spring 107 and a barrier blade holding plate 102. The pair of barrier blades 104 and 105 are biased to rotate in opposite directions to be closed by the pair of barrier blade biasing springs 106, respectively. The barrier blade drive ring 103 is rotatable about the lens barrel axis Z0, and is engaged with the pair of barrier blades 104 and 105 to open the pair of barrier blades 104 and 105 when driven to rotate in a predetermined rotational direction. The barrier blade drive ring 103 is biased to rotate in a barrier opening direction to open the pair of barrier blades 104 and 105 by the drive ring biasing spring 107. The barrier blade holding plate 102 is positioned between the barrier blade drive ring 103 and the pair of barrier blades 104 and 105. The spring force of the drive ring biasing spring 107 is greater than the spring force of the pair of barrier blade biasing springs 106 so that the barrier blade drive ring 103 is held by the spring force of the drive ring biasing spring 107 in a specific rotational position thereof to open the pair of barrier blades 104 and 105 against the biasing force of the pair of barrier blade biasing springs 106 in the state shown in Figure 9 where the zoom lens 71 has been extended forward to a point in a zooming range (zooming operation performable range) where a zooming operation can be carried out. In

the course of the retracting movement of the zoom lens 71 to the retracted position shown in Figure 10 from a position in the zooming range, the barrier blade drive ring 103 is forcefully rotated in a barrier closing direction opposite to the aforementioned barrier opening direction by a barrier drive ring pressing surface 11d (see Figures 3 and 16) formed on the cam ring 11. This rotation of the barrier blade drive ring 103 causes the barrier blade drive ring 103 to be disengaged from the pair of barrier blades 104 and 105 so that the pair of barrier blades 104 and 105 are closed by the spring force of the pair of barrier blade biasing springs 106. The zoom lens 71 is provided immediately in front of the lens barrier mechanism with a substantially round lens barrier cover (decorative plate) 101 which covers the front of the lens barrier mechanism.

A lens barrel advancing operation and a lens barrel retracting operation of the zoom lens 71 having the above described structure will be discussed hereinafter.

The stage at which the cam ring 11 is driven to advance from the retracted position shown in Figure 10 to the position shown in Figure 9 where the cam ring 11 rotates at the axial fixed position without moving in the optical axis direction has been discussed above, and will be briefly discussed hereinafter.

In the state shown in Figure 10 in which the zoom lens 71 is in the retracted state, the zoom lens 71 is fully accommodated in the camera body 72 so that the front face of the zoom lens 71 is substantially flush with the front face of the camera body 72. Rotating the zoom gear 28 in the lens barrel advancing direction by the zoom motor 150 causes a combination of the helicoid ring 18 and the third external barrel 15 to move forward while rotating about the lens barrel axis Z0 due to engagement of the female helicoid 22a with the male helicoid 18a, and further causes the first linear guide ring 14 to move forward together with the helicoid ring 18 and the third external barrel 15. At this time, the cam ring 11 which rotates by rotation of the third external barrel 15 moves forward in the optical axis direction by an amount of movement corresponding to the sum of the amount of the forward movement of the first linear guide ring 14 and the amount of the forward movement of the cam ring 11 by a leading structure between the cam ring 11 and the first linear guide ring 14, i.e., by engagement of the set of three roller followers 32 with the lead slot portions 14e-3 of the set of three through-slots 14e, respectively. Once the combination of the helicoid ring 18 and the third external barrel 15 advances to a predetermined point, the male helicoid 18a is disengaged from the female helicoid

22a while the set of three roller followers 32 are disengaged from the lead slot portions 14e-3 to enter the front circumferential slot portions 14e-1, respectively. Consequently, each of the helicoid ring 18 and the third
5 external barrel 15 rotates about the lens barrel axis Z0 without moving in the optical axis direction.

A rotation of the cam ring 11 causes the second lens group moving frame 8, which is positioned inside the cam ring 11, to move in the optical axis direction with respect
10 to the cam ring 11 in a predetermined moving manner due to the engagement of the set of three front cam followers 8b-1 with the set of three front inner cam grooves 11a-1 and the engagement of the set of three rear cam followers 8b-2 with the set of three rear inner cam grooves 11a-2,
15 respectively. In the state shown in Figure 10 in which the zoom lens 71 is in the retracted state, the second lens frame 6, which is positioned inside the second lens group moving frame 8, has rotated about the pivot shaft 33 to be held in the radially retracted position above
20 the photographing optical axis Z1 by the position-control cam bar 21a so that the optical axis of the second lens group LG2 moves from the photographing optical axis Z1 to a retracted optical axis Z2 positioned above the photographing optical axis Z1. In the course of movement
25 of the second lens group moving frame 8 from the retracted

position to a position in the zooming range as shown in Figure 9, the second lens frame 6 is disengaged from the position-control cam bar 21a to rotate about the pivot shaft 33 from the radially retracted position to the photographing position shown in Figure 9 where the optical axis of the second lens group LG2 coincides with the photographing optical axis Z1 by the sprig force of the front torsion coil spring 39. Thereafter, the second lens frame 6 remains to be held in the photographing position until when the zoom lens 71 is retracted into the camera body 72.

In addition, a rotation of the cam ring 11 causes the first external barrel 12, which is positioned around the cam ring 11 and guided linearly in the optical axis direction without rotating about the lens barrel axis Z0, to move in the optical axis direction relative to the cam ring 11 in a predetermined moving manner due to engagement of the set of three cam followers 31 with the set of three outer cam grooves 11b, respectively.

Therefore, an axial position of the first lens group LG1 relative to a picture plane (a light-sensitive surface of the CCD image sensor 60) when the first lens group LG1 is moved forward from the retracted position is determined by the sum of the amount of forward movement of the cam ring 11 relative to the stationary barrel 22 and the amount

of movement of the first external barrel 12 relative to the cam ring 11, while an axial position of the second lens group LG2 relative to the picture plane when the second lens group LG2 is moved forward from the retracted position is determined by the sum of the amount of forward movement of the cam ring 11 relative to the stationary barrel 22 and the amount of movement of the second lens group moving frame 8 relative to the cam ring 11. A zooming operation is carried out by moving the first and second lens groups LG1 and LG2 on the photographing optical axis Z1 while changing the space therebetween. When the zoom lens 71 is driven to advance from the retracted position shown in Figure 10, the zoom lens 71 firstly goes into a state shown below the photographing lens axis Z1 in Figure 9 in which the zoom lens 71 is set at wide-angle extremity. Subsequently, the zoom lens 71 goes into the state shown above the photographing lens axis Z1 in Figure 9 in which the zoom lens 71 is set at telephoto extremity by a further rotation of the zoom motor 150 in a lens barrel advancing direction thereof. As can be seen from Figure 9, the space between the first and second lens groups LG1 and LG2 when the zoom lens 71 is set at the wide-angle extremity is greater than that when the zoom lens 71 is set at the telephoto extremity. When the zoom lens 71 is set at the telephoto extremity

as shown above the photographing lens axis Z1 in Figure 9, the first and second lens groups LG1 and LG2 have moved to approach each other to have some space therebetween which is smaller than the space in the zoom lens 71 set
5 at the wide-angle extremity. This variation of the space between the first and second lens groups LG1 and LG2 for zooming operation is achieved by contours of the plurality of inner cam grooves 11a (11a-1 and 11a-2) and the set of three outer cam grooves 11b. In the zooming range
10 between the wide-angle extremity and the telephoto extremity, the cam ring 11, the third external barrel 15 and the helicoid ring 18 rotate at their respective axial fixed positions, i.e., without moving in the optical axis direction.

15 When the first through third lens groups LG1, LG2 and LG3 are in the zooming range, a focusing operation is carried out by moving the third lens group L3 along the photographing optical axis Z1 by rotation of the AF motor 160 in accordance with an object distance.

20 Driving the zoom motor 150 in a lens barrel retracting direction causes the zoom lens 71 to operate in the reverse manner to the above described advancing operation to fully retract the zoom lens 71 into the camera body 72 as shown in Figure 10. In the course of this
25 retracting movement of the zoom lens 71, the second lens

frame 6 rotates about the pivot shaft 33 to the radially retracted position by the position-control cam bar 21a while moving rearward together with the second lens group moving frame 8. When the zoom lens 71 is fully retracted into the camera body 72, the second lens group LG2 is retracted into the space radially outside the space in which the third lens group LG3, the low-pass filter LG4 and the CCD image sensor 60 are retracted as shown in Figure 10, i.e., the second lens group LG2 is radially retracted into an axial range substantially identical to an axial range in the optical axis direction in which the third lens group LG3, the low-pass filter LG4 and the CCD image sensor 60 are positioned. This structure of the camera 70 for retracting the second lens group LG2 in this manner reduces the length of the zoom lens 71 when the zoom lens 71 is fully retracted, thus making it possible to reduce the thickness of the camera body 72 in the optical axis direction, i.e., in the horizontal direction as viewed in Figure 10.

As described above, the helicoid ring 18, the third external barrel 15 and the cam ring 11 move forward while rotating at the stage at which the zoom lens 71 changes from the retracted state shown in Figure 10 to a ready-to-photograph state shown in Figure 9 (in which the first through third lens groups LG1, LG2 and LG3 remain

within the zooming range), whereas the helicoid ring 18,
the third external barrel 15 and the cam ring 11 rotate
at the respective axial fixed positions thereof without
moving in the optical axis direction when the zoom lens
5 71 is in the ready-to-photograph state. The third
external barrel 15 and the helicoid ring 18 are engaged
with each other to be rotatable together about the lens
barrel axis Z0 by making the three pairs of rotation
transfer projections 15a inserted into the three rotation
10 transfer recesses 18d, respectively. In this state where
the three pairs of rotation transfer projections 15a are
respectively engaged in the three rotation transfer
recesses 18d, the set of three engaging projections 15b
are respectively engaged in the set of three engaging
15 recesses 18e, which are formed on inner peripheral
surfaces of the helicoid ring 18 in three rotational
sliding projections 18b, respectively (see Figures 37 and
38). In a state where the relative rotational angle about
the lens barrel axis Z0 between the third external barrel
20 15 and the helicoid ring 18 is such that the three pairs
of rotation transfer projections 15a are respectively
engaged in the three rotation transfer recesses 18d and
that the set of three engaging projections 15b are
respectively engaged in the set of three engaging recesses
25 18e, the front ends of the three compression coil springs

25, the rear ends of which are respectively inserted in the three spring support holes 18f on the front end of the helicoid ring 18, are respectively in pressing contact with the three engaging recesses 15c that are formed at
5 the rear end of the third external barrel 15.

Each of the helicoid ring 18 and the third external barrel 15 is coupled to the first linear guide ring 14 to make respective relative rotations between the third external barrel 15 and the first linear guide ring 14 and
10 between the helicoid ring 18 and the first linear guide ring 14 possible due to the engagement of the first plurality of relative rotation guide projections 14b with the circumferential groove 18g, the engagement of the second plurality of relative rotation guide projections
15 14c with the circumferential groove 15e and the engagement of the plurality of relative rotation guide projections 15d with the circumferential groove 14d. As can be seen in Figures 33 through 36, the second plurality of relative rotation guide projections 14c and the circumferential
20 groove 15e are engaged with each other to be slightly movable relative to each other in the optical axis direction, the plurality of relative rotation guide projections 15d and the circumferential groove 14d are engaged with each other to be slightly movable relative
25 to each other in the optical axis direction, and the first

plurality of relative rotation guide projections 14b and the circumferential groove 18g are engaged with each other to be slightly movable relative to each other in the optical axis direction. Accordingly, the helicoid ring 5 18 and the third external barrel 15 are slightly movable relative to each other in the optical axis direction even though prevented from being separated totally from each other in the optical axis direction via the first linear guide ring 14. The amount of play (clearance) between 10 the helicoid ring 18 and the first linear guide ring 14 in the optical axis direction is greater than that between the third external barrel 15 and the first linear guide ring 14.

When the third external barrel 15 and the helicoid 15 ring 18 are engaged with each other to be rotatable relative to the first linear guide ring 14, the spaces between the three spring support holes 18f and the three engaging recesses 15c in the optical axis direction are smaller than the free lengths of the three compression 20 coil springs 25 so that the three compression coil springs 25 are compressed and held between opposed end surfaces of the third external barrel 15 and the helicoid ring 18. The three compression coil springs 25 compressed between the opposed end surfaces of the third external barrel 15 25 and the helicoid ring 18 bias the third external barrel

15 and the helicoid ring 18 in opposite directions away
from each other by the resilience of the three compression
coil springs 25, i.e., bias the third external barrel 15
and the helicoid ring 18 forward and rearward in the
5 optical axis direction by the resilience of the three
compression coil springs 25, respectively.

As shown in Figures 27 through 31, the stationary
barrel 22 is provided in each of the three inclined grooves
22c with two opposed inclined surfaces 22c-A and 22c-
10 B which are apart from each other in a circumferential
direction of the stationary barrel. The helicoid ring
18 is provided, on opposite side edges of each of the three
rotational sliding projections 18b in a circumferential
direction of the helicoid ring 18, with two
15 circumferential end surfaces 18b-A and 18b-B which face
the two opposed inclined surfaces 22c-A and 22c-B in the
associated inclined grooves 22c, respectively. Each of
the two opposed inclined surfaces 22c-A and 22c-B in each
inclined groove 22c extend parallel to threads of the
20 female helicoid 22a. The two circumferential end
surfaces 18b-A and 18b-B of each of the three rotational
sliding projections 18b are parallel to the two opposed
inclined surfaces 22c-A and 22c-B in the associated
inclined groove 22c, respectively. The two
25 circumferential end surfaces 18b-A and 18b-B of each

rotational sliding projection 18b are shaped so as not to interfere with the two opposed inclined surfaces 22c-A and 22c-B in the associated inclined groove 22c, respectively. More specifically, when the male helicoid 5 18a are engaged with the female helicoid 22a, the two opposed inclined surfaces 22c-A and 22c-B in each inclined groove 22c do not hold the associated rotational sliding projection 18b therebetween as shown in Figure 31. In other words, the two opposed inclined surfaces 22c-A and 10 22c-B in each inclined groove 22c are not engaged with the two circumferential end surfaces 18b-A and 18b-B of the associated rotational sliding projection 18b, respectively, when the male helicoid 18a are engaged with the female helicoid 22a.

15 One of the three rotational sliding projections 18b is provided on the circumferential end surface 18b-A thereof with an engaging surface 18b-E (see Figures 37, 38, 39, 42 and 43) with which the stop projection 26b of the stop member 26 can be engaged. The engaging surface 20 18b-E is parallel to the lens barrel axis Z0.

As described above, the stationary barrel 22 is provided in each of the set of three rotational sliding grooves 22d with two opposed surfaces: the front guide surface 22d-A and the rear guide surface 22d-B which are 25 apart from each other in the optical axis direction to

extend parallel to each other. Each of the three rotational sliding projections 18b is provided with a front sliding surface 18b-C and a rear sliding surface 18b-D which extend parallel to each other to be slidable
5 on the front guide surface 22d-A and the rear guide surfaces 22d-B, respectively. As shown in Figures 37 through 39, the set of three engaging recesses 18e are respectively formed on front sliding surfaces 18b-C of the three rotational sliding projections 18b of the
10 helicoid ring 18 to be open at the front end of the helicoid ring 18.

In the state shown in Figures 23 and 27 in which the zoom lens 71 is in the retracted state, the two circumferential end surfaces 18b-A and 18b-B of each
15 rotational sliding projection 18b are not in contact with the two opposed inclined surfaces 22c-A and 22c-B in each inclined groove 22c though the set of three rotational sliding projections 18b are positioned in the set of three inclined grooves 22c, respectively, as shown in Figure
20 31. In the retracted state of the zoom lens 71, the male helicoid 18a is engaged with the female helicoid 22a while the set of three rotational sliding projections 18b are engaged in the set of three inclined grooves 22c, respectively. Therefore, if the helicoid ring 18 is
25 rotated in a lens barrel advancing direction (in an upward

direction as viewed in Figure 23) by rotation of the zoom gear 28 that is in mesh with the annular gear 18c of the helicoid ring 18, the helicoid ring 18 moves forward in the optical axis direction (in a leftward direction as viewed in Figure 23) while rotating about the lens barrel axis Z0 due to engagement of the male helicoid 18a with the female helicoid 22a. During this rotating-advancing operation of the helicoid ring 18, the set of three rotational sliding projections 18b do not interfere with the stationary barrel 22 since the set of three rotational sliding projections 18b move in the set of three set of three inclined grooves 22c therealong, respectively.

When the set of three rotational sliding projections 18b are respectively positioned in the set of three set of three inclined grooves 22c, positions of the set of three engaging projections 15b in the optical axis direction are not limited by the set of three inclined grooves 22c, respectively, and also a position of the front sliding surface 18b-C and a position of the rear sliding surface 18b-D of each rotational sliding projection 18b in the optical axis direction are not limited by the associated inclined groove 22c. As shown in Figures 35 and 36, the third external barrel 15 and the helicoid ring 18, which are biased in opposite directions away from each other by the spring force of

the three compression coil springs 25, are slightly apart from each other in the optical axis direction by a distance corresponding to the amount of clearance between the relative rotation guide projections 14b, 14c and 15d and the circumferential grooves 18g, 15e and 14d, respectively, i.e., by a distance corresponding to the sum of the amount of play (clearance) between the helicoid ring 18 and the first linear guide ring 14 in the optical axis direction and the amount of play (clearance) between the third external barrel 15 and the first linear guide ring 14 in the optical axis direction. In this state, the spring force of the three compression coil springs 25 by which the third external barrel 15 and the helicoid ring 18 are biased in opposite directions away from each other is small because the three compression coil springs 25 are not compressed largely, so that the space between the third external barrel 15 and the helicoid ring 18 is loosely maintained. The existence of this loosely maintained space does not become a substantial problem because any pictures are not taken during the translation of the zoom lens 71 from the retracted state to the ready-to-photograph state, i.e., when the set of three rotational sliding projections 18b are engaged in the set of three inclined grooves 22c. In retractable telescoping type zoom lenses including the preset

embodiment of the zoom lens 71, it is generally the case that the total time in which the zoom lens is in the retracted position (including the time when the power is OFF) is greater than the service hours (operating time).

5 Accordingly, it is desirable to apply no heavy load to biasing members such as three compression coil springs 25 to prevent the biasing members from deteriorating with time unless the zoom lens is in the ready-to-photograph state. In addition, if the spring force of the three

10 compression coil springs 25 is small, only a little load is applied to the associated moving parts of the zoom lens 71 during the translation of the zoom lens 71 from the retracted state to the ready-to-photograph state. This lessens the loads applied to the zoom motor 150.

15 A forward movement of the helicoid ring 18 in the optical axis direction causes the first linear guide ring 14 to move together with the helicoid ring 18 in the optical axis direction due to engagement of the engagement of the first plurality of relative rotation guide

20 projections 14b with the circumferential groove 18g. At the same time, a rotation of the helicoid ring 18 is transferred to the cam ring 11 via the third external barrel 15 to move the cam ring 11 forward in the optical axis direction while rotating the cam ring 11 about the

25 lens barrel axis 20 relative to the first linear guide

ring 14 by engagement of the set of three roller followers
32 with the lead slot portions 14e-3 of the set of three
through-slots 14e, respectively. This rotation of the
cam ring 11 causes the first lens group LG1 and the second
5 lens group LG2 to move along the photographing optical
axis Z1 in a predetermined moving manner in accordance
with contours of the set of three outer cam grooves 11b
for moving the first lens group LG1 and the plurality of
inner cam grooves 11a (11a-1 and 11a-2) for moving the
10 second lens group LG2.

Upon moving beyond the front ends of the set of three
inclined grooves 22c, the set of three rotational sliding
projections 18b enter the set of three rotational sliding
grooves 22d, respectively. The ranges of formation of
15 the male helicoid 18a and the female helicoid 22a on the
helicoid ring 18 and the stationary barrel 22,
respectively, are determined so that the male helicoid
18a and the female helicoid 22a are disengaged from each
other at the time when the set of three rotational sliding
20 projections 18b enter the set of three rotational sliding
grooves 22d, respectively. More specifically, the
stationary barrel 22 is provided, on an inner peripheral
surface thereof immediately behind the set of three
rotational sliding grooves 22d, with the aforementioned
25 non-helicoid area 22z, on which no threads of the female

helicoid 22a are formed, and the width of the non-helicoid area 22z in the optical axis direction is greater than the width of that area on the outer peripheral surface of the helicoid ring 18 on which the male helicoid 18 is formed in the optical axis direction. On the other hand, the space between the male helicoid 18a and the set of three rotational sliding projections 18b in the optical axis direction is determined so that the male helicoid 18a and the set of three rotational sliding projections 18b are positioned within the non-helicoid area 22z in the optical axis direction when the set of three rotational sliding projections 18b are positioned in the set of three rotational sliding grooves 22d, respectively. Therefore, at the time when the set of three rotational sliding projections 18b respectively enter the set of three rotational sliding grooves 22d, the male helicoid 18a and the female helicoid 22a are disengaged from each other, so that the helicoid ring 18 does not move in the optical axis direction even if rotating about the lens barrel axis Z0 relative to the stationary barrel 22. Thereafter, the helicoid ring 18 rotates about the lens barrel axis Z0 without moving in the optical axis direction in accordance with rotation of the zoom gear 28 in the lens barrel advancing direction. As shown in Figure 24, the zoom gear 28 remains engaged with the

annular gear 18c even after the helicoid ring 18 has moved to the fixed axis position thereof, at which the helicoid ring 18 rotates about the lens barrel axis 20 without moving in the optical axis direction due to the engagement
5 of the set of three rotational sliding projections 18b with the set of three rotational sliding grooves 22d. This makes it possible to continue to transfer rotation of the zoom gear 28 to the helicoid ring 18.

The state of the zoom lens 71 shown in Figures 24
10 and 28 in which the helicoid ring 18 can rotate at the axial fixed position while the set of three rotational sliding projections 18b have slightly moved in the set of three rotational sliding grooves 22d corresponds to a state in which the zoom lens 71 is set at the wide-
15 angle extremity. As shown in Figure 28 in which the zoom lens 71 is set at the wide-angle extremity, each rotational sliding projection 18b is positioned in the associated rotational sliding groove 22d with the front sliding surface 18b-C and the rear sliding surface 18b-D
20 of the rotational sliding projection 18b facing the front guide surface 22d-A and the rear guide surface 22d-B in the associated rotational sliding groove 22d, so that the helicoid ring 18 is prevented from moving in the optical axis direction relative to the stationary barrel 22.

25 When the set of three rotational sliding projections

18b move into the set of three rotational sliding grooves 22d, respectively, as shown in Figure 33, the set of three engaging projections 15b of the third external barrel 15 move into the set of three rotational sliding grooves 22d at the same time, respectively, so that the set of three engaging projections 15b are respectively pressed against the front guide surfaces 22d-A in the set of three rotational sliding grooves 22d by the spring force of the three compression coil springs 25 and so that the set of three rotational sliding projections 18b of the helicoid ring 18 are respectively pressed against the rear guide surfaces 22d-B in the set of three rotational sliding grooves 22d by the spring force of the three compression coil springs 25. The space between the front guide surfaces 22d-A and the rear guide surfaces 22d-B in the optical axis direction is determined to make the set of three rotational sliding projections 18b and the set of three engaging projections 15b positioned closer to each other in the optical axis direction than those when the set of three rotational sliding projections 18b and the set of three engaging projections 15b are respectively positioned in the set of three inclined grooves 22c. At this time when the set of three rotational sliding projections 18b and the set of three engaging projections 15b are made to be positioned closer to each other in the

optical axis direction, the three compression coil
springs 25 are largely compressed to thereby apply a
stronger spring force to the set of three engaging
projections 15b and the set of three rotational sliding
5 projections 18b than the spring force which is applied
thereto by the three compression coil springs 25 when the
zoom lens 71 is in the retracted state. Thereafter, while
the set of three rotational sliding projections 18b and
the set of three engaging projections 15b are positioned
10 in the set of three rotational sliding grooves 22d, the
set of three engaging projections 15b and the set of three
rotational sliding projections 18b are pressed against
each other by the spring force of the three compression
coil springs 25. This stabilizes axial positions of the
15 third external barrel 15 and the helicoid ring 18 relative
to the stationary barrel 22 in the optical axis direction.
Namely, the third external barrel 15 and the helicoid ring
18 are supported by the stationary barrel 22 with no play
between the third external barrel 15 and the helicoid ring
20 18 in the optical axis direction.

Rotating the third external barrel 15 and the
helicoid ring 18 in the lens barrel advancing direction
from their respective wide-angle extremities (from the
positions shown in Figures 24 and 28) causes the set of
25 three engaging projections 15b and the set of three

rotational sliding projections 18b (the rear sliding surface 18b-D thereof) to firstly move toward the terminal ends of the set of three rotational sliding grooves 22d (upwards as viewed in Figure 28) while being guided by the front guide surfaces 22d-A and the rear guide surfaces 22d-B and subsequently reach telephoto extremities of the third external barrel 15 and the helicoid ring 18 (the positions shown in Figures 25 and 29). Since the set of three engaging projections 15b and the set of three rotational sliding projections 18b remain engaged in the set of three rotational sliding grooves 22d, respectively, the helicoid ring 18 and the third external barrel 15 are prevented from moving in the optical axis direction relative to the stationary barrel 22 and accordingly rotate about the lens barrel axis Z0 without moving in the optical axis direction relative to the stationary barrel 22. In this state, the helicoid ring 18 is guided to be rotatable about the lens barrel axis Z0 mainly by the rear sliding surfaces 18b-D of the set of three rotational sliding projections 18b and the rear guide surfaces 22d-B of the stationary barrel 22 because the helicoid ring 18 is biased rearward in the optical axis direction by the three compression coil springs 25, i.e., in a direction to make the rear sliding surfaces 18b-D come into pressing contact with the rear guide surfaces

22d-B, respectively (see Figure 32).

When the helicoid ring 18 rotates at the axial fixed position, the cam ring 11 also rotates at the axial fixed position without moving in the optical axis direction relative to the first linear guide ring 14 because the
5 set of three roller followers 32 are engaged in the front circumferential slot portions 14e-1 of the set of three through-slots 14e, respectively. Accordingly, the first and second lens groups LG1 and LG2 move in the optical
10 axis direction relative to each other in a predetermined moving manner to perform a zooming operation in accordance with contours of respective zooming sections of the plurality of inner cam grooves 11a (11a-1 and 11a-2) and the set of three outer cam grooves 11b.

15 Further rotating the external barrel 15 and the helicoid ring 18 in the lens barrel advancing direction to move the external barrel 15 and the helicoid ring 18 in the optical axis direction beyond their respective telephoto extremities causes the set of three rotational
20 sliding projections 18b to reach the terminal ends (assembly/disassembly sections) of the set of three rotational sliding grooves 22d as shown in Figures 26 and 30. In this state shown in Figures 26 and 30, movable elements of the zoom lens 71 such as the first through
25 third external barrels 12, 13 and 15 can be removed from

the stationary barrel 22 from the front thereof. However,
if the stop member 26 is provided fixed to the stationary
barrel 22 as shown in Figure 41, such movable elements
cannot be removed from the stationary barrel 22 unless
5 the stop member 26 is removed from the stationary barrel
22 because the engaging surface 18b-E, which is provided
on specific one of the three rotational sliding
projections 18b, comes into contact with the stop
projection 26b of the stop member 26 to prevent the set
10 of three rotational sliding projections 18b from reaching
the terminal ends (assembly/disassembly sections) of the
set of three rotational sliding grooves 22d,
respectively..

Rotating the third external barrel 15 and the
15 helicoid ring 18 in a lens barrel retracting direction
(downwards as viewed in Figure 25) from their respective
telephoto extremities causes the set of three rotational
sliding projections 18b and the set of three engaging
projections 15b to move toward the set of three inclined
20 grooves 22c in the set of three rotational sliding grooves
22d, respectively. During this movement, the third
external barrel 15 and the helicoid barrel 18 rotate
together about the lens barrel axis Z0 with no play between
the third external barrel 15 and the helicoid ring 18 in
25 the optical axis direction because the set of three

engaging projections 15b are respectively pressed against the front guide surfaces 22d-A in the set of three rotational sliding grooves 22d by the spring force of the three compression coil springs 25 while the set of three rotational sliding projections 18b of the helicoid ring 18 are respectively pressed against the rear guide surfaces 22d-B in the set of three rotational sliding grooves 22d by the spring force of the three compression coil springs 25.

Further rotating the external barrel 15 and the helicoid ring 18 in the lens barrel retracting direction beyond their respective wide-angle extremities (the positions shown in Figures 24 and 28) causes the circumferential end surfaces 18b-B of the set of three rotational sliding projections 18b to come into contact with the inclined surfaces 22c-B in the set of three inclined grooves 22c, respectively. Thereupon, the movement of the helicoid ring 18 in the lens barrel retracting direction generates a component force in a direction to make the circumferential end surfaces 18b-B of the set of three rotational sliding projections 18b move rearward in the optical axis direction along the inclined surfaces 22c-B in the set of three inclined grooves 22c while sliding thereon, respectively, because the two circumferential end surfaces 18b-A and 18b-B of

each of the three rotational sliding projections 18b are parallel to the two opposed inclined surfaces 22c-A and 22c-B in the associated inclined groove 22c as shown in Figure 31, respectively. Therefore, the helicoid ring 18 starts moving rearward in the optical axis direction while rotating about the lens barrel axis Z0 in the reverse manner to when the helicoid ring 18 moves forward while rotating. A slight rearward movement of the helicoid ring 18 in the optical axis direction by the engagement of the set of three rotational sliding projections 18b with the set of three inclined grooves 22c, respectively, causes the male helicoid 18a to be engaged with the female helicoid 22a again. Thereafter, further rotating the helicoid ring 18 in the lens barrel retracting direction causes the helicoid barrel 18 to keep moving rearward in the optical axis direction by the engagement of the set of three rotational sliding projections 18b with the set of three inclined grooves 22c, respectively, until the helicoid ring 18 reaches a retracted position thereof shown in Figures 23 and 27, i.e., until the zoom lens 71 is fully retracted. The third external barrel 15 moves rearward in the optical axis direction while rotating about the lens barrel axis Z0 due to the structures of the helicoid ring 18 and the first linear guide ring 14. During this rearward movement of the third external barrel

15, the set of three engaging projections 15b moves together with the set of three rotational sliding projections 18b in the set of three inclined grooves 22c, respectively. When the helicoid ring 18 and the third external barrel 15 move rearward in the optical axis direction, the first linear guide ring 14 also moves rearward in the optical axis direction, which causes the cam ring 11, which is supported by the first linear guide ring 14, to move rearward in the optical axis direction. In addition, at the time when the helicoid ring 18 starts moving rearward while rotating after rotating at the axial fixed position, the set of three roller followers 32 are disengaged from the front circumferential slot portions 14e-1 to be engaged in the lead slot portions 14e-3, respectively, while the cam ring 11 moves rearward in the optical axis direction while rotating about the lens barrel axis Z0 with respect to the first linear guide ring 14.

Upon the set of three rotational sliding projections 18b entering the set of three inclined grooves 22c from the set of three rotational sliding grooves 22d, respectively, the third external barrel 15 and the helicoid ring 18 change the relationship therebetween from the relationship in the ready-to-photograph state shown in Figures 33 and 34, in which the relative axial

positions of the third external barrel 15 and the helicoid ring 18 in the optical axis direction are finely determined, back to the relationship shown in Figures 35 and 36, in which the axial positions of the third external barrel 15 and the helicoid ring 18 are coarsely determined due to the engagement of the third external barrel 15 with the first linear guide ring 14 with a clearance therebetween in the optical axis direction and the engagement of the helicoid barrel 18 with the first linear guide ring 14 with a clearance therebetween in the optical axis direction since either positions of the set of three engaging projections 15b in the optical axis direction or positions of the set of three rotational sliding projections 18b in the optical axis direction are not limited by the set of three rotational sliding grooves 22d, respectively. In the state shown in Figures 35 and 36 in which the set of three rotational sliding projections 18b are engaged in the set of three inclined grooves 22c, the respective positions of the third external barrel 15 and the helicoid ring 18 in the optical axis direction do not need to be determined finely since the zoom lens 71 is no longer in the ready-to-photograph state.

As can be understood from the above descriptions, in the present embodiment of the zoom lens 71, a simple

mechanism having the male and female helicoids 18a and 22a (that have male threads and female threads which are formed on radially-opposed outer and inner peripheral surfaces of the helicoid ring 18 and the stationary barrel 22, respectively), the set of three rotational sliding projections 18b, the set of three inclined grooves 22c and the set of three rotational sliding grooves 22d can make the helicoid ring 18 perform a rotating-advancing/rotating-retracting operation in which the helicoid ring 18 rotates while moving forward or rearward in the optical axis direction, and a fixed-position rotating operation in which the helicoid ring 18 rotates at a predetermined axial fixed position without moving in the optical axis direction relative to the stationary barrel 22. A simple fit between two ring members such as the helicoid ring 18 and the stationary barrel 22 with a highly reliable precision in driving one of the two ring members relative to the other can generally be achieved with a fitting structure using helicoids (male and female helicoid threads). Moreover, the set of three rotational sliding projections 18b and the set of three rotational sliding grooves 22d, which are adopted to make the helicoid ring 18 rotatable at the axial fixed position which cannot be achieved by helicoids, also constitute a simple projection-depression structure similar to the

above fitting structure using helicoids. Furthermore,
the set of three rotational sliding projections 18b and
the set of three rotational sliding grooves 22d are formed
on the outer and inner peripheral surfaces of the helicoid
5 ring 18 and the stationary barrel 22 on which the male
helicoid 18a and the female helicoid 22a are also formed.
This does not require any additional space for the
installation of the set of three rotational sliding
projections 18b and the set of three rotational sliding
10 grooves 22d in the zoom lens 71. Accordingly, the
aforementioned rotating-advancing/rotating-retracting
operation and the fixed-position rotating operation that
are performed by rotation of the helicoid ring 18 are
achieved with a simple, compact and low-cost structure.

15 The zoom gear 28 has a sufficient length in the
optical axis direction to remain engaged with the annular
gear 18c of the helicoid ring 18 regardless of variations
of the position thereof in the optical axis direction.
Therefore, the zoom gear 28, that is provided as a single
20 gear, can transfer rotation thereof to the helicoid ring
18 at all times in each of the rotating-
advancing/rotating-retracting operation and the
fixed-position rotating operation of the helicoid ring
18. Accordingly, a simple and compact rotation transfer
25 mechanism for transferring rotation to the helicoid ring

18 that presents intricate movements is achieved in the present embodiment of the zoom lens, and the helicoid ring 18 and components associated therewith which are positioned inside the helicoid ring 18 can be driven with
5 a high degree of precision.

As shown in Figures 31 and 32, the tooth depth of each rotational sliding projection 18b of the female helicoid 18a is greater than that of each thread of the female helicoid 18a, and accordingly the set of three
10 inclined grooves 22c and the set of three rotational sliding grooves 22d are formed to have greater tooth depths than the threads of the female helicoid 22a. On the other hand, the zoom gear 28 is supported by the stationary barrel 22 so that the gear teeth formed around
15 the zoom gear 28 project radially inwards from an inner peripheral surface of the stationary barrel 22 (from a tooth flank of the female helicoid 22a) to be engaged with the annular gear 18c, which is formed on an outer peripheral surface of each thread of the male helicoid
20 18a. Therefore, the set of three rotational sliding projections 18b and gear teeth of the zoom gear 28 are positioned in the same annular range (radial range) about the lens barrel axis Z0 as viewed from the front of the zoom lens 71. However, the zoom gear 28 does not overlap
25 the moving paths of set of three rotational sliding

projections 18b because the zoom gear 28 is positioned between two of the set of three inclined grooves 22c in a circumferential direction of the stationary barrel 22 and because the zoom gear 28 is installed on the stationary barrel 22 at a position different from the position of the set of three rotational sliding grooves 22d in the optical axis direction. Accordingly, the set of three rotational sliding projections 18b do not interfere with the zoom gear 28 even though engaged in either the set of three inclined grooves 22c or the set of three rotational sliding grooves 22d.

It is possible that the set of three rotational sliding projections 18b and the zoom gear 28 be prevented from interfering with each other by reducing the amount of projection of the gear teeth of the zoom gear 28 from an inner peripheral surface of the stationary barrel 22 (from a tooth flank of the female helicoid 22a) so that the tooth depth of the zoom gear 28 becomes smaller than that of the male helicoid 18a. However, in this case, the amount of engagement of the teeth of the zoom gear 28 with the teeth of the male helicoid 18a will be small, which makes it difficult to achieve a stable rotation of the helicoid ring 18 when it rotates at the axial fixed position. Alternatively, if the tooth depth of the male helicoid 18a is increased without changing the amount of

projection of each rotational sliding projection 18b,
both the diameter of the stationary barrel 22 and the
radial distance between the zoom gear 28 and the lens
barrel axis Z0 increase accordingly. This increases the
5 diameter of the zoom lens 71. Accordingly, if either the
tooth depth of the male helicoid 18a or the amount of
projection of the set of three rotational sliding
projections 18b in radial directions of the helicoid ring
18 is changed to prevent the set of three rotational
10 sliding projections 18b and the zoom gear 28 from
interfering with each other, the helicoid ring 18 may not
be driven with stability; moreover, a sufficient
downsizing of the zoom barrel 71 may not be done. In
contrast, according to the configurations of the zoom gear
15 28 and the set of three rotational sliding projections
18b shown in Figures 27 through 30, the set of three
rotational sliding projections 18b and the zoom gear 28
can be prevented from interfering with each other without
such problems.

20 In the present embodiment of the zoom lens 71, a
rotatable portion of the zoom lens 71 which rotates at
an axial fixed position at one time and also rotates while
moving forward or rearward in the optical axis direction
at another time is divided into two parts: the third
25 external barrel 15, and the helicoid ring 18 that are

slightly movable relative to each other in the optical axis direction. In addition, the third external barrel 15 and the helicoid ring 18 are biased in opposite directions away from each other in the optical axis direction by the resilience of the three compression coil springs 25 to press the set of three engaging projections 15b of the third external barrel 15 against the front guide surfaces 22d-A in the set of three rotational sliding grooves 22d, respectively, and to press the set of three rotational sliding projections 18b of the helicoid ring 18 against the rear guide surfaces 22d-B in the set of three rotational sliding grooves 22d, respectively, to eliminate backlash between the third external barrel 15 and the stationary barrel 22 and backlash between the helicoid ring 18 and the stationary barrel 22. As described above, the set of three rotational sliding grooves 22d and the set of three rotational sliding projections 18b are elements of a drive mechanism for rotating the helicoid ring 18 at the axial fixed position or rotating the helicoid ring 18 while moving the same in the optical axis direction, and are also used as elements for removing the aforementioned backlashes. This reduces the number of elements of the zoom lens 71.

The zoom lens 71 does not have to secure an additional space in the vicinity of the stationary barrel

22 in which the three compression coil springs 25 adopted
for removing backlash are accommodated because the three
compression coil springs 25 are compressed and held
between opposed end surfaces of the third external barrel
5 15 and the helicoid ring 18 that rotate in one piece about
the lens barrel axis 20. In addition, the set of three
engaging projections 15b are respectively received in the
set of three engaging recesses 18e. This achieves a
space-saving connected portion between the third
10 external barrel 15 and the helicoid ring 18.

As described above, the three compression coil
springs 25 are largely compressed to apply a strong spring
force to the set of three engaging projections 15b and
the set of three rotational sliding projections 18b only
15 when the zoom lens 71 is in the ready-to-photograph state.
Namely, the three compression coil springs 25 are not
largely compressed to apply a strong spring force to the
set of three engaging projections 15b and the set of three
rotational sliding projections 18b when the zoom lens 71
20 is not in the ready-to-photograph state, e.g., the
retracted state. This reduces load on the associated
moving parts of the zoom lens 71 during the translation
of the zoom lens 71 from the retracted state to the
ready-to-photograph state, especially at the beginning
25 of driving the zoom lens in the lens barrel advancing

operation, and also increases durability of the three compression coil springs 25.

The helicoid ring 18 and the third external barrel 15 are disengaged from each other firstly in the disassembling operation of the zoom lens 71. A zoom lens assembling mechanism which makes it easy for the zoom lens 71 to be assembled and disassembled, mainly elements of the zoom lens assembling mechanism which are associated with the helicoid ring 18 and the third external barrel 15, will be discussed hereinafter.

As described above, the stationary barrel 22 is provided with the stop-member insertion hole 22e that radially penetrates the stationary barrel 22, from an outer peripheral surface of the stationary barrel 22 to a bottom surface of specific one of the three rotational sliding grooves 22d. The stationary barrel 22 is provided on a surface thereof in the vicinity of the stop-member insertion hole 22e with a screw hole 22f and a stop member positioning protrusion 22g. The stop member 26, which is fixed to the stationary barrel 22 as shown in Figure 41, is provided with an arm portion 26a which extends along an outer peripheral surface of the stationary barrel 22, and the aforementioned stop projection 26b which projects radially inwards from the arm portion 26a. The stop member 26 is provided at one

end thereof with an insertion hole 26c into which the set screw 67 is inserted, and is further provided at the other end thereof with a hook portion 26d. The stop member 26 is fixed to the stationary barrel 22 by screwing the set screw 67 into the screw hole 22f through the insertion hole 26c with the hook portion 26d being engaged with the stop member positioning protrusion 22g as shown in Figure 41. In a state where the stop member 26 is fixed to the stationary barrel 22 in this manner, the stop projection 26b is positioned in the stop-member insertion hole 22e so that the tip of the stop projection 26b projects inside a specific rotational sliding groove 22d among the set of three rotational sliding grooves 22d. This state is shown in Figure 37. Note that the stationary barrel 22 is not shown in Figure 37.

The stationary barrel 22 is provided, at the front end thereof on the front walls of the three rotational sliding grooves 22d, with three insertion/removable holes 22h through which the front of the stationary barrel 22 communicate with the three rotational sliding grooves 22d in the optical axis direction, respectively. Each of the three insertion/removable holes 22h has a sufficient width allowing the associated one of the three engaging projections 15b to be inserted into the insertion/removable hole 22h in the optical axis

direction. Figure 42 shows one of the three insertion/removable holes 22h and peripheral parts when the zoom lens 71 is set at the telephoto extremity as shown in Figures 25 and 29. As can be clearly seen in Figure 42, in the case where the zoom lens 71 is set at the telephoto extremity, the set of three engaging projections 15b cannot be removed, toward the front of the zoom lens 71, from the three rotational sliding grooves 22d through the three insertion/removable holes 22h because the three engaging projections 15b and the three insertion/removable holes 22h are not aligned in the optical axis direction (horizontal direction as viewed in Figure 42), respectively. This positional relationship is true for the remaining two insertion/removable holes 22h though only one of the three insertion/removable holes 22h is shown in Figure 42. On the other hand, when the zoom lens 71 is set at the wide-angle extremity as shown in Figures 24 and 28, the three engaging projections 15b are respectively positioned further from the three insertion/removable holes 22h than the three engaging projections 15b shown in Figures 25 and 29 in which the zoom lens 71 is set at the telephoto extremity. This means that the set of three engaging projections 15b cannot be removed from the three rotational sliding grooves 22d through the three

insertion/removable holes 22h, respectively, when the zoom lens 71 is in the ready-to-photograph state, i.e., when the zoom lens 71 is set at a focal length between the wide-angle extremity and the telephoto extremity.

5 In order to align the three engaging projections 15b and the three insertion/removable holes 22h in the optical axis direction, respectively, from the state shown in Figure 42 in which the zoom lens 71 is set at the telephoto extremity, the third external barrel 15 needs to be
10 further rotated together with the helicoid ring 18 counterclockwise as viewed from the front of the zoom lens 71 relative to the stationary barrel 22 (upwards as viewed in Figure 42) by a rotational angle (disassembling rotational angle) R_{t1} (see Figure 42). However, in a
15 state where the stop projection 26b is inserted into the stop-member insertion hole 22e as shown in Figure 41, if the third external barrel 15 is rotated together with the helicoid ring 18 counterclockwise as viewed from the front of the zoom lens 71 relative to the stationary barrel 22
20 by a rotational angle (allowable rotational angle) R_{t2} (see Figure 42), which is smaller than the disassembling rotational angle R_{t1} , from the state shown in Figure 42 in which the zoom lens 71 is set at the telephoto extremity, the engaging surface 18b-E that is formed on one of the
25 three rotational sliding projections 18b comes into

contact with the stop projection 26b of the stop member 26 to prevent the third external barrel 15 and the helicoid ring 18 from further rotating (see Figure 37). Since the allowable rotational angle $Rt2$ is smaller than the disassembling rotational angle $Rt1$, the three engaging projections 15b and the three insertion/removable holes 22h cannot be aligned in the optical axis direction, respectively, which makes it impossible to remove the set of three engaging projections 15b from the three rotational sliding grooves 22d through the three insertion/removable holes 22h, respectively. Namely, although terminal end portions of the set of three rotational sliding grooves 22d, which respectively communicate with the front of the stationary barrel 22 through the three insertion/removable holes 22h, serve as assembly/disassembly sections, the third external barrel 15 cannot be rotated together with the helicoid ring 18 to a point where the set of three engaging projections 15b are positioned in the terminal end portions of the set of three rotational sliding grooves 22d, respectively, as long as the stop member 26 remains fixed to the stationary barrel 22 with the stop projection 26b in the stop-member insertion hole 22e.

In the disassembling operation of the zoom lens 71, the stop member 26 needs to be removed from the stationary

barrel 22 in the first place. If the stop member 26 is removed, the stop projection 26b comes out of the stop-member insertion hole 22e. Once the stop projection 26b comes out of the stop-member insertion hole 22e, the third external barrel 15 and the helicoid ring 18 can be rotated together by the disassembling rotational angle $Rt1$. Rotating the third external barrel 15 and the helicoid ring 18 together by the disassembling rotational angle $Rt1$ in a state where the zoom lens 71 is set at the telephoto extremity causes the third external barrel 15 and the helicoid ring 18 to be positioned to their respective specific rotational positions relative to the stationary barrel 22 (hereinafter referred to as assembling/disassembling angular positions) as shown in Figures 26, 63. Figures 26 and 30 show a state of the zoom lens 71 where the third external barrel 15 and the helicoid ring 18 have been rotated together by the disassembling rotational angle $Rt1$ to be positioned in the respective assembling/disassembling angular positions from a state where the zoom lens 71 is set at the telephoto extremity. This state of the zoom lens 71, in which the third external barrel 15 and the helicoid ring 18 are positioned in the respective assembling/disassembling angular positions, is hereinafter referred to as an assemblable/disassemblable

state. Figure 43 shows a portion of the stationary barrel 22 on which one of the three insertion/removable holes 22h is formed and portions of peripheral elements in the able-to-be assembled/disassembled state. As can be
5 clearly understood from Figure 43, if the third external barrel 15 and the helicoid ring 18 have rotated by the disassembling rotational angle R_{t1} as shown in Figure 43, the three insertion/removable holes 22h and the three engaging recesses 18e that are formed on the set of three
10 rotational sliding projections 18b are aligned in the optical axis direction so that the set of three engaging projections 15b accommodated in the set of three engaging recesses 18e can be removed therefrom through the three insertion/removable holes 22h from the front of the zoom
15 lens 71, respectively. Namely, the third external barrel 15 can be removed from the stationary barrel 22 from the front thereof. Removing the set of three engaging projections 15b from the set of three engaging recesses 18e, respectively, causes the set of three engaging
20 projections 15b of the third external barrel 15 and the set of three rotational sliding projections 18b of the helicoid ring 18 to be free from the spring force of the three compression coil springs 25, which are adopted to bias the set of three engaging projections 15b and the
25 set of three rotational sliding projections 18b in

opposite directions away from each other in the optical axis direction. At the same time, a function of the three rotational sliding projections 18b for removing backlash between the third external barrel 15 and the stationary barrel 22 and backlash between the helicoid ring 18 and the stationary barrel 22 is cancelled. The three engaging projections 15b and the three insertion/removable holes 22h are aligned in the optical axis direction when the set of three engaging projections 15b are in contact with the terminal ends (upward ends as viewed in Figure 28) of the set of three rotational sliding grooves 22d, respectively. Accordingly, the three engaging projections 15b and the three insertion/removable holes 22h are automatically aligned in the optical axis direction if the third external barrel 15 and the helicoid ring 18 are fully rotated together counterclockwise as viewed from the front of the zoom lens 71 relative to the stationary barrel 22, i.e., if the third external barrel 15 and the helicoid ring 18 are rotated together to the respective assembling/disassembling angular positions.

Although the third external barrel 15 can be removed from the stationary barrel 22 when rotated to the assembling/disassembling angular position as shown in Figures 26 and 30, the third external barrel 15 is still

engaged with the first linear guide ring 14 by the engagement of the plurality of relative rotation guide projections 15d with the circumferential groove 14d and the engagement of the second plurality of relative rotation guide projections 14c with the circumferential groove 15e. As can be seen in Figures 14 and 15, the second plurality of relative rotation guide projections 14c are formed on the first linear guide ring 14 at irregular intervals in a circumferential direction thereof, and some of the second plurality of relative rotation guide projections 14c have different circumferential widths than another ones. Likewise, the plurality of relative rotation guide projections 15d are formed on the third external barrel 15 at irregular intervals in a circumferential direction thereof, and some of the relative rotation guide projections 15d have different circumferential widths than another ones. The third external barrel 15 is provided at a rear end thereof with a plurality of insertion/removable holes 15g through which the second plurality of relative rotation guide projections 14c can be removed from the circumferential groove 15e in the optical axis direction, respectively, only when the first linear guide ring 14 is positioned in a specific rotational position relative to the third external barrel 15. Likewise, the first linear guide

ring 14 is provided at the front end thereof with a plurality of insertion/removable holes 14h through which the plurality of relative rotation guide projections 15d can be removed from the circumferential groove 14d in the optical axis direction, respectively, only when the third external barrel 15 is positioned in a specific rotational position relative to the first linear guide ring 14.

Figures 44 through 47 are developed views of the third external barrel 15 and the first linear guide ring 14, showing the relationship of coupling therebetween in different states. Specifically, Figure 44 shows a state of coupling between the third external barrel 15 and the first linear guide ring 14 when the zoom lens 71 is in the retracted state (which corresponds to the state shown in each of Figures 23 and 27), Figure 45 shows the same when the zoom lens 71 is set at the wide-angle extremity (which corresponds to the state shown in each of Figures 24 and 28), Figure 46 shows the same when the zoom lens 71 is set at the telephoto extremity (which corresponds to the state shown in each of Figures 25 and 29), and Figure 47 shows the same when the zoom lens 71 is in the assemblable/disassemblable state (which corresponds to the state shown in each of Figures 26 and 30). As can be seen from Figures 44 through 47, all of the second plurality of relative rotation guide projections 14c and

the plurality of relative rotation guide projections 15d cannot be inserted into or removed from the circumferential groove 15e and the circumferential groove 14d in the optical axis direction through the plurality of insertion/removable holes 15g and the plurality of insertion/removable holes 14h at the same time, respectively, when the zoom lens 71 is in between the wide-angle extremity and the telephoto extremity, or even in between the wide-angle extremity and the retracted position, because some of the second plurality of relative rotation guide projections 14c and some of the plurality of relative rotation guide projections 15d are engaged in the circumferential groove 15e and the circumferential groove 14d, respectively. Only when the third external barrel 15 and the helicoid ring 18 are rotated together to the respective assembling/disassembling angular positions as shown in Figures 26 and 63 with the stop member having been removed, the second plurality of relative rotation guide projections 14c reach respective specific positions in the circumferential groove 15e at which the second plurality of relative rotation guide projections 14c and the plurality of insertion/removable holes 15g are aligned in the optical axis direction and at the same time the plurality of relative rotation guide projections 15d reach respective specific positions in

the circumferential groove 14d at which the plurality of relative rotation guide projections 15d and the plurality of insertion/removable holes 14h are aligned in the optical axis direction. This makes it possible to remove
5 the third external barrel 15 from the first linear guide ring 14 from the front thereof as shown in Figures 47 and 56. Note that the stationary barrel 22 is not shown in Figure 56. If the third external barrel 15 is removed, the three compression coil springs 25, which are to be
10 held between the third external barrel 15 and the helicoid ring 18, are exposed to the outside of the zoom lens 71, and can be removed accordingly (see Figures 39 and 56).

Therefore, if the third external barrel 15 and the helicoid ring 18 are rotated together to the respective
15 assembling/disassembling angular positions as shown in Figures 26 and 63 after the stop member has been removed, the third external barrel 15 can be removed from both the stationary barrel 22 and the first linear guide ring 14 at the same time. In other words, the stop member 26
20 serves as a rotation limiting device for limiting the range of rotation of each of the third external barrel 15 and the helicoid ring 18 about the lens barrel axis 20 relative to the stationary barrel 22 therein so that the third external barrel 15 and the helicoid ring 18
25 cannot be rotated together to the respective

assembling/disassembling angular positions in a normal
operating state of the zoom lens 71. As can be understood
from the above descriptions, a guiding structure
consisting of the set of three rotational sliding
5 projections 18b, the set of three rotational sliding
grooves 22d and the set of three inclined grooves 22c is
simple and compact; moreover, if only the stop member 26
is added to the guiding structure, the range of rotation
of each of the third external barrel 15 and the helicoid
10 ring 18 about the lens barrel axis Z0 relative to the
stationary barrel 22 can be securely limited so that the
third external barrel 15 and the helicoid ring 18 cannot
be rotated together to the respective
assembling/disassembling angular positions in a normal
15 operating state of the zoom lens 71.

Removing the third external barrel 15 from the zoom
lens 71 makes it possible to further disassemble the zoom
lens 71 in a manner which will be discussed hereinafter.
As shown in Figures 9 and 10, the third external barrel
20 15 is provided at the front end thereof with a frontmost
inner flange 15h which projects radially inwards to close
the front ends of the set of six second linear guide
grooves 14g. The second external barrel 13, the set of
six radial projections 13a of which are respectively
25 engaged in the set of six second linear guide grooves 14g,

cannot be removed from the front of the zoom lens 71 in
a state where the third external barrel 15 and the first
linear guide ring 14 are coupled to each other because
the frontmost inner flange 15h prevents the set of six
5 radial projections 13a from being removed from the set
of six second linear guide grooves 14g, respectively.
Hence, the second external barrel 13 can be removed from
the first linear guide ring 14 once the third external
barrel 15 is removed. However, the second external
10 barrel 13 cannot be removed from the cam ring 11 in the
optical axis direction if the discontinuous inner flange
13c remains engaged in the discontinuous circumferential
groove 11c of the cam ring 11. As shown in Figure 20,
the discontinuous inner flange 13c is formed as a
15 discontinuous groove which is disconnected at irregular
intervals in a circumferential direction of the second
external barrel 13. On the other hand, as shown in Figure
16, the cam ring 11 is provided on outer peripheral surface
thereof with a set of three external protuberances 11g
20 which project radially outwards, while the discontinuous
circumferential groove 11c is formed discontinuously on
only respective outer surfaces of the set of three
external protuberances 11g. The discontinuous
circumferential groove 11c is provided on each of the
25 three external protuberances 11g with an

insertion/removable hole 11r which is open at the front
end of the external protuberance 11g. The
insertion/removable holes 11r are arranged at irregular
intervals in a circumferential direction of the cam ring
5 11.

Figures 52 through 55 are developed views of the
cam ring 11, the first external barrel 12 and the second
external barrel 13, showing the relationship of coupling
of each of the first external barrel 12 and the external
10 barrel 13 to the cam ring 11 in different states.
Specifically, Figure 52 shows a state of coupling of the
first external barrel 12 and the external barrel 13 to
the cam ring 11 when the zoom lens 71 is in the retracted
state (which corresponds to the state shown in each of
15 Figures 23 and 27), Figure 53 shows the same when the zoom
lens 71 is set at the wide-angle extremity (which
corresponds to the state shown in each of Figures 24 and
28), Figure 54 shows the same when the zoom lens 71 is
set at the telephoto extremity (which corresponds to the
20 state shown in each of Figures 25 and 29), and Figure 55
shows the same when the zoom lens 71 is in the
assemblable/disassemblable state (which corresponds to
the state shown in each of Figures 26 and 30). As can
be seen from Figures 52 through 54, the second external
25 barrel 13 cannot be removed from the cam ring 11 in the

optical axis direction when the zoom lens 71 is in between the wide-angle extremity and the telephoto extremity, or even in between the wide-angle extremity and the retracted position because some portions of the discontinuous inner flange 13c are engaged in at least a part of the discontinuous circumferential groove 11c. Only when the third external barrel 15 and the helicoid ring 18 are rotated together to the respective assembling/disassembling angular positions as shown in Figures 26 and 63, the rotation of the third external barrel 15 causes the cam ring 11 to rotate to a specific rotational position thereof at which all the portions of the discontinuous inner flange 13c of the second external barrel 13 are exactly aligned with the three insertion/removable hole 11r or the three circumferential spaces among the three external protuberances 11g, respectively. This makes it possible to remove the second external barrel 13 from the cam ring 11 from the front thereof as shown in Figures 55 and 57.

In addition, in the state shown in Figure 55 in which the zoom lens 71 is in the assemblable/disassemblable state, the set of three cam followers 31 on the first external barrel 12 are positioned close to the front open ends of the set of three outer cam grooves 11b, respectively, so that the first external barrel 12 can

be removed from the front of the zoom lens 71 as shown in Figure 58. In addition, the first lens group adjustment ring 2 can also be removed from the second external barrel 12 after the two set screws 64 are screwed off to remove the fixing ring 3 as shown in Figure 2. Thereafter, the first lens frame 1 that is supported by the first lens group adjustment ring 2 therein can also be removed from the first lens group adjustment ring 2 from the front thereof.

Although the first linear guide ring 14, the helicoid ring 18, the cam ring 11, and some other elements in the cam ring 11 such as the second lens group moving frame 8 still remain in the stationary barrel 22 in the state shown in Figure 58, the zoom lens 71 can be further disassembled as needed.

As can be seen from Figures 57 and 58, if the third external barrel 15 is removed with the zoom lens 71 being fully extended forward from the stationary barrel 22, each of the three set screws 32a becomes accessible. Thereafter, if the set of three roller followers 32 are removed together with the three set screws 32a as shown in Figure 59, a combination of the cam ring 11 and the second linear guide ring 10 can be removed from the first linear guide ring 14 from the rear thereof because no elements of the zoom lens 71 prevent the cam ring 11 from

moving rearward in the optical axis direction relative to the first linear guide ring 14. As shown in Figures 15 and 59, frond ends of each pair of first linear guide grooves 14f, in which the pair of radial projections of the associated bifurcated projection 10a are engaged, are each formed as a closed end while rear ends of the same are each formed as an open end at the rear end of the first linear guide ring 14. Accordingly, the combination of the cam ring 11 and the second linear guide ring 10 can be removed from the first linear guide ring 14 only from the rear thereof. Although the second linear guide ring 10 and the cam ring 11 are coupled to each other with the discontinuous outer edge of the ring portion 10b being engaged in the discontinuous circumferential groove 11e to be rotatable relative to each other about the lens barrel axis 20, the second linear guide ring 10 and the cam ring 11 can be disengaged from each other as shown in Figure 3 when one of the second linear guide ring 10 and the cam ring 11 is positioned in a specific rotational position relative to the other.

When the third external barrel 15 and the helicoid ring 18 are rotated together to the respective assembling/disassembling angular positions as shown in Figures 26 and 63, the set of three front cam followers 8b-1 are removed from the set of three front inner cam

grooves 11a-1 in the optical axis direction from the front of the cam ring 11 while the set of three rear cam followers 8b-2 are positioned in front open end sections 11a-2x of the set of three rear inner cam grooves 11a-2, respectively. Therefore, the second lens group moving frame 8 can be removed from the cam ring 11 from the front thereof as shown in Figure 3. Since the front open end sections 11a-2x of the set of three rear inner cam grooves 11a-2 are formed as linear grooves extending in the optical axis direction, the second lens group moving frame 8 can be removed from the cam ring 11 from the front thereof regardless of whether the second lens group moving frame 8 is guided linearly in the optical axis direction by the second linear guide ring 10, i.e., whether or not the set of three front cam followers 8b-1 and the set of three rear cam followers 8b-2 are engaged in the set of three front inner cam grooves 11a-1 and the set of three rear inner cam grooves 11a-2, respectively. In the state shown in Figure 58 in which the cam ring 11 and the second linear guide ring 10 remain inside the first linear guide ring 14, only the second lens group moving frame 8 can be removed.

The pivot shaft 33 and the second lens frame 6 can be removed from the second lens group moving frame 8 after the set screws 66 are unscrewed to remove the pair of

second lens frame support plates 36 and 37 (see Figure 3).

Aside from the elements positioned inside the cam ring 11, the helicoid ring 18 can be removed from the stationary barrel 22. In this case, after the CCD holder 21 is removed from the stationary barrel 22, the helicoid ring 18 is rotated in the lens barrel retracting direction from the assembling/disassembling angular position to be removed from the stationary barrel 22. This rotation of the helicoid ring 18 in the lens barrel retracting direction causes the set of three rotational sliding projections 18b to move back into the set of three inclined grooves 22c from the set of three rotational sliding grooves 22d so that the male helicoid 18a is engaged with the female helicoid 22a, thus causing the helicoid ring 18 to move rearward while rotating about the lens barrel axis Z0. Upon the helicoid ring 18 moving rearward beyond the position thereof shown in Figures 23 and 27, the set of three rotational sliding projections 18b are respectively removed from the set of three inclined grooves 22c from rear open end sections 22c-x thereof while the male helicoid 18a is disengaged from the female helicoid 22a. Consequently, the helicoid ring 18, together with the linear guide ring 14, is removed from the stationary barrel 22 from the rear thereof.

The helicoid ring 18 and the linear guide ring 14 are engaged with each other by engagement of the first plurality of relative rotation guide projections 14b with the circumferential groove 18g. Similar to the second
5 plurality of relative rotation guide projections 14c, the first plurality of relative rotation guide projections 14b are formed on the first linear guide ring 14 at irregular intervals in a circumferential direction thereof, and some of the first plurality of relative
10 rotation guide projections 14b have different circumferential widths than another ones. The helicoid ring 18 is provided on an inner peripheral surface thereof with a plurality of insertion/removable grooves 18h via which the first plurality of relative rotation guide
15 projections 14b can enter the helicoid ring 18 (the circumferential groove 18g) in the optical axis direction, respectively, only when the first linear guide ring 14 is positioned in a specific rotational position relative to the helicoid ring 18.

20 Figures 48 through 51 show developed views of the first linear guide ring 14 and the helicoid ring 18, showing the relationship of coupling therebetween in different states. Specifically, Figure 48 shows a state of coupling between the first linear guide ring 14 and
25 the helicoid ring 18 when the zoom lens 71 is in the

retracted state (which corresponds to the state shown in each of Figures 23 and 27), Figure 49 shows another state of coupling between the first linear guide ring 14 and the helicoid ring 18 when the zoom lens 71 is set at the wide-angle extremity (which corresponds to the state shown in each of Figures 24 and 28), Figure 50 shows the same when the zoom lens 71 is set at the telephoto extremity as shown in Figures 25 and 29, and Figure 51 shows another state of coupling between the first linear guide ring 14 and the helicoid ring 18 when the zoom lens 71 is in the assemblable/disassemblable state (which corresponds to the state shown in each of Figures 26 and 30). As can be seen from Figures 48 through 51, when the zoom lens 71 is in between the retracted position and the position in the assemblable/disassemblable state, in which the third external barrel 15 and the helicoid ring 18 are positioned in the respective assembling/disassembling angular positions as shown in Figures 26 and 63, all of the first plurality of relative rotation guide projections 14b cannot be inserted into or removed from the plurality of insertion/removable grooves 18h at the same time, respectively, which makes it impossible to disengage the helicoid ring 18 and the first linear guide ring 14 from each other in the optical axis direction. All the first plurality of relative

rotation guide projections 14b can be inserted into or removed from the plurality of insertion/removable grooves 18h at the same time, respectively, only when the helicoid ring 18 is further rotated in the lens barrel retracting direction (downwards as viewed in Figure 48) to a specific rotational position beyond the retracted position of the helicoid ring 18 shown in Figure 48. After the helicoid ring 18 has been rotated to the specific rotational position, moving the helicoid 18 forward (leftward as viewed in Figures 48 through 51) with respect to the first linear guide ring 14 causes the first plurality of relative rotation guide projections 14b to be removed from the plurality of insertion/removable grooves 18h to the rear of the circumferential groove 18g, respectively. Alternatively, it is possible to modify the structure coupling between the first linear guide ring 14 and the helicoid ring 18 so that all the first plurality of relative rotation guide projections 14b can pass the helicoid ring 18 in the optical axis direction through the plurality of insertion/removable grooves 18h at the same time when the helicoid ring 18 and the linear guide ring 14 are positioned at the aforementioned respective rotational positions at which the helicoid ring 18 and the linear guide ring 14 can be removed from the stationary barrel 22.

The second plurality of relative rotation guide projections 14c, which are engaged in the circumferential groove 15e of the third external barrel 15, are formed in front of the first plurality of relative rotation guide projections 14b on first linear guide ring 14 in the optical axis direction. As described above, the first plurality of relative rotation guide projections 14b are formed as circumferentially elongated projections at different circumferential positions on the first linear guide ring 14 while the second plurality of relative rotation guide projections 14c are formed as circumferentially elongated projections at different circumferential positions on the first linear guide ring 14. More specifically, although the respective positions of the first plurality of relative rotation guide projections 14b are not coincident with those of the second plurality of relative rotation guide projections 14c in a circumferential direction of the first linear guide ring 14, the first plurality of relative rotation guide projections 14b and the second plurality of relative rotation guide projections 14c are the same as each other in the number of projections, intervals of projections, and circumferential widths of corresponding projections as shown in Figure 15. Namely, there is a specific relative rotational position between

the second plurality of relative rotation guide projections 14c and the plurality of insertion/removable grooves 18h, in which the second plurality of relative rotation guide projections 14c and the plurality of insertion/removable grooves 18h can be disengaged from each other in the optical axis direction. If the helicoid ring 18 is moved forward from the first linear guide ring 14 in a state where the second plurality of relative rotation guide projections 14c and the plurality of insertion/removable grooves 18h are in such a specific relative rotational position, each relative rotation guide projections 14c can be inserted into the corresponding insertion/removable groove 18h from the front end thereof and subsequently removed from the same insertion/removable groove 18h from the rear end thereof so that the helicoid ring 18 can be removed from the first linear guide ring 14 from the front thereof. Accordingly, the front and rear ends of each insertion/removable groove 18h are respectively formed as open ends so that the associated relative rotation guide projections 14c can pass the helicoid ring 18 in the optical axis direction through the insertion/removable groove 18h.

Namely, the helicoid ring 18 and the first linear guide ring 14 are not in a disengagable state until the helicoid ring 18 and the first linear guide ring 14 are

removed from the stationary barrel 22 and relatively
rotated by a predetermined amount of rotation. In other
words, when disassembling the third external barrel 15,
the helicoid ring 18 and the first linear guide ring 14
5 are mutually engaged with each other while being supported
inside the stationary barrel 22. The assembly process
is accordingly facilitated by disallowing the first
linear guide ring 14 from being disengaged.

As can be understood from the foregoing, in the
10 present embodiment of the zoom lens, the third external
barrel 15, which performs the rotating-
advancing/rotating-retracting operation and the
fixed-position rotating operation, can be easily removed
from the zoom lens 71 by rotating the third external barrel
15 and the helicoid ring 18 together to the respective
assembling/disassembling angular positions as shown in
Figures 26 and 63, which are different from any of their
respective positions in either of the zooming range and
the retracting range, after the stop member 26 has been
20 removed from the stationary barrel 22. Moreover, a
function of the three rotational sliding projections 18b
for removing backlash between the third external barrel
15 and the stationary barrel 22 and backlash between the
helicoid ring 18 and the stationary barrel 22 can be
25 cancelled by removing the third external barrel 15 from

the zoom lens 71. Furthermore, when the zoom lens 71 is in the assemblable/disassemblable state, in which the third external barrel 15 can be inserted into or removed from the zoom lens 71, the second external barrel 13, the first external barrel 12, the cam ring 11, the second lens group moving frame 8 and other elements are also positioned at their respective assembling/disassembling positions to become removable from the zoom lens 71 one after another after the third external barrel 15 is removed from the zoom lens 71. This results in an improvement in workability of disassembling the zoom lens 71.

Although only a disassembling procedure of the zoom lens 71 has been discussed above, a reverse procedure to the above disassembling procedure can be performed as an assembling procedure of the zoom lens 71. This also results in an improvement in workability of assembling the zoom lens 71.

Another feature of the zoom lens 71 which is associated with the third external barrel 15 (and also the helicoid ring 18) will be hereinafter discussed with reference mainly to Figures 60 through 72. In Figures 60 through 63, some portions of the linear guide ring 14 and the third external barrel 15, and the follower-biasing ring spring 17 for biasing the set of three roller

followers 32 would not normally be visible (i.e., are supposed to be shown by hidden lines), but are shown by solid lines for the purpose of illustration. Figures 64 through 66 show portions of the third external barrel 15 and the helicoid ring 18, viewed from the inside thereof, and accordingly the direction of inclination of, e.g. the inclined lead slot portion 14e-3 appeared in Figure 64 and 65, is opposite to that shown in the other Figures.

As can be understood from the above descriptions, in the present embodiment of the zoom lens 71, a rotatable barrel positioned immediately inside the stationary barrel 22 (namely, the first rotatable barrel when viewed from the side of the stationary barrel 22) is divided into two parts: the third external barrel 15 and the helicoid ring 18. In the following descriptions, the third external barrel 15 and the helicoid ring 18 are referred to as a rotatable barrel KZ in some cases for clarity (e.g., see Figures 23 through 26, 60 through 62). The function of the rotatable barrel KZ is to impart motion to the set of three roller followers 32 to rotate the set of three roller followers 32 about the lens barrel axis Z0. The cam ring 11 receives force, which makes the cam ring 11 rotate about the lens barrel axis Z0 while moving in the optical axis direction, via the set of three roller followers 32 to move the first and second lens groups LG1

and LG2 in the optical axis direction in a predetermined moving manner. Engaging portions of the rotatable barrel KZ which are engaged with the set of three roller followers 32, i.e., the set of three rotation transfer grooves 15f satisfy some conditions which will be hereinafter discussed.

First of all, the set of three rotation transfer grooves 15f, in which the set of three roller followers 32 are engaged, need to have lengths corresponding to the range of movement of the set of three roller followers 32 in the optical axis direction. This is because each roller follower 32 is not only rotated about the lens barrel axis Z0 between a retracted position shown in Figure 60 and a position shown in Figure 62 which corresponds to the telephoto extremity of the zoom lens 71 via a position shown in Figure 61 which corresponds to the wide-angle extremity of the zoom lens 71, but also moved in the optical axis direction relative to the rotatable barrel KZ by the associated inclined lead slot portion 14e-3 of the first linear guide ring 14.

The third external barrel 15 and the helicoid ring 18 substantially operate as a one-piece rotatable barrel: the rotatable barrel KZ. This is because the third external barrel 15 and the helicoid ring 18 are prevented from rotating relative to each other by engagement of the

three pairs of rotation transfer projections 15a with the three rotation transfer recesses 18d, respectively. However, in the present embodiment of the zoom lens, since the third external barrel 15 and the helicoid ring 18 are provided as separate members for the purpose of assembling and disassembling the zoom lens 71, there is provided a slight clearance between each pair of rotation transfer projections 15a and the associated rotation transfer recess 18d in a rotational direction (vertical direction as viewed in Figure 66). More specifically, as shown in Figure 66, the three pairs of rotation transfer projections 15a and the three rotation transfer recesses 18d are formed so that a circumferential space WD1 between circumferentially-opposed two side surfaces 18d-S of the helicoid ring 18 in each rotation transfer recess 18d that extend parallel to each other becomes slightly greater than a circumferential space WD2 between opposite end surfaces 15a-S of the associated pair of rotation transfer projections 15a that also extend parallel to each other. Due to this clearance, the third external barrel 15 and the helicoid ring 18 slightly rotate relative to each other about the lens barrel axis Z0 when one of the third external barrel 15 and the helicoid ring 18 is rotated about the lens barrel axis Z0 relative to the other. For instance, in the state shown in Figure 64, if the helicoid

ring 18 is rotated in the lens barrel advancing direction shown by an arrow AR1 in Figure 65 (downwards as viewed in Figures 64 and 65) with respect to the third external barrel 15, the helicoid ring 18 rotates in the same direction by an amount of rotation "NR" with respect to the third external barrel 15 so that one of the circumferentially-opposed two side surfaces 18d-S in each rotation transfer recess 18d comes into contact with corresponding one of the opposite end surfaces 15a-S of the associated pair of rotation transfer projections 15a as shown in Figure 65. Therefore, the set of three rotation transfer grooves 15f must be formed on the third external barrel 15 to be capable of guiding the set of three roller followers 32 smoothly in the optical axis direction at all times regardless of the presence or absence of a variation in the relative rotational position between the third external barrel 15 and the helicoid ring 18 that is caused by the presence of the clearance between each pair of rotation transfer projections 15a and the associated rotation transfer recess 18d. This clearance is exaggerated in the drawings for the purpose of illustration.

In the present embodiment of the zoom lens, the three pairs of rotation transfer projections 15a that extend rearward in the optical axis direction are formed on the

third external barrel 15 as engaging portions thereof for
engaging the third external barrel 15 with the helicoid
ring 18. This structure of the three pairs of rotation
transfer projections 15a has been fully utilized for the
5 formation of the set of three rotation transfer grooves
15f on the third external barrel 15. More specifically,
the major portion of each rotation transfer groove 15f is
formed on an inner peripheral surface of the third
external barrel 15 so that the circumferential positions
10 of the three rotation transfer grooves 15f correspond to
those of the three pairs of rotation transfer projections
15a, respectively. In addition, the remaining rear end
portion of each rotation transfer groove 15f is elongated
rearward in the optical axis direction to be formed
15 between opposed guide surfaces 15f-S (see Figure 66) of
the associated pair of rotation transfer projections 15a.

No gaps or steps are formed in each rotation transfer
groove 15f because each rotation transfer groove 15f is
formed only on the third external barrel 15, not formed
20 as a groove extending over the third external barrel 15
and the helicoid ring 18. Even if the relative rotational
position between the third external barrel 15 and the
helicoid ring 18 slightly varies due to the clearance
between each pair of rotation transfer projections 15a
25 and the associated rotation transfer recess 18d, the

opposed guide surfaces 15f-S of each rotation transfer groove 15f remain invariant in shape. Therefore, the set of three rotation transfer grooves 15f are capable of guiding the set of three roller followers 32 smoothly in the optical axis direction at all times.

The set of three rotation transfer grooves 15f can be formed to have sufficient lengths in the optical axis direction by making most of the three pairs of rotation transfer projections 15a that project in the optical axis direction, respectively. As shown in Figures 60 through 62, a range of movement D1 of the set of three roller followers 32 in the optical axis direction (see Figure 60) is greater than an axial length D2 of an area on the inner peripheral surface of the third external barrel 15 (except for the three pairs of rotation transfer projections 15a) in the optical axis direction on which grooves extending in the optical axis direction can be formed. Specifically, in the state shown in Figures 60 and 64 in which the zoom lens 71 is in the retracted state as shown in Figure 10, each roller follower 32 has moved rearward to a point (retracted point) between the front and rear ends of the helicoid ring 18 in the optical axis direction. However, since each pair of rotation transfer projections 15a extends rearward to a point corresponding to the retracted point between the front and rear ends

of the helicoid ring 18 in the optical axis direction because the three pairs of rotation transfer projections 15a need to remain engaged in the three rotation transfer recesses 18d, respectively, the engagement of the set of three roller followers 32 with the set of three rotation transfer grooves 15f is maintained even if the set of three roller followers 32 are moved rearward to the respective retracted points. Accordingly, the set of three roller followers 32 can be guided in the optical axis direction in a range of movement extending over the third external barrel 15 and the helicoid ring 18 even if guiding portions (the set of three rotation transfer grooves 15f) which are engaged with the set of three roller followers 32 (to guide the set of three roller followers 32) are formed only on the third external barrel 15 of the rotatable barrel K2.

Even though the circumferential groove 15e intersects each rotation transfer groove 15f on the inner peripheral surface of the third external barrel 15, the circumferential groove 15e does not deteriorate the guiding function of the set of three rotation transfer grooves 15f because the depth of the circumferential groove 15e is smaller than that of each rotation transfer groove 15f.

Figures 67 and 68 show a comparative example which

is to be compared with the above described structure shown mainly in Figures 64 through 66. In this comparative example, a front ring 15' (which corresponds to the third external barrel 15 of the present embodiment of the zoom lens) is provided with a set of three rotation transfer grooves 15f' (only one of them is shown in Figures 67 and 68) extending linearly in the optical axis direction, while a rear ring 18' (which corresponds to the helicoid ring 18 of the present embodiment of the zoom lens) is provided with a set of three extension grooves 18x extending linearly in the optical axis direction. A set of three roller followers 32' (which corresponds to the set of three roller followers 32 of the present embodiment of the zoom lens 71) are engaged in the set of three rotation transfer grooves 15f' or the set of three extension grooves 18x so that each roller follower 32' can move in the associated rotation transfer groove 15f' and the associated extension groove 18x in the optical axis direction. Namely, the set of three roller followers 32' are respectively movable in a set of three grooves extending over the front ring 15' and the rear ring 18'. The front ring 15' and the rear ring 18' are engaged with each other via a plurality of rotation transfer projections 15a' of the front ring 15' and a corresponding plurality of rotation transfer grooves

18d' of the rear ring 18' in which the plurality of rotation transfer projections 15a' are respectively engaged. The plurality of rotation transfer projections 15a' are formed on a rear end surface of the front ring 15' which faces a front surface of the rear ring 18', while the plurality of rotation transfer grooves 18d' are formed on the front surface of the rear ring 18'. There is a slight clearance between the plurality of rotation transfer projections 15a' and the plurality of rotation transfer grooves 18d' in a rotational direction (vertical direction as viewed in Figure 68). Figure 67 shows a state where the set of three rotation transfer grooves 15f' and the set of three extension grooves 18x are precisely aligned in the optical axis direction.

15 In the comparative example having the above described structure, in the state shown in Figure 67, if the front ring 18' is rotated in a direction shown by an arrow AR1' in Figure 68 (downwards as viewed in Figures 67 and 68) with respect to the rear ring 18', the rear ring 18' slightly rotates in the same direction due to the aforementioned clearance between the plurality of rotation transfer projections 15a' and the plurality of rotation transfer grooves 18d'. This causes a misalignment between the set of three rotation transfer grooves 15f' and the set of three extension grooves 18x.

Therefore, in the state shown in Figure 68, a gap is produced between a guide surface of each rotation transfer groove 15f' and a corresponding guide surface of the associated extension groove 18x. This gap may interfere
5 with a movement of each roller follower 32' in the associated rotation transfer groove 15f' and the associated extension groove 18x in the optical axis direction, which cannot ensure a smooth movement of each roller follower 32'. If the gap becomes large, each
10 roller follower 32' may not be able to move between the associated rotation transfer groove 15f' and the associated extension groove 18x across a border therebetween.

Supposing either the set of rotation transfer
15 grooves 15f' or the set of extension grooves 18x is omitted to prevent such an undesirable gap from being produced between a guide surface of each rotation transfer groove 15f' and a corresponding guide surface of the associated extension groove 18x, the other set of rotation transfer
20 grooves 15f' or extension grooves 18x may need to be elongated in the optical axis direction. Consequently, the length of either the front ring 15' or the rear ring 18' in the optical axis direction will increase. For instance, if it is desired to omit the set of extension
25 grooves 18x, each rotation transfer groove 15f' must be

elongated forward by a length corresponding to the length of each extension groove 18x. This increases the dimensions of the zoom lens, specifically the length thereof.

5 In contrast to this comparative example, the present embodiment of the zoom lens, in which the three pairs of rotation transfer projections 15a that extend rearward in the optical axis direction are formed on the third external barrel 15 as engaging portions thereof for
10 engaging the third external barrel 15 with the helicoid ring 18, has the advantage that the set of three rotation transfer grooves 15f are respectively capable of guiding the set of three roller followers 32 smoothly in the optical axis direction at all times without any gaps being
15 produced in the set of three rotation transfer grooves 15f. Moreover, the present embodiment of the zoom lens has the advantage that each rotation transfer groove 15f can be formed to have a sufficient effective length without the third external barrel 15 being elongated
20 forward in the optical axis direction.

 Exerting a force to the set of three roller followers 32 in a direction to rotate the same about the lens barrel axis Z0 via the set of three rotation transfer grooves 15f causes the cam ring 11 to rotate about the lens barrel
25 axis Z0 while rotating in the optical axis direction due

to engagement of the set of three roller followers 32 with the lead slot portions 14e-3 of the set of three through-slots 14e, respectively, when the zoom lens 71 is set in between the wide-angle extremity and the retracted position. When the zoom lens 71 is in the zooming range, the cam ring 11 rotates at the axial fixed position without moving in the optical axis direction due to engagement of the set of three roller followers 32 with the front circumferential slot portions 14e-1 of the set of three through-slots 14e, respectively. Since the cam ring 11 rotates at the axial fixed position in the ready-to-photograph state of the zoom lens 71, the cam ring 11 must be positioned precisely at a predetermined position in the optical axis direction to insure optical accuracy of movable lens groups of the zoom lens 71 such as the first lens group LG1 and the second lens group LG2. Although the position of the cam ring 11 in the optical axis direction when the cam ring 11 rotates at the axial fixed position thereof is determined by the engagement of the set of three roller followers 32 with the front circumferential slot portions 14e-1 of the set of three through-slots 14e, respectively, a clearance is provided between the set of three roller followers 32 and the front circumferential slot portions 14e-1 so that the set of three roller followers 32 can smoothly move in the front

circumferential slot portions 14e-1 of the set of three through-slots 14e, respectively. Accordingly, it is necessary to remove backlash between the set of three roller followers 32 and the set of three through-slots 14e which is caused by the clearance when the set of three roller followers 32 are engaged in the front circumferential slot portions 14e-1 of the set of three through-slots 14e, respectively.

The follower-biasing ring spring 17 for removing the backlash is positioned inside the third external barrel 15, and a structure supporting the follower-biasing ring spring 17 is shown in Figures 33, 35, 63 and 69 through 72. The frontmost inner flange 15h is formed on the third external barrel 15 to extend radially inwards from a front end of the inner peripheral surface of the third external barrel 15. As shown in Figure 63, the follower-biasing ring spring 17 is a non-flat annular member which is provided with a plurality of bends which are bent in the optical axis direction to be resiliently deformable in the optical axis direction. More specifically, the follower-biasing ring spring 17 is disposed so that the set of three follower pressing protrusions 17a are positioned at the rear end of the follower-biasing ring spring 17 in the optical axis direction. The follower-biasing ring spring 17 is provided with a set

of three forwardly-projecting arc portions 17b which project forward in the optical axis direction. The three forwardly-projecting arc portions 17b and the three follower pressing protrusions 17a are alternately
5 arranged to form the follower-biasing ring spring 17 as shown in Figures 4, 14 and 63. The follower-biasing ring spring 17 is disposed between the frontmost inner flange 15h and the plurality of relative rotation guide projections 15d in a slightly compressed state so as not
10 to come off the third external barrel 15 from the inside thereof. If the set of three forwardly-projecting arc portions 17b are installed between the frontmost inner flange 15h and the plurality of relative rotation guide projections 15d with the set of three follower pressing
15 protrusions 17a and the set of three rotation transfer grooves 15f being aligned in the optical axis direction, the set of three follower pressing protrusions 17a are engaged in respective front portions of the set of three rotation transfer grooves 15f to be supported thereby.
20 When the first linear guide ring 14 is not attached to the third external barrel 15, each follower pressing protrusion 17a is sufficiently apart from the frontmost inner flange 15h of the third external barrel 15 in the optical axis direction as clearly shown in Figure 72 to
25 be movable to a certain degree in the associated rotation

transfer groove 15f.

When the first linear guide ring 14 is attached to the third external barrel 15, the set of three forwardly-projecting arc portions 17b of the follower-biasing ring spring 17 are deformed by being pressed forward, toward the frontmost inner flange 15h, by the front end of the linear guide ring 14 to make the shape of the set of three forwardly-projecting arc portions 17b become close to a flat shape. When the follower-biasing ring spring 17 is deformed in such a manner, the first linear guide ring 14 is biased rearward by the resiliency of the follower-biasing ring spring 17 to thereby fix the position of the first linear guide ring 14 with respect to the third external barrel 15 in the optical axis direction. At this time, a front guide surface in the circumferential groove 14d of the first linear guide ring 14 is pressed against respective front surfaces of the plurality of relative rotation guide projections 15d, while respective rear surfaces of the second plurality of relative rotation guide projections 14c are pressed against a rear guide surface in the circumferential groove 15e of the third external barrel 15 in the optical axis direction, as clearly shown in Figure 69. At the same time, the front end of the first linear guide ring 14 is positioned between the frontmost

inner flange 15h and the plurality of relative rotation guide projections 15d in the optical axis direction, while front surfaces the set of three forwardly-projecting arc portions 17b of the follower-biasing ring spring 17 are
5 not entirely in pressing contact with the frontmost inner flange 15h. Therefore, when the zoom lens 71 is in the retracted state, a slight space is secured between the set of three follower pressing protrusions 17a and the frontmost inner flange 15h so that each follower pressing
10 protrusion 17a can move to a certain extent in the associated rotation transfer groove 15f in the optical axis direction. In addition, as shown in Figures 35 and 69, each follower pressing protrusion 17a which extends rearward that the tip thereof (rear end thereof in the
15 optical axis direction) is positioned inside the front circumferential slot portion 14e-1 of the associated radial slot 14.

In the state shown in Figures 60 and 64 in which the zoom lens 71 is in the retracted state, the follower-
20 biasing ring spring 17 do not contact with any elements other than the first linear guide ring 14. At this time, although engaged in the set of three rotation transfer grooves 15f, the set of three roller followers 32 stay away from the set of three follower pressing protrusions
25 17a, respectively, because each roller follower 32 is

engaged in the associated rear circumferential slot portion 14e-2 to be positioned in the vicinity of the rear end thereof.

Rotating the third external barrel 15 in the lens barrel advancing direction (upwards as viewed in Figures 5 60 and 69) causes the set of three rotation transfer groove 15f to push the set of three roller followers 32 upwards as viewed in Figures 60 and 69, respectively, to move each roller follower 32 in the associated through-slots 14e 10 from the rear circumferential slot portion 14e-2 to the inclined lead slot portion 14e-3. Since the inclined lead slot portion 14e-3 of each through-slot 14e extends in a direction having both a component in a circumferential direction of the first linear guide ring 15 14 and a component in the optical axis direction, each roller follower 32 gradually moves forward in the optical axis direction as the roller follower 32 moves in the inclined lead slot portion 14e-3 of the associated through-slot 14e toward the front circumferential slot 20 portion 14e-1. However, as long as the roller follower 32 is in the inclined lead slot portion 14e-3 of the associated through-slot 14e, the roller follower 32 is still away from the associated pressing protrusion 17a. This means that the set of three roller followers 32 are 25 not at all biased by the set of three follower pressing

protrusions 17a, respectively. Nevertheless, no substantial problem arises even if backlash between the set of three roller followers 32 and the set of three through-slots 14e are removed thoroughly since the zoom lens 71 is in the retracted state or the transitional state from the retracted state to the ready-to-photograph state when each roller follower 32 is engaged in the rear circumferential slot portion 14e-2 or the inclined lead slot portion 14e-3 of the associated through-slot 14e, respectively. If anything, the load on the zoom motor 150 decreases with decrease in frictional resistance to each roller follower 32.

If the set of three roller followers 32 move from the inclined lead slot portions 14e-3 of the set of three through-slots 14e to the front circumferential slot portions 14e-1 of the same, respectively, by a further rotation of the third external barrel 15 in the lens barrel advancing direction, the first linear guide ring 14, the third external barrel 15 and the set of three roller followers 32 are positioned as shown in Figures 61 and 70 so that the zoom lens 71 is set at the wide-angle extremity. Since the tip of each follower pressing protrusion 17a is positioned inside the front circumferential slot portion 14e-1 of the associated radial slot 14 as described above, each roller follower

32 comes into contact with the associated follower pressing protrusion 17a upon entering the associated front circumferential slot portion 14e-1 (see Figures 33, 61 and 70). This causes each follower pressing protrusion 17a to be pressed forward in the optical axis direction by the associated roller follower 32, thus causing the follower-biasing ring spring 17 to be further deformed to make the shape of the set of three forwardly-projecting arc portions 17b become closer to a flat shape. At this time, each roller follower 32 is pressed against a rear guide surface in the associated front circumferential slot portion 14e-1 in the optical axis direction by the resiliency of the follower-biasing ring spring 17 to thereby remove backlash between the set of three roller followers 32 and the set of three through-slots 14e, respectively.

Thereafter, even if the set of three roller followers 32 move in the front circumferential slot portions 14e-1 of the set of three through-slots 14e during a zooming operation between the positions shown in Figures 61 and 70 in which the zoom lens 71 is set at the wide-angle extremity and the positions shown in Figures 62 and 71 in which the zoom lens 71 is set at the telephoto extremity, each roller follower 32 remains in contact with the associated follower pressing protrusion

17a because each roller follower 32 does not move in the associated rotation transfer groove 15f in the optical axis direction when moving in the associated front circumferential slot portion 14e-1 that extend only in
5 a circumferential direction of the first linear guide ring 14. Therefore, in the zooming range of the zoom lens 71 in which photographing is possible, the set of three roller followers 32 are always biased rearward in the optical axis direction by the roller spring 17, which
10 achieves a stable positioning of the set of three roller followers 32 with respect to the first linear guide ring 14.

Rotating the third external barrel 15 in the lens barrel retracting direction causes the first linear guide
15 ring 14 and the set of three roller followers 32 to operate in the reverse manner to the above described operations. In this reverse operation, each roller follower 32 is disengaged from the associated follower pressing protrusion 17a upon passing a point (wide-angle extremity
20 point) in the associated through-slot 14e which corresponds to the wide-angle extremity of the zoom lens 71 (the position of each roller follower 32 in the associated through-slot 14e in Figure 61). From the wide-angle extremity point down to a point (retracted
25 point) in the associated through-slot 14e which

corresponds to the retracted position of the zoom lens 71 (the position of each roller follower 32 in the associated through-slot 14e in Figure 60), the set of three roller followers 32 receive no pressure from the set of three follower pressing protrusions 17a, respectively. If the set of three follower pressing protrusions 17a do not apply any pressure to the set of three roller followers 32, the frictional resistance to each roller follower 32 becomes small when moving in the associated through-slot 14e. Consequently, the load on the zoom motor 150 decreases with decrease in frictional resistance to each roller follower 32.

As can be understood from the above descriptions, the set of three follower pressing protrusions 17a, which are respectively fixed at the locations of the set of three roller followers 32 in the optical axis direction in the set of three rotation transfer grooves 15f when the zoom lens 71 is in the ready-to-photograph state, automatically bias the set of three roller followers 32 rearward to press the set of three roller followers 32 against rear guide surfaces of the front circumferential slot portions 14e-1 of the set of three through-slots 14e immediately after the set of three roller followers 32 which are guided by the inclined lead slot portions 14e-3 of the set of three through-slots 14e to move forward in

the optical axis direction reach their respective photographing positions in a rotatable range at an axial fixed position (i.e., in the front circumferential slot portions 14e-1). With this structure, the backlash
5 between the set of three roller followers 32 and the set of three through-slots 14e can be removed by a simple structure using a single biasing member: the follower-biasing ring spring 17. Moreover, the follower-biasing ring spring 17 consumes little space in
10 the zoom lens 71 since the follower-biasing ring spring 17 is a substantially simple annular member disposed along an inner peripheral surface and since the set of three follower pressing protrusions 17a are positioned in the set of three rotation transfer grooves 15f, respectively.
15 Accordingly, in spite of its small and simple structure, the follower-biasing ring spring 17 can make the cam ring 11 positioned precisely at a predetermined fixed position in the optical axis direction with stability in the ready-to-photograph state of the zoom lens 71. This
20 insures optical accuracy of the photographing optical system such as the first lens group LG1 and the second lens group LG2. Furthermore, the follower-biasing ring spring 17 can be removed easily because the set of three forwardly-projecting arc portions 17b are simply held and
25 supported between the frontmost inner flange 15h and the

plurality of relative rotation guide projections 15d.

The follower-biasing ring spring 17 has not only a function of biasing the set of three roller followers 32 rearward in the optical axis direction to position the
5 cam ring 11 precisely with respect to the first linear guide ring 14 in the optical axis direction, but also a function of biasing the first linear guide ring 14 rearward in the optical axis direction to give stability to positioning of the first linear guide ring 14 with
10 respect to the third external barrel 15 in the optical axis direction. Although the second plurality of relative rotation guide projections 14c and the circumferential groove 15e are engaged with each other to be slightly movable relative to each other in the
15 optical axis direction while the plurality of relative rotation guide projections 15d and the circumferential groove 14d are engaged with each other to be slightly movable relative to each other in the optical axis direction as shown in Figures 69 through 72, both backlash
20 between the second plurality of relative rotation guide projections 14c and the circumferential groove 15e and backlash between the plurality of relative rotation guide projections 15d and the circumferential groove 14d are removed since the front end of the first linear guide ring
25 14 contacts with the follower-biasing ring spring 17 to

be biased rearward in the optical axis direction by the follower-biasing ring spring 17. Accordingly, in the case where three annular members: the cam ring 11, the first linear guide ring 14 and the third external barrel
5 15 are regarded as a rotating-advancing/rotating-retracting unit, all the different backlashes arising in this whole rotating-advancing/rotating-retracting unit can be removed by a single biasing member: the follower-biasing ring spring 17. This achieves a quite
10 simple backlash removing structure.

Figures 73 through 75 show elements of a linear guide structure in section which guides the first external barrel 12 (which supports the first lens group LG1) and the second lens group moving frame 8 (which supports the
15 second lens group LG2) linearly in the optical axis direction without rotating each of the first external barrel 12 and the second lens group moving frame 8 about the lens barrel axis Z0. Figures 76 through 78 show the elements of the linear guide structure in oblique
20 perspective. Figures 73, 74 and 75 show the linear guide structure when the zoom lens 71 is set at the wide-angle extremity, when the zoom lens 71 is set at the telephoto extremity, and when the zoom lens 71 is in the retracted state, respectively. In each of the cross sectional
25 views in Figures 73 through 75, the elements of the linear

guide structure are crosshatched for the purpose of illustration. In addition, in each of the cross sectional views in Figures 73 through 75, among all the rotatable elements only the cam ring is crosshatched by
5 dashed lines for the purpose of illustration.

The cam ring 11 is a double-side grooved cam ring that is provided on an outer peripheral surface thereof with the set of three outer cam grooves 11b for moving the first external barrel 12 in a predetermined moving
10 manner, and that is provided on an inner peripheral surface of the cam ring 11 with the plurality of inner cam grooves 11a (11a-1 and 11a-2) for moving the second lens group moving frame 8 in a predetermined moving manner. Accordingly, the first external barrel 12 is positioned
15 radially outside the cam ring 11 while the second lens group moving frame 8 is positioned radially inside the cam ring 11. On the other hand, the first linear guide ring 14, which is adopted for guiding each of the first external barrel 12 and the second lens group moving frame
20 8 linearly without rotating each of the first external barrel 12 and the second lens group moving frame 8 about the lens barrel axis Z0, is positioned radially outside the cam ring 11.

In this linear guide structure having the above
25 described positional relationship among the first linear

guide ring 14, the first external barrel 12 and the second lens group moving frame 8, the first linear guide ring 14 directly guides the second external barrel 13 (which serves as a linear guide member for guiding the first external barrel 12 linearly in the optical axis direction without rotating the same about the lens barrel axis Z0) and the second linear guide ring 10 (which serves as a linear guide member for guiding the second lens group moving frame 8 linearly in the optical axis direction without rotating the same about the lens barrel axis Z0) linearly in the optical axis direction without rotating the same about the lens barrel axis Z0. The second external barrel 13 is positioned radially between the cam ring 11 and the first linear guide ring 14, and guided linearly in the optical axis direction without rotating about the lens barrel axis Z0 by engagement of the set of six radial projections 13a, which are formed on an outer peripheral surface of the second external barrel 13, with the set of six second linear guide grooves 14g, respectively. Moreover, the second external barrel 13 guides the first external barrel 12 linearly in the optical axis direction without rotating the same about the lens barrel axis Z0 by engagement of the set of three linear guide grooves 13b, which are formed on an inner peripheral surface of the second external barrel 13, with

the set of three engaging protrusions 12a of the first external barrel 12, respectively. On the other hand, as for the second linear guide ring 10, to make the first linear guide ring 14 guide the second lens group moving frame 8 that is positioned inside the cam ring 11, the ring portion 10b is positioned behind the cam ring 11, the set of three bifurcated projections 10a are formed to project radially outwards from the ring portion 10b to be respectively engaged in the set of three pairs of first linear guide grooves 14f, and the set of three linear guide keys 10c are formed to project forward from the ring portion 10b in the optical axis direction to be respectively engaged in the set of three guide grooves 8a.

15 In the case of a linear guide structure having conditions similar to conditions of the linear guide structure shown in Figures 73 through 75 that two linearly guided outer and inner movable elements (the first external barrel 12 and the second lens group moving frame 20 8) are respectively positioned outside and inside a double-side grooved cam ring (the cam ring 11) and that a primary linear guide member (the first linear guide ring 14) of the linear guide structure is positioned outside the cam ring, a secondary linear guide member serving as 25 the outer movable element (which corresponds to the second

external barrel 13) is disposed outside the cam ring, while a linearly guided movable member (which corresponds to the first external barrel 12) which is guided linearly in the optical axis direction without rotating by the
5 secondary linear guide member is provided with a set of linear guide portions for guiding a movable member serving as the inner movable element (which corresponds to the second lens group moving frame 8) positioned inside the cam ring linearly in the optical axis direction without
10 rotating the same in a conventional zoom lens. In other words, in the linear guide structure of such a conventional zoom lens, each of the aforementioned set of linear guide portions of the outer movable element extend radially inwards from the outside of the cam ring
15 to the inside of the cam ring to be engaged with the inner movable element through a single path. According to this type of conventional linear guide structure, the resistance produced due to linear guiding operations of the outer and inner movable elements of the linear guide
20 structure increases when a relative velocity in the optical axis direction between the two linearly guided movable elements that are respectively positioned outside and inside the cam ring is fast. In addition, since the inner movable element is indirectly guided
25 linearly in the optical axis direction without rotating

via the outer movable element, the inner movable element, in particular, is difficult to be guided linearly in the optical axis direction without rotating with a high degree of travel accuracy.

5 In contrast to such a conventional linear guide structure, according to the linear guide structure of the zoom lens 71 shown in Figures 73 through 75, the aforementioned resistance problem can be prevented from occurring by the structure wherein the second external
10 barrel 13, which serves as a linear guide member for guiding the first external barrel 12 (positioned outside the cam ring 11) linearly in the optical axis direction without rotating the same about the lens barrel axis Z0, is engaged with the set of six second linear guide grooves
15 14g while the second linear guide ring 10, which serves as a linear guide member for guiding the second lens group moving frame 8 (positioned inside the cam ring 11) linearly in the optical axis direction without rotating the same about the lens barrel axis Z0, is engaged with
20 the set of three pairs of first linear guide grooves 14f so that the second external barrel 13 and the second linear guide ring 10 are directly guided by the first linear guide ring 14 through two paths : a first path (inner path) extending from the set of three pairs of first linear guide
25 grooves 14f to the set of three bifurcated projections

10a and a second path (outer path) extending from the set of six second linear guide grooves 14g to the set of six radial projections 13a. Moreover, the first linear guide ring 14 that directly guides each of the second linear guide ring 10 and the second external barrel 13 linearly at the same time is, in effect, reinforced by the second linear guide ring 10 and the second external barrel 13. This structure makes it easy for the linear guide structure to secure sufficient strength.

10 Furthermore, each pair of first linear guide grooves 14f, which are adopted for guiding the second linear guide ring 10 linearly in the optical axis direction without rotating the same about the lens barrel axis Z0, are formed by using two opposed side walls between which the associated second linear guide groove 14g is formed. This structure is advantageous to make the linear guide structure simple, and does not impair the strength of the first linear guide ring 14 very much.

20 The relationship between the cam ring 11 and the second lens group moving frame 8 will be hereinafter discussed in detail. As described above, the plurality of inner cam grooves 11a, which are formed on an inner peripheral surface of the cam ring 11, consist of the set of three front inner cam grooves 11a-1 that are formed at different circumferential positions, and the set of

three rear inner cam grooves 11a-2 that are formed at different circumferential positions behind the set of three front inner cam grooves 11a-1 in the optical axis direction. Each rear inner cam groove 11a-2 is formed
5 as a discontinuous cam groove as shown in Figure 17. All the six cam grooves of the cam ring 11: the set of three front inner cam grooves 11a-1 and the set of three rear inner cam grooves 11a-2 trace six reference cam diagrams "VT" having the same shape and size, respectively. Each
10 reference cam diagram VT represents the shape of each cam groove of the set of three front inner cam grooves 11a-1 and the set of three rear inner cam grooves 11a-2, and includes a lens-barrel operating section and a lens-barrel assembling/disassembling section, wherein the
15 lens-barrel operating section consists of a zooming section and a lens-barrel retracting section. The lens-barrel operating section serves as a control section which controls movement of the second lens group moving frame 8 with respect to the cam ring 11, and which is to
20 be distinguished from the lens-barrel assembling/disassembling section that is used only when the zoom lens 71 is assembled or disassembled. The zooming section serves as a control section which controls the movement of the second lens group moving frame 8 with
25 respect to the cam ring 11, especially from a position

of the second lens group moving frame 8 which corresponds to the wide-angle extremity of the zoom lens 71 to another position of the second lens group moving frame 8 which corresponds to the telephoto extremity of the zoom lens 71, and which is to be distinguished from the lens-barrel retracting section. If each front inner cam groove 11a-1 and the rear inner cam groove 11a-2 positioned therebehind in the optical axis direction are regarded as a pair, it can be said that the cam ring 11 is provided, at regular intervals in a circumferential direction of the cam ring 11, with three pairs of inner cam grooves 11a for guiding the second lens group LG2.

As can be seen in Figure 17, the length of an axial range W1 of the reference cam diagrams VT of the set of three front inner cam grooves 11a-1 in the optical axis direction (the horizontal direction as viewed in Figure 17), which is equivalent to an axial range of the reference cam diagrams VT of the set of three rear inner cam grooves 11a-2 in the optical axis direction, is greater than a length W2 of the cam ring 11 in the optical axis direction. The length of the zooming section included in the axial range W1 of the reference cam diagrams VT of the set of three front inner cam grooves 11a-1 (or the rear inner cam grooves 11a-2) in the optical axis direction is represented by a length W3 shown in Figure 17 which is

alone substantially equivalent to the length W_2 of the cam ring 11. This means that a set of cam grooves each having a sufficient length will not be obtained for the present embodiment of the cam ring 11 if designed according to a conventional method of formation of cam groove wherein a set of long cam grooves which entirely trace a corresponding set of long cam diagrams are formed on a peripheral surface of a cam ring. According to a cam mechanism of the present embodiment of the zoom lens, a sufficient range of movement of the second lens group moving frame 8 in the optical axis direction can be secured without increasing the length of the cam ring 11 in the optical axis direction. The detail of this cam mechanism will be discussed hereinafter.

Each front inner cam groove 11a-1 does not cover the entire range of the associated reference cam diagram VT while each rear inner cam groove 11a-2 does not cover the entire range of the associated reference cam diagram VT either. A range of each front inner cam groove 11a-1 which is included in the associated reference cam diagram VT is partly different from a range of each rear inner cam groove 11a-2 which is included in the associated reference cam diagram VT. Each reference cam diagram VT can be roughly divided into four sections: first through fourth sections VT1 through VT4. The first section VT1

extends in the optical axis direction. The second section VT2 extends from a first inflection point VTh positioned at the rear end of the first section VT1 to a second inflection point VTm positioned behind the first
5 inflection point VTh in the optical axis direction. The third section VT3 extends from the second inflection point VTm to a third inflection point VTn positioned in front of the second inflection point VTm in the optical axis direction. The fourth section VT4 extends from the third
10 inflection point VTn. The fourth section VT4 is used only when the zoom lens 71 is assembled or disassembled, and is included in both each front inner cam groove 11a-1 and each rear inner cam groove 11a-2. Each front inner cam groove 11a-1 is formed in the vicinity of the front end
15 of the cam ring 11 not to include the entire part of the first section VT1 and a part of the second section VT2, and is formed to include a front end opening R1 at an intermediate point of the second section VT2 so that the front end opening R1 opens on a front end surface of the
20 cam ring 11. On the other hand, each rear inner cam groove 11a-2 is formed in the vicinity of the rear end of the cam ring 11 not to include adjoining portions of the second section VT2 and the third section VT3 on opposite sides of the second inflection point VTm. In addition, each
25 rear inner cam groove 11a-2 is formed to include a front

end opening R4 (which corresponds to the aforementioned front open end section 11a-2x) at the front end of the first section VT1 so that the front end opening R4 opens on a front end surface of the cam ring 11. A missing
5 portion of each front inner cam groove 11a-1 which lies on the associated reference cam diagram VT is included in the associated rear inner cam groove 11a-2 that is positioned behind the front inner cam groove 11a-1 in the optical axis direction, whereas a missing portion of each
10 rear inner cam groove 11a-2 which lies on the associated reference cam diagram VT is included in the associated front inner cam groove 11a-1 that is positioned in front of the rear inner cam groove 11a-2 in the optical axis direction. Namely, if each front inner cam groove 11a-1 and the associated rear inner cam groove 11a-2 are
15 combined into a single cam groove, this signal cam groove will include the entire part of one reference cam diagram VT. In other words, one of each front inner cam groove 11a-1 and the associated rear inner cam groove 11a-2 is
20 complemented by the other. The width of each front inner cam groove 11a-1 and the width of each rear inner cam groove 11a-2 are the same.

Meanwhile, as shown in Figure 19, the plurality of cam followers 8b, which are respectively engaged in the
25 plurality of inner cam grooves 11a, consist of the set

of three front cam followers 8b-1 that are formed at different circumferential positions, and the set of three rear cam followers 8b-2 that are formed at different circumferential positions behind the set of three front cam followers 8b-1 in the optical axis direction, wherein each front cam follower 8b-1 and the rear cam follower 8b-2 positioned therebehind in the optical axis direction are provided as a pair in a manner similar to each pair of inner cam grooves 11a. The space between the set of three front cam followers 8b-1 and the set of three rear cam followers 8b-2 in the optical axis direction is determined so that the set of three front cam followers 8b-1 are respectively engaged in the set of three front inner cam grooves 11a-1 and so that the set of three rear cam followers 8b-2 are respectively engaged in the set of three rear inner cam grooves 11a-2. The diameter of each front cam follower 8b-1 and the diameter of each rear cam follower 8b-2 are the same.

Figure 79 shows the positional relationship between the plurality of inner cam grooves 11a and the plurality of cam followers 8b when the zoom lens 71 is the retracted state as shown in Figure 10. When the zoom lens 71 is the retracted state, each front cam follower 8b-1 is positioned in the associated front inner cam groove 11a-1 in the vicinity of the third inflection point VTn thereof

while each rear cam follower 8b-2 is positioned in the associated rear inner cam groove 11a-2 in the vicinity of the third inflection point VTn thereof. Since each front inner cam groove 11a-1 includes a portion thereof in the vicinity of the third inflection point VTn while each rear inner cam groove 11a-2 includes a portion thereof in the vicinity of the third inflection point VTn, each front cam follower 8b-1 and each rear cam follower 8b-2 are engaged in the associated front inner cam groove 11a-1 and the associated rear inner cam groove 11a-2, respectively.

Rotating the cam ring 11 in the lens barrel advancing direction (upwards as viewed in Figure 79) in the retracted state shown in Figure 79 causes each front cam follower 8b-1 and each rear cam follower 8b-2 to be guided rearward in the optical axis direction to move on the third section VT3 toward the second inflection point VTm by the associated front inner cam groove 11a-1 and the associated rear inner cam groove 11a-2, respectively. In the middle of this movement of each cam follower 8b, each rear cam follower 8b-2 is disengaged from the associated rear inner cam groove 11a-2 through a first rear end opening R3 thereof which opens on a rear end surface of the cam ring 11 because each rear inner cam groove 11a-2 does not include adjoining portions of the second section VT2 and

the third section VT3 on opposite sides of the second inflection point VTm. At this time, each front cam follower 8b-1 remains engaged in the associated front inner cam groove 11a-1 since each front inner cam groove 11a-1 includes a rear portion thereof in the optical axis direction which corresponds to the missing rear portion of each rear inner cam groove 11a-2 in the optical axis direction. On or after each rear cam follower 8b-2 being disengaged from the associated rear inner cam groove 11a-2 through the first rear end opening R3 thereof, the second lens group moving frame 8 moves in the optical axis direction by rotation of the cam ring 11 only due to engagement of each front cam follower 8b-1 with the associated front inner cam groove 11a-1.

Figure 80 shows the positional relationship between the plurality of inner cam grooves 11a and the plurality of cam followers 8b when the zoom lens 71 is in the state shown below the photographing lens axis Z1 in Figure 9 in which the zoom lens 71 is set at the wide-angle extremity. In this state shown below the photographing lens axis Z1 in Figure 9, each front cam follower 8b-1 is positioned in the second section VT2 slightly beyond the second inflection point VTm. Although each rear cam follower 8b-2 is currently disengaged from the associated rear inner cam groove 11a-2 through the first rear end

opening R3 thereof as described above, each rear cam follower 8b-2 remains positioned on the associated reference cam diagram VT because the associated front cam follower 8b-1 positioned in front of the rear cam follower 8b-2 remains engaged in the associated front inner cam groove 11a-1.

Rotating the cam ring 11 in the lens barrel advancing direction (upward as viewed in Figure 80) in the state shown in Figure 80, in which the zoom lens 71 is set at the wide-angle extremity, causes each front cam follower 8b-1 to be guided forward in the optical axis direction to move on the second section VT2 toward the first section VT1 by the associated front inner cam groove 11a-1. With this forward movement of each front cam follower 8b-1, each rear cam follower 8b-2 which is currently disengaged from the associated rear inner cam groove 11a-2 moves on the second section VT2 toward the first section VT1, and shortly enters a second rear end opening R2 formed on a rear end surface of the cam ring 11 to be re-engaged in the associated rear inner cam groove 11a-2. On or after this re-engagement of each rear cam follower 8b-2 with the associated rear inner cam groove 11a-2, each front cam follower 8b-1 and each rear cam follower 8b-2 are guided by the associated front inner cam groove 11a-1 and the associated rear inner cam groove 11a-2, respectively.

However, a shortly after the re-engagement of each rear cam follower 8b-2 with the associated rear inner cam groove 11a-2, each front cam follower 8b-1 is disengaged from the associated front inner cam groove 11a-1 through the front end opening R1 because a front end portion of each front inner cam groove 11a-1 which lies on the associated reference cam diagram VT is missing. At this time, each rear cam follower 8b-2 remains engaged in the associated rear inner cam groove 11a-2 since each rear inner cam groove 11a-2 includes a front end portion thereof in the optical axis direction which corresponds to the missing front end portion of each front inner cam groove 11a-1 in the optical axis direction. On or after each front cam follower 8b-1 being disengaged from the associated front inner cam groove 11a-1 through the front end opening R1 thereof, the second lens group moving frame 8 moves in the optical axis direction by rotation of the cam ring 11 only due to engagement of each rear cam follower 8b-2 with the associated rear inner cam groove 11a-2.

Figure 81 shows the positional relationship between the plurality of inner cam grooves 11a and the plurality of cam followers 8b when the zoom lens 71 is in the state shown above the photographing lens axis Z1 in Figure 9 in which the zoom lens 71 is set at the telephoto extremity.

In this state shown above the photographing lens axis Z1 in Figure 9, each front cam follower 8b-1 is positioned in the second section VT2 in the vicinity of the first inflection point VTh. Although each front cam follower 8b-1 is currently disengaged from the associated front inner cam groove 11a-1 through the front end opening R1 thereof as described above, each front cam follower 8b-1 remains on the associated reference cam diagram VT because the associated rear cam follower 8b-2 positioned behind the front cam follower 8b-1 remains engaged in the associated rear inner cam groove 11a-2.

Further rotating the cam ring 11 in the lens barrel advancing direction (upward as viewed in Figure 81) in the state shown in Figure 81, in which the zoom lens 71 is set at the telephoto extremity, causes each rear cam follower 8b-2 to enter the first section VT1 via the first inflection point VTh as shown in Figure 82. At this time, each front cam follower 8b-1 has been disengaged from the associated front inner cam groove 11a-1, and merely each rear cam follower 8b-2 is engaged in a front end portion (the first section VT1) of the associated rear inner cam groove 11a-2 which extends in the optical axis direction, so that the second lens group moving frame 8 can be removed from the cam ring 11 from the front thereof in the optical axis direction to remove each rear cam follower 8b-2 from

the associated rear inner cam groove 11a-2 via the front end opening R4. Accordingly, Figure 82 shows a state where the cam ring 11 and the second lens group moving frame 8 are put together or removed from each other.

5 As described above, in the present embodiment of the zoom lens, each pair of cam grooves having the same reference cam diagram VT, i.e., each front inner cam groove 11a-1 and the associated rear inner cam groove 11a-2 are formed at different points in the optical axis
10 direction on the cam ring 11; moreover, each front inner cam groove 11a-1 and the associated rear inner cam groove 11a-2 are formed so that one end of the front inner cam groove 11a-1 opens on a front end surface of the cam ring 11 without the front inner cam groove 11a-1 including the
15 entire part of the associated reference cam diagram VT and so that one end of the rear inner cam groove 11a-2 opens on a rear end surface of the cam ring 11 without the rear inner cam groove 11a-2 including the entire part of the associated reference cam diagram VT; and
20 furthermore, one of the front inner cam groove 11a-1 and the rear inner cam groove 11a-2 is complemented by the other to include the entire part of one reference cam diagram VT. In addition, only each rear cam follower 8b-2 is engaged in the associated rear inner cam groove 11a-2
25 when the second lens group moving frame 8 is positioned

at a front limit for the axial movement thereof with respect to the cam ring 11 (which corresponds to the state shown above the photographing lens axis Z1 in Figure 9 in which the zoom lens 71 is set at the telephoto
5 extremity), while only each front cam follower 8b-1 is engaged in the associated front inner cam groove 11a-1 when the second lens group moving frame 8 is positioned at a rear limit for the axial movement thereof with respect to the cam ring 11 (which corresponds to a state shown
10 below the photographing lens axis Z1 in Figure 9 in which the zoom lens 71 is set at the wide-angle extremity). With this structure, a sufficient range of movement of the second lens group moving frame 8 in the optical axis direction which is greater than the range of movement of
15 the cam ring 11 in the optical axis direction is achieved. Namely, the length of the cam ring 11 in the optical axis direction can be reduced without sacrificing the range of movement of the second lens group moving frame 8, which supports the second lens group LG2 via the second lens
20 frame 6, in the optical axis direction.

In a typical cam mechanism having a rotatable cam ring on which a set of cam grooves are formed and a driven member having a set of cam followers which are respectively engaged in the set of cam grooves, the amount
25 of movement of each cam follower per unit of rotation of

the cam ring decreases to thereby make it possible to move the driven member with a higher degree of positioning accuracy by rotation of the cam ring as the degree of inclination of each cam groove on the cam ring relative to the rotational direction of the cam ring becomes small, i.e., as the direction of extension of each cam groove becomes close to a circumferential direction of the cam ring. In addition, the degree of resistance to the cam ring when it rotates becomes smaller to thereby make the driving torque for rotating the cam ring smaller as the degree of inclination of each cam groove on the cam ring relative to the rotational direction of the cam ring becomes small. A reduction of the driving torque results in an increase in durability of elements of the cam mechanism and a decrease in power consumption of the motor for driving the cam ring, and makes it possible to adopt a small motor for driving the cam ring to downsize the lens barrel. Although it is known that the actual contours of the cam grooves are determined in consideration of various factors such as the effective area of an outer or inner peripheral surface of the cam ring and the maximum angle of rotation of the cam ring, it is generally the case that the cam grooves have the above described tendencies.

As described above, it can be said that the cam ring

11 is provided, at regular intervals in a circumferential direction of the cam ring 11, with three pairs (groups) of inner cam grooves 11a for guiding the second lens group LG2 if each front inner cam groove 11a-1 and the rear inner cam groove 11a-2 positioned therebehind in the optical axis direction are regarded as a pair (group). Similarly, it can be said that the second lens group moving frame 8 is provided, at regular intervals in a circumferential direction thereof, with three pairs (groups) of cam followers 8b if each front rear cam follower 8b-1 and the rear cam follower 8b-2, positioned therebehind in the optical axis direction, are regarded as a pair (group). As for the reference cam diagrams VT of the plurality of inner cam grooves 11a, provided only three of the reference cam diagrams VT are to be arranged on an inner peripheral surface of the cam ring 11 along a line thereon extending in a circumferential direction of the cam ring 11, the three reference cam diagrams VT will not interfere with one another on the inner peripheral surface of the cam ring 11 though each reference cam diagram VT has an undulating shape. However, in the present embodiment of the zoom lens, in order to shorten the length of the cam ring 11 in the optical axis direction to thereby minimize the length of the zoom lens 71, six reference cam diagrams VT need to be arranged on the inner peripheral surface

of the cam ring 11 in total because the set of three front inner cam grooves 11a-1 and the corresponding set of three rear cam grooves (three discontinuous rear cam grooves) 11a-2, six cam grooves in total, need to be formed separately on front and rear portions on the inner peripheral surface of the cam ring 11 in the optical axis direction, respectively. Although each of the six inner cam grooves 11a-1 and 11a-2 is shorter than the reference cam diagram VT, it is generally the case that the space for the inner cam grooves 11a-1 and 11a-2 on the cam ring 11 becomes tighter as the number of the cam grooves is great. Therefore, if the number of the cam grooves is great, it is difficult to form the cam grooves on the cam ring without making the cam grooves interfering with each other. To prevent this problem from occurring, it has been conventionally practiced to increase the degree of inclination of each cam groove relative to the rotational direction of the cam ring (i.e., to make the direction of extension of each cam groove close to a circumferential direction of the cam ring) or to increase the diameter of the cam ring to enlarge the area of a peripheral surface of the cam ring on which the cam grooves are formed. However, increasing the degree of inclination of each cam groove is not desirable in terms of the attainment of a high degree of positioning accuracy in driving a driven

member driven by the cam ring and also a saving in the driving torque for rotating the cam ring, and increasing the diameter of the cam ring is not desirable either because the zoom lens will be increased in size.

5 In contrast to such conventional practices, according to the present embodiment of the zoom lens, the inventor of the present invention has found the fact that a substantial performance characteristics of the cam mechanism is maintained even if each front inner cam
10 groove 11a-1 intersects one of the set of three rear inner cam grooves 11a-2, as long as the reference cam diagrams VT of the six inner cam grooves 11a (11a-1 and 11a-2) are the same while one cam follower of each pair of cam
15 followers (each front cam follower 8b-1 and the associated rear cam follower 8b-2) remains engaged in the associated inner cam groove 11a-1 or 11a-2 at the moment at which the other cam follower 8b-1 or 8b-2 passes through a point
20 of intersection between the front inner cam groove 11a-1 and the rear inner cam groove 11a-2. On the basis of this fact, each front inner cam groove 11a-1 and adjacent one
25 of the set of three rear inner cam grooves 11a-2, which are adjacent to each other in a circumferential direction of the cam ring 11, are formed to intersect each other intentionally without changing the shape of each reference cam diagram VT and without increasing the

diameter of the cam ring 11. More specifically, if the three pairs of inner cam grooves 11a are respectively treated as a first pair of cam grooves G1, a second pair of cam grooves G2 and a third pair of cam grooves G3 as shown in Figure 17, the front inner cam groove 11a-1 of the first pair G1 and the rear inner cam groove 11a-2 of the second pair G2, which are adjacent to each other in a circumferential direction of the cam ring 11, intersect each other, the first inner cam groove 11a-1 of the second pair G2 and the rear inner cam groove 11a-2 of the third pair G3, which are adjacent to each other in a circumferential direction of the cam ring 11, intersect each other, and the front inner cam groove 11a-1 of the third pair G3 and the rear inner cam groove 11a-2 of the first pair G1, which are adjacent to each other in a circumferential direction of the cam ring 11, intersect each other.

To make one cam follower of each pair of cam followers (each front cam follower 8b-1 and the associated rear cam follower 8b-2) remain properly engaged in the associated inner cam groove 11a-1 or 11a-2 at the moment at which the other cam follower 8b-1 or 8b-2 passes through the point of intersection between the front inner cam groove 11a-1 and the rear inner cam groove 11a-2, the front inner cam groove 11a-1 and the rear inner cam groove 11a-2

of each pair of the first through third pairs of cam grooves G1, G2 and G3 are formed not only at different axial positions in the optical axis direction but also at different circumferential positions in a circumferential direction of the cam ring 11. The positional difference in a circumferential direction of the cam ring 11 between the front inner cam groove 11a-1 and the rear inner cam groove 11a-2 of each pair of the first through third pairs of cam grooves G1, G2 and G3 is indicated by "HJ" in Figure 17. This positional difference HJ changes the point of intersection between the front inner cam groove 11a-1 and the rear inner cam groove 11a-2 in a circumferential direction of the cam ring 11. Consequently, in each pair of the first through third pairs of cam grooves G1, G2 and G3, the point of intersection is positioned in the vicinity of the second inflection point VTm on the third section VT3 of the front inner cam groove 11a-1, and also in the vicinity of the first inflection point VTh the front end opening R4 (the front open end section 11a-2x) at the front end of the first section VT1.

As can be understood from the above descriptions, at the moment at which the set of three front cam followers 8b-1 pass through the points of intersection in the set of three front inner cam grooves 11a-1, the set of three

rear cam followers 8b-2 remain engaged in the set of three rear inner cam grooves 11a-2 so that the set of three front cam followers 8b-1 can pass through the points of intersection without being disengaged from the set of three front inner cam grooves 11a-1, respectively (see Figure 83), by forming the set of three front inner cam grooves 11a-1 and the corresponding set of three rear inner cam grooves 11a-2 in the above described manner. Although each front inner cam groove 11a-1 has the point of intersection therein between the zooming section and the lens-barrel retracting section, i.e. in the lens-barrel operating section, the lens barrel 71 can securely be advanced and retracted with the cam ring 11 regardless of the existence of a section of each front inner cam groove 11a-1 which includes the point of intersection therein.

Although each front cam follower 8b-1 is already disengaged from the associated front inner cam groove 11a-1 when each rear cam follower 8b-2 reaches the point of intersection in the rear inner cam groove 11a-2 as shown in Figure 82, this point of intersection is positioned in the lens-barrel assembling/disassembling section, i.e., out of the lens-barrel operating section, so that each rear cam follower 8b-2 is not in a state where it receives torque from the cam ring 11. Accordingly, as

for the set of three rear inner cam grooves 11a-2, a possibility of each rear cam follower 8b-2 being disengaged from the associated rear inner cam groove 11a-2 at the point of intersection therein does not have to be
5 taken into consideration when the zoom lens 71 is in the ready-to-photograph state.

The point of intersection in each front inner cam groove 11a-1 is in a section thereof through which the associated front cam follower 8b-1 passes between a state
10 shown in Figure 79 in which the zoom lens 71 is in the retracted state and a state shown in Figure 80 in which the zoom lens 71 is in the wide-angle extremity, while the point of intersection in each rear inner cam groove 11a-2 is in the lens-barrel assembling/disassembling
15 section as described above. Therefore, either each front inner cam groove 11a-1 or each rear inner cam groove 11a-2 does not have the point of intersection therein in the zooming range between the wide-angle extremity and the telephoto extremity. This makes it possible to insure
20 a high degree of positioning accuracy in driving the second lens group LG2 during a zooming operation of the zoom lens 71 regardless of the existence of the point of intersection between cam grooves.

Namely, the timing of engagement or disengagement
25 of each cam follower in or from the associated cam groove

can be varied by adjusting the aforementioned positional difference b. Moreover, the point of intersection between two cam grooves (11a-1 and 11a-2) can be positioned in an appropriate section therein which does not affect any adverse effect on a zooming operation by adjusting the aforementioned positional difference b.

As can be understood from the above descriptions, in the present embodiment of the zoom lens, each front inner cam groove 11a-1 and each rear inner cam groove 11a-2 are successfully arranged on the inner peripheral surface of the cam ring 11 in a space-saving fashion without deteriorating the positioning accuracy in driving the second lens group LG2 by making each front inner cam groove 11a-1 and adjacent one of the set of three rear inner cam grooves 11a-2, which are adjacent to each other in a circumferential direction of the cam ring 11, intersect each other intentionally and further by forming each front inner cam groove 11a-1 and the associated rear inner cam groove 11a-2 not only at different axial positions in the optical axis direction but also at different circumferential positions in a circumferential direction of the cam ring 11. Accordingly, not only the length of the cam ring 11 in the optical axis direction but also the diameter of the cam ring 11 can be reduced.

The second lens group moving frame 8 is movable in

the optical axis direction by a comparatively great amount of movement as compared with the length of the zoom lens by the above described structure of the cam ring 11. However, it is conventionally the case that it is
5 difficult to guide such a moving member the moving range of which is great linearly in a direction of an optical axis without rotating the moving member about the optical axis by a small linear guide structure. In the present embodiment of the zoom lens, the second lens group moving
10 frame 8 can be guided linearly in the optical axis direction without rotating about the lens barrel axis 20 with reliability, without increasing the size of the second lens group moving frame 8.

As can be seen from Figures 73 through 75 and 79
15 through 82, the second linear guide ring 10 does not move in the optical axis direction relative to the cam ring 11. This is because the discontinuous outer edge of the ring portion 10b of the second linear guide ring 10 is engaged in the discontinuous circumferential groove 11e
20 of the cam ring 11 to be rotatable about the lens barrel axis 20 relative to the cam ring 11 and to be immovable relative to the cam ring 11 in the optical axis direction. On the other hand, in the operating range of the zoom lens 71 from the retracted position to the telephoto extremity
25 via the wide-angle extremity, the second lens group moving

frame 8 is positioned at the rear limit for the axial movement thereof with respect to the cam ring 11 when the zoom lens 71 is set at a focal length in the vicinity of the wide-angle extremity, while the second lens group moving frame 8 is positioned at the front limit for the axial movement thereof with respect to the cam ring 11 when the zoom lens 71 is set at the telephoto extremity. More specifically, the second lens group moving frame 8 is positioned at the rear limit for the axial movement thereof with respect to the cam ring 11 when each front cam follower 8b-1 and each rear cam follower 8b-2 are positioned on the second inflection point VTm of the associated front inner cam groove 11a-1 and the second inflection point VTm of the associated rear inner cam groove 11a-2, respectively, namely, when each front cam follower 8b-1 and each rear cam follower 8b-2 are each positioned in close vicinity of its wide-angle position between this wide-angle position and its retracted position.

As for the second linear guide ring 10, the set of three linear guide keys 10c project forward in the optical axis direction from the ring portion 10b, whereas the rear end of the second lens group moving frame 8 projects rearward, beyond the ring portion 10b of the second linear guide ring 10, when the zoom lens 71 is set at the

wide-angle extremity as shown in Figures 73 and 80. To allow the second lens group moving frame 8 having such a structure to move in the optical axis direction with respect to the second linear guide ring 10, the ring portion 10b of the second linear guide ring 10 is provided with a central aperture 10b-T (see Figure 88) which has a diameter allowing the second lens group moving frame 8 to pass therethrough. The set of three linear guide keys 10c are positioned to project forward through the central aperture 10b-T. In other words, the set of three linear guide keys 10c are formed on the second linear guide ring 10 at radial positions not interfering with the ring portion 10b. Front and rear ends of each guide groove 8a that is formed on the second lens group moving frame 8 are open on front and rear end surfaces of the second lens group moving frame 8 so that the associated linear guide key 10c can project forward and rearward from the front and the rear of the second lens group moving frame 8, respectively.

Therefore, the second lens group moving frame 8 does not interfere with the ring portion 10b of the second linear guide ring 10 wherever the second lens group moving frame 8 is positioned relative to the second linear guide ring 10 in the optical axis direction. This makes it possible to utilize the full ranges of each linear guide

key 10c and each guide groove 8a as sliding parts for guiding the second lens group moving frame 8 linearly without rotating the same about the lens barrel axis Z0. For instance, in the state shown in Figures 84 and 85 showing the positional relationship between the second lens group moving frame 8 and the second linear guide ring 10 when the zoom lens 71 is set at the wide-angle extremity (i.e., when the second lens group moving frame 8 is positioned at its rear limit for the axial movement thereof with respect to the second linear guide ring 10), approximately a rear half of the second lens group moving frame 8 projects rearward from the ring portion 10b through the central aperture 10b-T in the optical axis direction, and a rear portion of each linear guide key 10c in the vicinity of the rear end thereof in the optical axis direction is engaged with a front portion of the associated guide groove 8a in the vicinity of the front end thereof in the optical axis direction. In addition, the front end of each linear guide key 10c projects forward from the associated guide groove 8a. Assuming that each linear guide key 10c is not positioned radially inside the ring portion 10b but projects forward directly from the front of the ring portion 10b unlike the present embodiment of the zoom lens, the second lens group moving frame 8 will not be capable of moving rearward beyond the

position thereof shown in Figures 84 and 85 since the second lens group moving frame 8 will be prevented from moving rearward upon contacting with the ring portion 10b.

Thereafter, if the zoom lens 71 changes its focal
5 length from the wide-angle extremity to the telephoto extremity, a rear portion of the second lens group moving frame 8 which is positioned behind the ring portion 10b in the optical axis direction when the zoom lens 71 is set at the wide-angle extremity has been moved forward
10 from the ring portion 10b through the central aperture 10b-T in the optical axis direction so that the entire part of the second lens group moving frame 8 is positioned in front of the ring portion 10b as shown in Figures 86 and 87. As a result, the rear end of each linear guide
15 key 10c projects rearward from the associated guide groove 8a so that only a front portion of each linear guide key 10c and a rear portion of the associated guide groove 8a are engaged with each other in the optical axis direction. During the movement of the second lens group moving frame
20 8 in the optical axis direction when the zoom lens 71 changes its focal length from the wide-angle extremity to the telephoto extremity, the set of three linear guide keys 10c remain engaged in the set of three guide grooves 8a so that the second lens group moving frame 8 is securely
25 guided linearly in the optical axis direction without

rotating about the lens barrel axis Z0.

In the case where only a linear guiding function between the second linear guide ring 10 and the second lens group moving frame 8 is considered, almost the entire portion of each linear guide key 10c in the optical axis direction and almost the entire portion of each guide groove 8a in the optical axis direction can be utilized theoretically as effective guide portions which can remain engaged with each other until just before being disengaged from each other. However, each of the respective effective guide portions is determined with a margin so as not to deteriorate the stability of engagement of the set of three linear guide keys 10c with the set of three guide grooves 8a. For instance, in the state shown in Figures 84 and 85 in which the zoom lens 71 is set at the wide-angle extremity, the relative position between the set of three linear guide keys 10c and the set of three guide grooves 8a shown in Figures 84 and 85 corresponds to the wide-angle extremity of the zoom lens 71 to ensure a sufficient amount of engagement between the set of three linear guide keys 10c and the set of three guide grooves 8a though each guide groove 8a still has room for the associated linear guide key 10c to further move rearward in the optical axis direction. Although the second lens group moving frame 8 is

positioned at the rear limit for the axial movement thereof with respect to the cam ring 11 when each front cam follower 8b-1 and each rear cam follower 8b-2 are positioned on the second inflection point VTm of the associated front inner cam groove 11a-1 and the second inflection point VTm of the associated rear inner cam groove 11a-2, respectively, namely, when each front cam follower 8b-1 and each rear cam follower 8b-2 are each positioned in close vicinity of its wide-angle position between this wide-angle position and its retracted position as described above, a sufficient amount of engagement of the set of three linear guide keys 10c with the set of three guide grooves 8a is secured even when the second lens group moving frame 8 is positioned at such a rear limit for the axial movement thereof with respect to the cam ring 11. In the state shown in Figures 86 and 87 in which the zoom lens 71 is set at the telephoto extremity, the second lens group moving frame 8 can further move forward to the second linear guide ring 10 when the zoom lens 71 is in the assembling/disassembling state, each linear guide key 10c remains engaged in the associated guide groove 8a in the assembling/disassembling state (see Figure 82).

As described above, to increase the maximum amount of movement of the second lens group moving frame 8

relative to the cam ring 11, the plurality of cam followers 8b of the second lens group moving frame 8 include the set of three front cam followers 8b-1, which are formed at different circumferential positions to be
5 respectively engaged in the set of three front inner cam grooves 11a-1, and a set of three rear cam followers 8b-2, which are formed at different circumferential positions behind the set of three front cam followers 8b-1 to be respectively engaged in the set of three rear inner cam
10 grooves 11a-2. The set of three rear cam followers 8b-2 move rearward from the ring portion 10b when the zoom lens 71 is driven from the retracted position to the wide-angle extremity, and move forward from the ring portion 10b when the zoom lens 71 is driven from the wide-angle
15 extremity to the telephoto extremity. The set of three rear cam followers 8b-2 are positioned behind the ring portion 10b when disengaged from the set of three rear inner cam grooves 11a-2 from the first rear end openings R3 or the second rear end openings R2, respectively. The
20 ring portion 10b is provided on an inner edge thereof at different circumferential positions with three radial recesses 10e through which the set of three rear cam followers 8b-2 can pass the ring portion 10b in the optical axis direction, respectively, (see Figures 88 and 89).

25 The three radial recesses 10e are formed on the ring

portion 10b to be aligned with the set of three rear cam followers 8b-2 in the optical axis direction when engaged therewith, respectively. Therefore, at the time when each rear cam follower 8b-2 reaches the first rear end opening R3 of the associated rear inner cam groove 11a-2 in the course of rearward movement of the rear cam follower 8b-2 with respect to the second linear guide ring 10 from the retracted position shown in Figure 79 toward a position shown in Figure 80 which corresponds to the wide-angle extremity of the zoom lens 71, the three radial recesses 10e are also aligned with the three first rear end openings R3 in the optical axis direction to allow the set of three rear cam followers 8b-2 to move rearward beyond the ring portion 10b through the three radial recesses 10e and the three first rear end openings R3, respectively. Thereafter, each rear cam follower 8b-2 changes the direction of movement thereof at the second inflection point VTm of the associated reference cam diagram VT to then move forward in the optical axis direction, and remains positioned behind the ring portion 10b until reaching the second rear end opening R2 of the associated rear inner cam groove 11a-2 as shown in Figures 80 and 85. Upon each rear cam follower 8b-2 reaching the second rear end opening R2 of the associated rear inner cam groove 11a-2 when moving forward further from the

position shown in Figure 80 which corresponds to the wide-angle extremity of the zoom lens 71, the three radial recesses 10e are aligned with the three second rear end openings R2 in the optical axis direction this time to
5 allow the set of three rear cam followers 8b-2 to enter the set of three rear inner cam grooves 11a-2 through the three radial recesses 10e and the three second rear end openings R2, respectively. Accordingly, the ring portion 10b of the second linear guide ring 10 does not
10 interfere with movement of the set of three rear cam followers 8b-2 because the ring portion 10b is provided with the three radial recesses 10e, through which the set of three rear cam followers 8b-2 can pass the ring portion 10b in the optical axis direction, respectively.

15 As can be understood from the above descriptions, according to the above described linear guide structure, the second lens group moving frame 8, the moving range of which in the optical axis direction is comparatively great, can be securely guided linearly without rotating
20 about the lens barrel axis Z0 by the second linear guide ring 10 without the ring portion 10b interfering with the second lens group moving frame 8. As can be seen from Figures 79 through 82, the present embodiment of the linear guide structure cannot be greater than a
25 conventional linear guide structure because the length

of each linear guide key 10c is smaller than the length of the cam ring 11 in the optical axis direction.

The support structure between the second linear guide ring 10 and the second lens group moving frame 8 that are positioned inside the cam ring 11 has been discussed above. The support structure between the first external barrel 12 and the second external barrel 13 that are positioned outside the cam ring 11 will be discussed hereinafter.

The cam ring 11 and the first external barrel 12 are arranged concentrically about the lens barrel axis Z0. The first external barrel 12 moves in the optical axis direction in a predetermined moving manner by engagement of the set of three cam followers 31, which project radially inwards from the first external barrel 12, with the set of three outer cam grooves 11b, which are formed on an outer peripheral surface of the cam ring 11. Figures 90 through 100 show positional relationships between the set of three cam followers 31 and the set of three outer cam grooves 11b. In Figures 90 through 100, the first external barrel 12 is shown by one-dot chain lines while the second external barrel 13 is shown by two-dot chain lines.

As shown in Figure 16, each outer cam groove 11b, which is formed on an outer peripheral surface of the cam

ring 11, is provided at one end (front end) thereof with
a front end opening section 11b-X which is open on a front
end surface of the cam ring 11, and is provided at the
other end (rear end) thereof with a rear end opening
5 section 11b-Y which is open on a rear end surface of the
cam ring 11. Accordingly, the opposite ends of each outer
cam groove 11b are respectively formed as open ends. Each
outer cam groove 11b is provided between the front end
opening section 11b-X and the rear end opening section
10 11b-Y with an inclined lead section 11b-L which extends
linearly obliquely from the rear end opening section 11b-Y
toward the front of the optical axis direction, and a
curved section 11b-Z which is positioned between the
inclined lead section 11b-L and the front end opening
15 section 11b-X to be curved rearward (downward as viewed
in Figure 16) in the optical axis direction. A zooming
section for changing the focal length of the zoom lens
71 before picture taking is included in the curved section
11b-Z of each outer cam groove 11b. As shown in Figures
20 94 through 100, the set of three cam followers 31 can be
inserted into and removed from the set of three outer cam
grooves 11b through the front end opening sections 11b-X
thereof, respectively. When the zoom lens 71 is set at
the telephoto extremity, each cam follower 31 is
25 positioned in the associated curved section 11b-Z in the

vicinity of the front end opening section 11b-X as shown
in Figures 93 and 99. When the zoom lens 71 is set at
the wide-angle extremity, each cam follower 31 is
positioned in the associated curved section 11b-Z in the
5 vicinity of inclined lead section 11b-L as shown in
Figures 92 and 98.

In the state shown in Figures 90 and 95 in which the
zoom lens 71 is in the retracted state, each cam follower
31 is in the associated rear end opening section 11b-
10 Y. The width of the rear end opening section 11b-Y of
each outer cam groove 11b is greater than the width of
the inclined lead section 11b-L and the width of the curved
section 11b-Z in a circumferential direction of the cam
ring 11 so that each cam follower 31 is allowed to move
15 in a circumferential direction of the cam ring 11 to some
extent in the associated rear end opening section 11b-Y.
Although the rear end opening section 11b-Y of each outer
cam groove 11b is open at the rear of the cam ring 11,
the set of three cam followers 31 do not come off the set
20 of three outer cam grooves 11b through the three rear end
opening sections 11b-Y, respectively, because the cam
ring 11 is provided with at least one stop portion which
determines a rear limit for the axial movement of the first
external barrel 12 with respect to the cam ring 11.

25 More specifically, the cam ring 11 is provided, at

the front end thereof at different circumferential positions, with a set of three front projecting portions 11f which project forward in the optical axis direction as shown in Figure 16. The aforementioned set of three
5 external protuberances 11g, which are formed on the cam ring 11 to project radially outwards, are formed behind the set of three front projecting portions 11f in the optical axis direction, respectively. Each external protuberance 11g is provided with a corresponding section
10 of the discontinuous circumferential groove 11c. The set of three roller followers 32 are fixed onto the set of three external protuberances 11g by the three set screws 32a, respectively. The set of three front projecting portions 11f are provided at the front ends thereof with
15 a set of three front stop surfaces 11s-1, respectively, which lie in a plane orthogonal to the photographing optical axis Z1. The set of three external protuberances 11g are provided at the front ends thereof with a set of three rear stop surfaces 11s-2 which lie in a plane
20 orthogonal to the photographing optical axis Z1. On the other hand, as shown in Figure 21, the first external barrel 12 is provided on an inner peripheral surface thereof with a set of three protuberances, and a set of three front stop surfaces 12s-1 are provided at the rear
25 end surface of the protuberances to correspond (oppose)

to the set of three front stop surfaces 11s-1 so that the set of three front stop surfaces 12s-1 can come into contact with the set of three front stop surfaces 11s-1, respectively. The first external barrel 12 is provided
5 at the rear end thereof with a set of three rear stop surfaces 12s-2 to correspond to the set of three rear stop surfaces 11s-2 so that the set of three rear stop surfaces 12s-2 can come into contact with the set of three rear stop surfaces 11s-2, respectively. Each front stop
10 surface 12s-1 and each rear stop surface 12s-2 are parallel to each front stop surface 11s-1 and each rear stop surface 11s-2, respectively. The space between the set of three front stop surfaces 11s-1 and the set of three rear stop surfaces 11s-2 is the same as the space between
15 the set of three front stop surfaces 12s-1 and the set of three rear stop surfaces 12s-2.

When the zoom lens 71 is in the retracted state, each front stop surface 12s-1 comes very close to the associated front stop surface 11s-1 while each rear stop
20 surface 12s-2 comes very close to the associated rear stop surface 11s-2 so that the first external barrel 12 does not further move rearward beyond the position thereof shown in Figures 90 and 95. In the lens barrel retracting operation of the zoom lens 71, the first external barrel
25 12 stops moving rearward immediately before each front

stop surface 12s-1 and each rear stop surface 12s-2 comes into contact with the associated front stop surface 11s-1 and the associated rear stop surface 11s-2, respectively, because the first external barrel 12 stops being driven in the optical axis direction by the cam ring 11 via the set of three cam followers 31 at the time when the set of three cam followers 31 respectively enter the rear end opening sections 11b-Y of the set of three outer cam grooves 11b due to a wide circumferential width of each rear end opening section 11b-Y. The space between the set of three front stop surfaces 11s-1 and the set of three front stop surfaces 12s-1 in the retracted state of the zoom lens 71 is predetermined at approximately 0.1 mm. Likewise, the space between the set of three rear stop surfaces 11s-2 and the set of three rear stop surfaces 12s-2 in the retracted state of the zoom lens 71 is also predetermined at approximately 0.1 mm. However, in an alternative embodiment, the first external barrel 12 can be allowed to retract by inertia so that the front stop surfaces 11s-1 and 12s-1 and the rear stop surfaces 11s-2 and 12s-2 contact each other, respectively.

The first external barrel 12 is provided on an inner peripheral surface thereof with an inner flange 12c which projects radially inwards. The set of three front stop surfaces 12s-1 are positioned in front of the inner flange

12c in the optical axis direction. The inner flange 12c of the first external barrel 12 is provided with a set of three radial recesses 12d through which the set of three front projecting portions 11f can pass the inner flange 12c in the optical axis direction, respectively. When the set of three front stop surfaces 11s-1 approach the set of three front stop surfaces 12s-1, the set of three front projecting portions 11f passes the inner flange 12c through the set of three radial recesses 12d.

Although each of the cam ring 11 and the first external barrel 12 is provided, at front and rear portions thereof in the optical axis direction, with a set of front stop surfaces (11s-1 or 12s-1) and a set of rear stop surfaces (11s-2 or 12s-2) in the present embodiment of the zoom lens, each of the cam ring 11 and the first external barrel 12 can be provided with only one of the set of front stop surfaces or the set of rear stop surfaces to determine the rear limit for the axial movement of the first external barrel 12 with respect to the cam ring 11. Conversely, each of the cam ring 11 and the first external barrel 12 can be provided with one or more additional sets of stop surfaces. For instance, in addition to the front stop surfaces 11s-1 and 12s-1 and the rear stop surfaces 11s-2 and 12s-2, three front end surfaces 11h each of which are formed between two adjacent front projecting portions

11f can be made to be capable of coming into contact with a rear surface 12h of the inner flange 12c to determine the rear limit for the axial movement of the first external barrel 12 with respect to the cam ring 11. Note that the front projecting portions 11f do not contact with the rear surface 12h, in the illustrated embodiment.

In each of the three outer cam grooves 11b, the entire section thereof except for the front end opening section 11b-X serving as a lens-barrel assembling/disassembling section serves as a lens-barrel operating section consisting of a zooming section and a lens-barrel retracting section. Namely, a specific section of each of the three outer cam grooves 11b which extends from the position of the associated cam follower 31 in the outer cam groove 11b shown in Figures 90 and 95 (i.e., the rear end opening section 11b-Y), where the zoom lens 71 is in the retracted state, to that shown in Figures 93 and 99, where the zoom lens 71 is set at the telephoto extremity serves as a lens-barrel operating section consisting of a zooming section and a lens-barrel retracting section. In the present embodiment of the zoom lens, the rear end opening section 11b-Y of each outer cam groove 11b is formed as an opening which is open at the rear of the cam ring 11. This structure makes it unnecessary to form any rear end wall having a certain

thickness on a portion of the cam ring 11 behind each rear
end opening section 11b-Y, thus reducing the length of
the cam ring 11 in the optical axis direction. In a
conventional cam ring having cam grooves thereon, at least
5 the terminal end of an operating section of each cam groove
(one end of each cam groove if the other end is an open
end for the insertion of the associated cam groove in the
cam groove) has to be formed as a closed end which requires
the cam ring to have a end wall having a certain thickness
10 to close the terminal end of the operating section of each
cam groove. This kind of end wall does not have to be
formed on the cam ring 11 of the present embodiment of
the zoom lens, which is advantageous to downsize the cam
ring 11.

15 The reason why the rear end of each outer cam groove
11b is successfully formed as an open end such as the rear
end opening section 11b-Y is that the rear limit for the
axial movement of the first external barrel 12 with
respect to the cam ring 11 is determined by the front stop
20 surfaces (11s-1 and 12s-1) and the rear stop surfaces
(11s-2 and 12s-2) which are provided independent of the
set of three outer cam grooves 11b and the set of three
cam followers 31. Providing the cam ring 11 and the first
external barrel 12 with such stop surfaces as the front
25 and rear stop surfaces (11s-1, 12s-1, 11s-2 and 12s-2)

that operate independently of the set of three outer cam grooves 11b and the set of three cam followers 31, eliminates a possibility of each cam follower 31 becoming incapable of being re-engaged in the associated outer cam groove 11b through the rear end opening section 11b-Y thereof if each cam follower 31 should be disengaged therefrom.

When the set of three cam followers 31 are respectively positioned in the rear end opening sections 11b-Y of the set of three outer cam grooves 11b, the optical elements of the zoom lens 71 are not required to have a high degree of positioning accuracy because the zoom lens 71 is in the retracted state as shown in Figure 10. Due to this reason, there is no substantial problem even if each rear end opening section 11b-Y has a wide circumferential width so that each cam follower 31 is loosely engaged in the associated rear end opening section 11b-Y. Conversely, the lens-barrel retracting section of the lens-barrel operating section of each outer cam groove 11b is successfully formed as an open end such as the rear end opening section 11b-Y because the lens-barrel retracting section of the lens-barrel operating section of each outer cam groove 11b, in which the associated cam follower 31 is allowed to be loosely engaged, is formed at the terminal end of the outer cam groove 11b and further

because the entire cam contour of each outer cam groove 11b is determined so that the terminal end thereof is positioned at the rearmost position of the outer cam groove 11b in the optical axis direction.

5 To make each cam follower 31 move from the rear end opening section 11b-Y, in which the cam follower 31 is loosely engaged, to the inclined lead section 11b-L of the associated outer cam groove 11b with reliability, the cam ring 11 is provided at different circumferential
10 positions with a set of three beveled lead surfaces 11t while the first external barrel 12 is provided at different circumferential positions with a set of three beveled lead surfaces 12t. The set of three beveled lead surfaces 11t are formed to adjoin the set of three front
15 stop surfaces 11s-1 on the set of three front projecting portions 11f so that the set of three beveled lead surfaces 11t and the set of three front stop surfaces 11s-1 become a set of three continuous surfaces, respectively. The first external barrel 12 is provided at different
20 circumferential positions with a set of three rear end protrusions 12f each having a substantially isosceles triangle shape. The set of three engaging protrusions 12a are formed on the set of three rear end protrusions 12f, respectively. One of the two equal sides of each
25 rear end protrusion 12f is formed as one of the three

beveled lead surfaces 12t. As shown in Figures 95 through 100, each beveled lead surface 11t and each beveled lead surface 12t extend parallel to the inclined lead section 11b-L.

5 In the state shown in Figures 90 and 95 in which the zoom lens 71 is in the retracted state, an edge ED1 of each of the three inner flanges 12c is positioned to be opposed to the adjacent beveled lead surface 11t in a circumferential direction, and also an edge ED2 of each
10 of the three external protuberances 11g is positioned to be opposed to the adjacent beveled lead surface 12t in a circumferential direction. In addition, in the same state shown in Figures 90 and 95, the edge ED1 of each inner flange 12c is slightly apart from the adjacent
15 beveled lead surface 11t while the edge ED2 of each external protuberance 11g is slightly apart from the adjacent beveled lead surface 12t. In this state shown in Figures 90 and 95, a rotation of the cam ring 11 in the lens barrel advancing direction (upwards as viewed
20 in Figures 91 and 96) causes each beveled lead surface 11t to come into contact with the edge ED1 of the adjacent inner flange 12c, and at the same time causes each beveled lead surface 12t to come into contact with the edge ED2 of the associated external protuberance 11g as shown in
25 Figures 91 and 96. Accordingly, at an initial stage of

rotation of the cam ring 11 from the state shown in Figure 95, in which the three edges ED1 and the three edges ED2 are respectively apart from the three beveled lead surfaces 11t and the three beveled lead surfaces 12t, to the state shown in Figure 96, in which the three edges ED1 and the three edges ED2 are respectively in contact with the three beveled lead surfaces 11t and the three beveled lead surfaces 12t, each cam follower 31 moves solely within the associated rear end opening section 11b-Y in a circumferential direction of the cam ring 11, so that the first external barrel 12 is not moved in the optical axis direction with respect to the cam ring 11 by rotation of the cam ring 11.

In the state shown in Figures 91 and 96, in which the three edges ED1 and the three edges ED2 are respectively in contact with the three beveled lead surfaces 11t and the three beveled lead surfaces 12t, each cam follower 31 is positioned at the insertion end of the inclined lead section 11b-L of the associated outer cam groove 11b. A further rotation of the cam ring 11 causes each edge ED1 to slide on the associated beveled lead surface 11t and at the same time causes each edge ED2 to slide on the associated beveled lead surface 12t so that the first external barrel 12 is pushed forward with respect to the cam ring 11 by the three beveled lead

surfaces 11t in accordance with the sliding movements of the three edges ED1 and the three edges ED2 on the three beveled lead surfaces 11t and the three beveled lead surfaces 12t, respectively. Since each beveled lead surface 11t and each beveled lead surface 12t extend parallel to the inclined lead section 11b-L, the force acting on the first external barrel 12 by the rotation of the cam ring 11 via the three beveled lead surfaces 11t causes each cam follower 31 to move into the inclined lead section 11b-L of the associated outer cam groove 11b from the rear end opening section 11b-Y thereof. After each cam follower 31 completely enters the inclined lead section 11b-L of the associated outer cam groove 11b as shown in Figure 97, each beveled lead surface 11t and each beveled lead surface 12t are disengaged from the associated edge ED1 and the associated edge ED2, respectively, and accordingly, the first external barrel 12 is guided linearly in the optical axis direction due only to the engagement of the set of three cam followers 31 with the set of three outer cam grooves 11b, respectively.

Accordingly, in the lens barrel advancing operation of the zoom lens 71 which commences from the retracted state shown in Figure 10, providing the cam ring 11 and the first external barrel 12 with the three beveled lead

surfaces 11t and the three beveled lead surfaces 12t,
whose functions are similar to those of the three inclined
lead section 11b-L, and further providing the first
external barrel 12 with the three edge ED2 and the three
5 ED1, whose functions are similar to those of the three
cam followers 31, respectively, make it possible to have
each cam follower 31 enter the inclined lead section 11b-L
of the associated outer cam groove 11b properly to move
therein toward the associated curved section 11b-Z even
10 from a state as shown in Figure 95 where each cam follower
31 is loosely engaged in the associated rear end opening
section 11b-Y. This prevents the zoom lens 71 from
malfunctioning.

Although each of the cam ring 11 and the first
15 external barrel 12 is provided with a set of three beveled
lead surfaces (11t or 12t) in the present embodiment of
the zoom lens, only one of the cam ring 11 and the first
external barrel 12 can be provided with a set of three
beveled lead surfaces (11t or 12t), or each of the cam
20 ring 11 and the first external barrel 12 can be provided
with more than one set of three beveled lead surfaces.

Figure 101 shows another embodiment of the structure
shown in Figure 95, in which the zoom lens 71 is in the
retracted state. Elements shown in Figure 101 which are
25 similar to those shown in Figure 95 are designated by the

same reference numerals each of which the mark (') is appended to.

Each outer cam groove 11b' is provided at the rear end of each inclined lead section 11b-L' with a rear end opening 11b-K instead of the rear end opening section 11b-Y of the cam ring 11 shown in Figure 95. Unlike each rear end opening section 11b-Y, each rear end opening 11b-K is formed as a simple end opening of the associated outer cam groove 11b. Performing the lens barrel retracting operation in a state where the zoom lens is set at the wide-angle extremity causes each cam follower 31' to move rearward (rightward as viewed in Figure 101) in the associated inclined lead section 11b-L', and subsequently causes each cam follower 31' to come out of the associated outer cam groove 11b' through the rear end opening 11b-K thereof upon the zoom lens reaching the retracted position thereof. If each cam follower 31' comes out of the associated outer cam groove 11b' through the rear end opening 11b-K thereof, the first external barrel 12' stops being driven by the cam ring 11' via the set of three cam followers 31' and therefore stops moving rearward. At this time, the first external barrel 12' is prevented from further moving rearward because each front stop surface 12s-1' and each rear stop surface 12s-2' are positioned very close to the associated front

stop surface 11s-1' and the associated rear stop surface 11s-2', respectively. Therefore, the first external barrel 12' is prevented from moving rearward overly even if each cam follower 31' comes out of the associated outer cam groove 11b' through the rear end opening 11b-K thereof. In this embodiment shown in Figure 101, similar to the embodiment shown in Figure 95, the space between the set of three front stop surfaces 11s-1' and the set of three front stop surfaces 12s-1' in the retracted state of the zoom lens is desirably at approximately 0.1 mm. Likewise, the space between the set of three rear stop surfaces 11s-2' and the set of three rear stop surfaces 12s-2' in the retracted state of the zoom lens is desirably at approximately 0.1 mm. However, in an alternative embodiment, the first external barrel 12' can be allowed to retract by inertia so that the front stop surfaces 11s-1' and 12s-1' and the rear stop surfaces 11s-2' and 12s-2' contact each other, respectively.

According to the structure shown in Figure 101 in which each cam follower 31' comes out of the associated outer cam groove 11b' in the retracted state of the zoom lens 71, it is possible to further downsize the cam ring 11' because each outer cam groove 11b' does not have to be provided with any accommodation section, which corresponds to each rear end opening section 11b-Y of the

cam ring 11, for accommodating the associated cam follower therein when the zoom lens is in the retracted position.

In the retracted state shown in Figure 101, the edge ED1' of each of the three inner flanges 12c' is in contact with the beveled lead surface 11t' of the associated front projecting portions 11f' while the edge ED2' of each of the three external protuberances 11g' is in contact with the beveled lead surface 12t' of the associated rear projecting portions 12f'. Each beveled lead surface 11t' and each beveled lead surface 12t' extend parallel to the inclined lead section 11b-L'. Due to this structure, rotating the cam ring 11' in the retracted state shown in Figure 101 causes the first external barrel 12' to be pushed forward with respect to the cam ring 11', and subsequently causes each cam follower 31' which is currently positioned outside the associated outer cam groove 11b' to move into the inclined lead section 11b-L' of the associated outer cam groove 11b' from the rear end opening 11b-K thereof. Thereafter, a further rotation of the cam ring 11' in the lens barrel advancing direction causes each cam follower 31' to move into the associated curved section 11b-Z' in the associated outer cam groove 11b'. Thereafter, each cam follower 31' moves in the associated outer cam groove 11b' to perform a zooming operation in accordance with rotation of the cam ring 11'.

Moving each cam follower 31' to the front end opening sections 11b-X of the associated outer cam groove 11b makes it possible to remove the first external barrel 12' from the cam ring 11'.

5 As can be understood from the foregoing, also in the embodiment shown in Figure 101, the rear limit for the axial movement of the first external barrel 12' with respect to the cam ring 11' can be surely determined, while each cam follower 31' can properly enter the inclined lead
10 section 11b-L' of the associated outer cam groove 11b' even though each cam follower 31' comes out of the associated outer cam groove 11b' through the rear end opening 11b-K thereof when the zoom lens is retracted into the camera body.

15 The structure of the zoom lens 71 which accommodates the zoom lens 71 in the camera body 72 as shown in Figure 9 upon a main switch (not shown) of the digital camera 70 being turned OFF, which incorporates the structure retracting the second lens frame 6 (the second lens group
20 LG2) to the radially retracted position, will be hereinafter discussed in detail. In the following descriptions the terms "vertical direction" and "horizontal direction" mean the vertical direction and the horizontal direction as viewed from front or rear of
25 the digital camera 70 such as the vertical direction of

Figure 110 and the horizontal direction of Figure 111,
respectively. In addition, the term "forward/backward
direction" corresponds to the optical axis direction
(i.e., a direction parallel to the photographing optical
5 axis Z1).

The second lens group LG2 is supported by the second
lens group moving frame 8 via peripheral elements shown
in Figures 102. The second lens frame 6 is provided with
a cylindrical lens holder portion 6a, a pivoted
10 cylindrical portion 6b, a swing arm portion 6c and an
engaging protrusion 6e. The cylindrical lens holder
portion 6a directly holds and supports the second lens
group L2. The swing arm portion 6c extends in a radial
direction of the cylindrical lens holder portion 6a to
15 connect the cylindrical lens holder portion 6a to the
pivoted cylindrical portion 6b. The engaging protrusion
6e is formed on the cylindrical lens holder portion 6a
to extend in a direction away from the swing arm portion
6c. The pivoted cylindrical portion 6b is provided with
20 a through hole 6d extending in a direction parallel to
the optical axis of the second lens group LG2. The
pivoted cylindrical portion 6b is provided at front and
rear ends thereof, on front and rear sides of a portion
of the pivoted cylindrical portion 6b which is connected
25 to the swing arm portion 6c, with a front spring support

portion 6f and a rear spring support portion 6g, respectively. The front spring support portion 6f is provided, on an outer peripheral surface thereof in the vicinity of the front end of the front spring support
5 portion 6f, with a front spring hold projection 6h. The rear spring support portion 6g is provided, on an outer peripheral surface thereof in the vicinity of the rear end of the rear spring support portion 6g, with a rear spring hold projection 6i. The pivoted cylindrical
10 portion 6b is provided on an outer peripheral surface thereof with a position control arm 6j extending in a direction away from the swing arm portion 6c. The position control arm 6j is provided with a first spring engaging hole 6k, and the swing arm portion 6c is provided
15 with a second spring engaging hole 6p (see Figures 118 through 120).

The second lens frame 6 is provided with a rear projecting portion 6m which projects rearward in the optical axis direction from the swing arm portion 6c. The
20 rear projecting portion 6m is provided at the rear end thereof with a contacting surface 6n which lies in a plane orthogonal to the optical axis of the second lens group LG2, i.e., to the photographing optical axis Z1. Although a light shield ring 9 is fixed as shown in Figures
25 104, 105, 128 and 129, the contacting surface 6n is

positioned behind the second lens group light shield ring in the optical axis direction. Namely, the contacting surface 6n is positioned behind the rearmost position of the second lens group LG2 in the optical axis direction.

5 The front second lens frame support plate 36 is a vertically-elongated narrow plate having a narrow width in horizontal direction. The front second lens frame support plate 36 is provided with a first vertically-elongated hole 36a, a pivot hole 36b, a cam-bar insertable
10 hole 36c, a screw insertion hole 36d, a horizontally-elongated hole 36e and a second vertically-elongated hole 36f, in this order from top to bottom of the front second lens frame support plate 36. All of these holes 36a through 36f are through holes which penetrate the front
15 second lens frame support plate 36 in the optical axis direction. The front second lens frame support plate 36 is provided on an outer edge thereof in the vicinity of the first vertically-elongated hole 36a with a spring engaging recess 36g.

20 Similar to the front second lens frame support plate 36, the rear second lens frame support plate 37 is also a vertically-elongated narrow plate having a narrow width in horizontal direction. The rear second lens frame support plate 37 is provided with a first vertically-
25 elongated hole 37a, a pivot hole 37b, a cam-bar insertable

hole 37c, a screw hole 37d, a horizontally-elongated hole 37e and a second vertically-elongated hole 37f, in this order from top to bottom of the rear second lens frame support plate 37. All of these holes 37a through 37f are
5 through holes which penetrate through the rear second lens frame support plate 37 in the optical axis direction. The rear second lens frame support plate 37 is provided on an inner edge of the cam-bar insertable hole 37c with a guide key insertable recess 37g. The through holes 36a
10 through 36f of the front second lens frame support plate 36 and the through holes 37a through 37f of the rear second lens frame support plate 37 are aligned in the optical axis direction, respectively.

The set screw 66 is provided with a threaded shaft
15 portion 66a and a head portion fixed to an end of the threaded shaft portion 66. The head portion is provided with a cross-slot 66b into which the tip of a Phillips screwdriver (not shown) serving as an adjusting tool can be inserted. The screw insertion hole 36d of the front
20 second lens frame support plate 36 has a diameter by which the threaded shaft portion 66a of the set screw 66 is insertable. The threaded shaft portion 66a of the set screw 66 can be screwed through the screw hole 37d of the rear second lens frame support plate 37 to fix the front
25 second lens frame support plate 36 and the rear second

lens frame support plate 37 to the second lens group moving frame 8.

The zoom lens 71 is provided between the front second lens frame support plate 36 and the rear second lens frame support plate 37 with a first eccentric shaft 34X which extends in the optical axis direction. The first eccentric shaft 34X is provided with a large diameter portion 34X-a, and is provided at front and rear ends of the large diameter portion 34X-a with a front eccentric pin 34X-b and a rear eccentric pin 34X-c, which project forward and rearward in the optical axis direction, respectively. The front eccentric pin 34X-b and the rear eccentric pin 34X-c have the common axis eccentric to the axis of the large diameter portion 34X-a. The front eccentric pin 34X-b is provided at the front end thereof with a recess 34X-d into which the tip of a flatblade screwdriver (not shown) serving as an adjusting tool can be inserted.

The zoom lens 71 is provided between the front second lens frame support plate 36 and the rear second lens frame support plate 37 with a second eccentric shaft 34Y which extends in the optical axis direction. The structure of the second eccentric shaft 34Y is the same as the structure of the first eccentric shaft 34X. Namely, the second eccentric shaft 34Y is provided with a large diameter

portion 34Y-a, and is provided at front and rear ends of the large diameter portion 34Y-a with a front eccentric pin 34Y-b and a rear eccentric pin 34Y-c which projects forward and rearward in the optical axis direction, respectively. The front eccentric pin 34Y-b and the rear eccentric pin 34Y-c have the common axis eccentric to the axis of the large diameter portion 34Y-a. The front eccentric pin 34Y-b is provided at the front end thereof with a recess 34Y-d into which the tip of a flatblade screwdriver (not shown) serving as an adjusting tool can be inserted.

The bore diameter of a rear end portion of the through hole 6d that penetrates the second lens frame 6 is increased to form a spring-accommodation large diameter hole 6Z (see Figure 126) so that the compression coil spring 38 is accommodated in the spring-accommodation large diameter hole 6Z. The front torsion coil spring 39 and a rear torsion coil spring 40 are fitted on the front spring support portion 6f and the rear spring support portion 6g, respectively. The front torsion coil spring 39 is provided with a front spring end 39a and a rear spring end 39b, and the rear torsion coil spring 40 is provided with a front stationary spring end 40a and a rear movable spring end 40b.

The pivot shaft 33 is fitted in the through hole 6d

from the rear end thereof so that the pivoted cylindrical portion 6b of the second lens frame 6 can freely rotate on the pivot shaft 33 with no play in radial directions. The diameters of front and rear ends of the pivot shaft 33 correspond to the pivot hole 36b of the front second lens frame support plate 36 and the pivot hole 37b of the rear second lens frame support plate 37 so that the front and rear ends of the pivot shaft 33 are fitted in the pivot hole 36b and the pivot hole 37b to be supported by the front second lens frame support plate 36 and the rear second lens frame support plate 37, respectively. In a state where the pivot shaft 33 is fitted in the through hole 6d, the axis of the pivot shaft 33 extends parallel to the optical axis of the second lens group LG2. As shown in Figure 113, the pivot shaft 33 is provided in the vicinity of the rear end thereof with a flange 33a which is inserted in the spring-accommodation large diameter hole 6Z to contact with the rear end of the compression coil spring 38 that is accommodated in the spring-accommodation large diameter hole 6Z.

As clearly shown in Figures 106 and 107, the second lens group moving frame 8 is an annular member having a through internal space 8n which penetrates the second lens group moving frame 8 in the optical axis direction. The second lens group moving frame 8 is provided, on an inner

peripheral surface thereof at a substantially center thereof in the optical axis direction, with a central inner flange 8s. The inner edge of the central inner flange 8s forms a vertically-elongated opening 8t in which
5 the second lens frame 6 is swingable. The shutter unit 76 is fixed to a front surface of the central inner flange 8s. The second lens group moving frame 8 is provided on an inner peripheral surface thereof behind the central inner flange 8s in the optical axis direction with a first
10 radial recess 8q (see Figures 111 and 112) which is recessed radially outwards (upwards as viewed in Figure 111) to correspond to the shape of an outer peripheral surface of the cylindrical lens holder portion 6a of the second lens frame 6 so that the cylindrical lens holder
15 portion 6a can partly enter the radial recess 8q. The second lens group moving frame 8 is further provided on an inner peripheral surface thereof behind the central inner flange 8s with a second radial recess 8r (see Figures 111 and 112) which is recessed radially outwards to
20 correspond to the shape of an outer edge of the engaging protrusion 6e of the second lens frame 6 so that the engaging protrusion 6e can partly enter the second radial recess 8r.

As shown in Figures 106 and 107, the second lens
25 group moving frame 8 is provided on a front end surface

thereof (specifically, a right portion of the front end surface of the second lens group moving frame 8, on the right hand side of the vertically-elongated opening 8t, as viewed from front of the second lens group moving frame 8) with a vertically-elongated front fixing surface 8c to which the front second lens frame support plate 36 is fixed. The front fixing surface 8c is hatched in Figures 106 and 107 for the purpose of illustration. The front fixing surface 8c does not overlap the vertically-elongated opening 8t in the optical axis direction, and lies in a plane orthogonal to the lens barrel axis Z0 (the photographing optical axis Z1, the optical axis of the second lens group LG2). The front fixing surface 8c is positioned in front of the shutter unit 76 in the optical axis direction. The front fixing surface 8c is formed to be exposed to the front of the second lens group moving frame 8. The second lens group moving frame 8 is provided at the front end thereof with a set of three extensions 8d extending forward in the optical axis direction. The set of three extensions 8d are formed as extensions of the second lens group moving frame 8 which extend forward from the front end of the second lens group moving frame 8. The set of three front cam followers 8b-1 are formed on outer peripheral surfaces of the set of three extensions 8d, respectively. The second lens group

moving frame 8 is provided on a rear end surface thereof
(specifically, a left portion of the rear end surface of
the second lens group moving frame 8, on the left hand
side of the vertically-elongated opening 8t, as viewed
5 from rear of the second lens group moving frame 8) with
a vertically-elongated rear fixing surface 8e to which
the rear second lens frame support plate 37 is fixed. The
rear fixing surface 8e is positioned on the opposite side
of the central inner flange 8s from the front fixing
10 surface 8c in the optical axis direction to be parallel
to the front fixing surface 8c. The rear fixing surface
8e is formed as a part of the rear end surface of the second
lens group moving frame 8; namely, the rear fixing surface
8e is flush with the rear end surface of the second lens
15 group moving frame 8.

The second lens group moving frame 8 is provided with
a first eccentric shaft support hole 8f, a pivoted
cylindrical portion receiving hole 8g, a screw insertion
hole 8h and a second eccentric shaft support hole 8i, in
20 this order from top to bottom of the second lens group
moving frame 8. All of these holes 8f, 8g, 8h and 8i are
through holes which penetrate the second lens group moving
frame 8 in the optical axis direction between the front
fixing surface 8c and the rear fixing surface 8e. The
25 through holes 8f, 8h and 8i of the second lens group moving

frame 8 are aligned with the through holes 36a, 36d and 36e of the front second lens frame support plate 36, respectively, and also aligned with the through holes 37a, 37d and 37e of the rear second lens frame support plate 37 in the optical axis direction, respectively. The second lens group moving frame 8 is provided on an inner peripheral surface thereon in the pivoted cylindrical portion receiving hole 8g with a key way 8p extending in the optical axis direction. The key way 8p penetrates the second lens group moving frame 8 in the optical axis direction between the front fixing surface 8c and the rear fixing surface 8e. The diameter of the first eccentric shaft support hole 8f is determined so that the large diameter portion 34X-a is rotatably fitted in the first eccentric shaft support hole 8f, and the diameter of the second eccentric shaft support hole 8i is determined so that the large diameter portion 34Y-a is rotatably fitted in the second eccentric shaft support hole 8i (see Figure 113). On the other hand, the diameter of the screw insertion hole 8h is determined so that the threaded shaft portion 66a is inserted in the screw insertion hole 8h with a substantial gap between the threaded shaft portion 66a and an inner peripheral surface of the screw insertion hole 8h (see Figure 113). The second lens group moving frame 8 is provided on the front fixing surface 8c and

the rear fixing surface 8e with a front boss 8j and a rear boss 8k which project forward and rearward in the optical axis direction, respectively. The front boss 8j and the rear boss 8k have a common axis extending in the optical axis direction. The second lens group moving frame 8 is provided below the vertically-elongated opening 8t with a through hole 8m which penetrates through the central inner flange 8s in the optical axis direction so that the rotation limit shaft 35 can be inserted into the vertically-elongated opening 8t.

The rotation limit shaft 35 is provided with a large diameter portion 35a, and is provided at a rear end thereof with an eccentric pin 35b which projects rearward in the optical axis direction. The axis of the eccentric pin 35b is eccentric to the axis of the large diameter portion 35. The rotation limit shaft 35 is provided at a front end thereof with a recess 35c into which the tip of a flatblade screwdriver (not shown) serving as an adjusting tool can be inserted.

Figures 108 through 112 show a state where the above described assemble parts shown in Figures 102 through 107 are put together, viewed from different angles. A manner of putting the assembled parts together will be discussed hereinafter.

First, the front torsion coil spring 39 and the rear

torsion coil spring 40 are fixed to the second lens frame 6. At this time, a coil portion of the front torsion coil spring 39 is fitted on the front spring support portion 6f of the pivoted cylindrical portion 6b with the rear spring end 39b being engaged with a portion of the second lens frame 6 between the pivoted cylindrical portion 6b and the swing arm portion 6c (see Figure 104). The front spring end 39a of the front torsion coil spring 39 is not engaged with any part of the second lens frame 6. A coil portion of the rear torsion coil spring 40 is fitted on the rear spring support portion 6g of the pivoted cylindrical portion 6b with the front stationary spring end 40a and the rear movable spring end 40b being inserted into the second spring engaging hole 6p of the swing arm portion 6c and the first spring engaging hole 6k of the position control arm 6j, respectively. The front stationary spring end 40a is fixed to the second spring engaging hole 6p while the rear movable spring end 40b is allowed to move in the first spring engaging hole 6k in a range "NR1" shown in Figure 120. In a free state, the rear torsion coil spring 40 is supported by the second lens frame 6 thereon with the front stationary spring end 40a and the rear movable spring end 40b being slightly pressed to move in opposite directions approaching each other so that the rear movable spring end 40b is in

pressing contact with an inner wall surface of the position control arm 6j in the first spring engaging hole 6k (see Figure 120). The front torsion coil spring 39 is prevented from coming off the front spring support portion 6f from the front end thereof in the optical axis direction by the front spring hold projection 6h, while the rear torsion coil spring 40 is prevented from coming off the rear spring support portion 6g from the rear end thereof in the optical axis direction by the rear spring hold projection 6i.

Aside from the installation of the front torsion coil spring 39 and the rear torsion coil spring 40, the pivot shaft 33 is inserted into the through hole 6d after the compression coil spring 38 is inserted into the spring-accommodation large diameter hole 6Z that is formed in the rear end portion of the rear spring support portion 6g. At this time, the flange 33a of the pivot shaft 33 enters the rear spring support portion 6g to contact with the rear end of the compression coil spring 38. The axial length of the pivot shaft 33 is greater than the axial length of the pivoted cylindrical portion 6b so that the opposite ends of the pivot shaft 33 project from the front and rear ends of the pivoted cylindrical portion 6b, respectively.

Concurrent with the above described installation

operations to the pivoted cylindrical portion 6b, the first eccentric shaft 34X and the second eccentric shaft 34Y are inserted into the first eccentric shaft support hole 8f and the second eccentric shaft support hole 8i, respectively. As shown in Figure 113, the diameter of a front end portion (left end portion as viewed in Figure 113) of the large diameter portion 34X-a of the first eccentric shaft 34X is greater than the diameter of the remaining portion of the large diameter portion 34X-a, and the inner diameter of a corresponding front end portion (left end portion as viewed in Figure 113) of the first eccentric shaft support hole 8f is greater than the inner diameter of the remaining portion of the first eccentric shaft support hole 8f. Likewise, the diameter of a front end portion (left end portion as viewed in Figure 113) of the large diameter portion 34Y-a of the second eccentric shaft 34Y is greater than the diameter of the remaining portion of the large diameter portion 34Y-a, and the inner diameter of a corresponding front end portion (left end portion as viewed in Figure 113) of the second eccentric shaft support hole 8i is greater than the inner diameter of the remaining portion of the second eccentric shaft support hole 8i. Therefore, when inserted into the first eccentric shaft support hole 8f from the front end thereof (the left end as viewed in

Figure 113), the first eccentric shaft 34X is prevented from being further inserted into the first eccentric shaft support hole 8f upon the stepped portion between the large diameter portion 34X-a and the remaining portion of the first eccentric shaft 34X contacting with the bottom of the large-diameter front end portion of the first eccentric shaft support hole 8f as shown in Figure 113. Likewise, when inserted into the second eccentric shaft support hole 8i from the front end thereof (the left end as viewed in Figure 113), the second eccentric shaft 34Y is prevented from being further inserted into the second eccentric shaft support hole 8i upon the stepped portion between the large diameter portion 34Y-a and the remaining portion of the first eccentric shaft 34Y contacting with the bottom of the large-diameter front end portion of the second eccentric shaft support hole 8i as shown in Figure 113. In this state, the front eccentric pin 34X-b and the front eccentric pin 34Y-b project forward in the optical axis direction from the front fixing surface 8c while the rear eccentric pin 34X-c and the eccentric pin 34Y-c project rearward in the optical axis direction from the rear fixing surface 8e.

Subsequently, the front second lens frame support plate 36 and the rear second lens frame support plate 37 are fixed to the front fixing surface 8c and the rear

fixing surface 8e, respectively, while the front end of the pivot shaft 33, which projects from the front end of the front spring support portion 6f of the pivoted cylindrical portion 6b, is fitted into the pivot hole 36b of the front second lens frame support plate 36 and at the same time the rear end of the pivot shaft 33 is fitted into the pivot hole 37b of the rear second lens frame support plate 37. At this time, the front eccentric pin 34X-b, the front eccentric pin 34Y-b and the front boss 8j which project forward from the front fixing surface 8c are inserted into the first vertically-elongated hole 36a, the horizontally-elongated hole 36e and the second vertically-elongated hole 36f, respectively, and also the rear eccentric pin 34X-c, the rear eccentric pin 34Y-c and the rear boss 8k which project rearward from the rear fixing surface 8e are inserted into the first vertically-elongated hole 37a, the horizontally-elongated hole 37e and the second vertically-elongated hole 37f, respectively. The front eccentric pin 34X-b is movable and immovable in the first vertically-elongated hole 36a in the lengthwise direction and the widthwise direction thereof (vertically and horizontally as viewed in Figure 110), respectively, the front eccentric pin 34Y-b is movable and immovable in the horizontally-elongated hole 36e in the lengthwise

direction and the widthwise direction thereof
(horizontally and vertically as viewed in Figure 110),
respectively, and the front boss 8j is movable and
immovable in the second vertically-elongated hole 36f in
5 the lengthwise direction and the widthwise direction
thereof (vertically and horizontally as viewed in Figure
110), respectively. Likewise, the rear eccentric pin
34X-c is movable and immovable in the first
vertically-elongated hole 37a in the lengthwise
10 direction and the widthwise direction thereof
(vertically and horizontally as viewed in Figure 111),
respectively, the rear eccentric pin 34Y-c is movable and
immovable in the horizontally-elongated hole 37e in the
lengthwise direction and the widthwise direction thereof
15 (horizontally and vertically as viewed in Figure 111),
respectively, and the rear boss 8k is movable and
immovable in the second vertically-elongated hole 37f in
the lengthwise direction and the widthwise direction
thereof (vertically and horizontally as viewed in Figure
20 111), respectively.

Lastly, the threaded shaft portion 66a of the set
screw 66 is inserted into the screw insertion hole 36d
and the screw insertion hole 8h, and is screwed through
the screw hole 37d to fix the front second lens frame
25 support plate 36 and the rear second lens frame support

plate 37 to the second lens group moving frame 8. In this state, screwing down the set screw 66 with the set screw 66 being engaged in the screw hole 37d causes the front second lens frame support plate 36 and the rear second lens frame support plate 37 to be pressed against the front fixing surface 8c and the rear fixing surface 8e, respectively, so that the front second lens frame support plate 36 and the rear second lens frame support plate 37 are fixed to the second lens group moving frame 8 with a spacing therebetween which corresponds to the spacing between the front fixing surface 8c and the rear fixing surface 8e in the optical axis direction. As a result, the first eccentric shaft 34X and the second eccentric shaft 34Y are prevented from coming off the second lens group moving frame 8 by the front second lens frame support plate 36 and the rear second lens frame support plate 37. The front end of the pivoted cylindrical portion 6b is pressed against the front second lens frame support plate 36 because the flange 33a of the pivot shaft 33 contacts with the rear second lens frame support plate 37 to be prevented from moving rearward beyond the rear second lens frame support plate 37 so that the pivot shaft 33 is biased forward in the optical axis direction by the spring force of the compression coil spring 38 which is compressed in the spring-accommodation large diameter hole 6Z of the

rear spring support portion 6g. This maintains the position of the second lens frame 6 relative to the second lens group moving frame 8 in the optical axis direction. In a state where the rear second lens frame support plate 5 37 is fixed to the second lens group moving frame 8, the guide key insertable recess 37g communicates with the key way 8p in the optical axis direction (see Figure 112).

After the front second lens frame support plate 36 is fixed to the second lens group moving frame 8, the front 10 spring end 39a of the front torsion coil spring 39 is placed into the spring engaging recess 36g. The rear spring end 39b of the front torsion coil spring 39 has been engaged with a portion of the second lens frame 6 between the pivoted cylindrical portion 6b and the swing 15 arm portion 6c as mentioned above. Placing the front spring end 39a into the spring engaging recess 36g causes the front torsion coil spring 39 to be twisted, thus causing the second lens frame 6 to be biased to rotate about the pivot shaft 33 in a counterclockwise direction 20 as viewed from front of the second lens frame 6 (counterclockwise as viewed in Figure 114).

Aside from the installation of the second lens frame 6, the rotation limit shaft 35 is inserted into the through hole 8m of the second lens group moving frame 8 from the 25 front end of the through hole 8m. An inner peripheral

surface in the through hole 8m is formed to prevent the rotation limit shaft 35 from being further inserted into the through hole 8m from the position of the rotation limit shaft 35 shown in Figures and 108 and 109. In this state
5 where the rotation limit shaft 35 is properly inserted into the through hole 8m, the eccentric pin 35b of the rotation limit shaft 35 projects rearward from the rear end of the through hole 8m as shown in Figure 109.

In a state where the second lens frame 6 is properly
10 mounted to the second lens group moving frame 8 in the above described manner, the second lens frame 6 can swing about the pivot shaft 33. The pivoted cylindrical portion receiving hole 8g of the second lens group moving frame 8 is sufficiently large so that the pivoted
15 cylindrical portion 6b and the swing arm portion 6c may not interfere with the inner edge in the pivoted cylindrical portion receiving hole 8g when the second lens frame 6 swings. Since the pivot shaft 33 extends parallel to the photographing optical axis Z1 and the optical axis
20 of the second lens group LG2, the second lens group LG2 swings about the pivot shaft 33 while the optical axis thereof remaining parallel to the photographing optical axis Z1 when the second lens frame 6 swings. One end of the range of rotation of the second lens frame 6 about
25 the pivot shaft 33 is determined by the engagement of the

tip of the engaging protrusion 6e with the eccentric pin 35b as shown in Figure 111. The front torsion coil spring 39 biases the second lens frame 6 to rotate in a direction to bring the tip of the engaging protrusion 6e into contact
5 with the eccentric pin 35b.

Subsequently, the shutter unit 76 is fixed to the second lens group moving frame 8 to obtain a sub-assembly shown in Figures 108 through 112. As can be seen in Figures 108 through 112, the shutter unit 76 is fixed to
10 the front of the central inner flange 8s. In this state where the shutter unit 76 is fixed to the front of the central inner flange 8s, the front fixing surface 8c is positioned in front of the shutter S and the adjustable diaphragm A in the shutter unit 76 in the optical axis
15 direction. A front portion of the cylindrical lens holder portion 6a of the second lens frame 6 is positioned in the vertically-elongated opening 8t, and is also positioned immediately behind the shutter unit 76 regardless of variation of the position of the second lens
20 frame 6 relative to the second lens group moving frame 8 as can be see in Figures 111 and 112.

In a state where the second lens group moving frame 8 and the second linear guide ring 10 are coupled to each other, the flexible PWB 77 that extends from the shutter
25 unit 76 is installed as shown in Figure 125. As described

above, the wide linear guide key 10c-W of the second linear guide ring 10 is engaged in the wide guide groove 8a-W. The flexible PWB 77, the wide guide groove 8a-W and the wide linear guide key 10c-W in a radial direction of the lens barrel axis Z0 are positioned in the same position in a circumferential direction of the zoom lens 71. Namely, the flexible PWB 77, the wide guide groove 8a-W and the wide linear guide key 10c-W are aligned in a radial direction perpendicular to the optical axis direction.

As shown in Figure 125, the flexible PWB 77 includes a first straight portion 77a, a loop-shaped turning portion 77b, a second straight portion 77c and a third straight portion 77d in this order from the side of the shutter unit 76. A bend of the flexible PWB 77 is formed between the second straight portion 77c and the third straight portion 77d in the vicinity of the front end of the wide linear guide key 10c-W. From the side of the shutter unit 76 (the left side as viewed in Figure 125), firstly the first straight portion 77a extends rearward in the optical axis direction from the shutter unit 76, and subsequently the flexible PWB 77 bends radially outwards to extend forward so that the loop-shaped turning portion 77b is formed in the vicinity of the rear end of the second lens group moving frame 8 and so that the second straight portion 77c extends forward in the optical axis direction

along an inner surface of the wide linear guide key 10c-W.
Subsequently, the flexible PWB bends radially outwards
to extend rearward so that the third straight portion 77d
extends rearward in the optical axis direction along an
5 outer surface of the wide linear guide key 10c-W.
Subsequently, the tip of the third straight portion 77d
(the tip of the flexible PWB) passes through the radial
through hole 10d to extend rearward, is further passed
through a hole 22q (see Figures 4 and 40) to extend through
10 to the outer side of the stationary barrel 22, to be
connected to the control circuit 140 via a main circuit
board (not shown). The third straight portion 77d is
partly fixed to the outer surface of the wide linear guide
key 10c-W by a fixing means such as a double-faced tape
15 (not shown) so that the size of the loop-shaped turning
portion 77b becomes variable in accordance with relative
axial movement between the second lens group moving frame
8 and the second linear guide ring 10.

The AF lens frame 51, which is positioned behind the
20 second lens group moving frame 8, is made of an opaque
material, and is provided with a forwardly-projecting
lens holder portion 51c, a first arm portion 51d and a
second arm portion 51e. The first arm portion 51d and
the second arm portion 51e are positioned on radially
25 opposite sides of the forwardly-projecting lens holder

portion 51c. The forwardly-projecting lens holder portion 51c is positioned in front of the first arm portion 51d and the second arm portion 51e in the optical axis direction. The pair of guide holes 51a and 52a, in which
5 the pair of AF guide shafts 52 and 53 are respectively fitted, are formed on the first arm portion 51d and the second arm portion 51e, respectively. The forwardly-projecting lens holder portion 51c is formed in a box shape (rectangular ring shape) including a substantially
10 square-shaped front end surface 51c1 and four side surfaces 51c3, 51c4, 51c5 and 51c6. The front end surface 51c1 lies in a plane orthogonal to the photographing optical axis Z1. The four side surfaces 51c3, 51c4, 51c5 and 51c6 extend rearward in a direction substantially
15 parallel to the photographing optical axis Z1, toward the CCD image sensor 60, from the four sides of the front end surface 51c1. The rear end of the forwardly-projecting lens holder portion 51c is formed as an open end which is open toward the low-pass filter LG4 the CCD image sensor
20 60. The forwardly-projecting lens holder portion 51c is provided on the front end surface 51c1 thereof with a circular opening 51c2 the center of which is coincident with the photographing optical axis Z1. The third lens group LG3 is positioned inside the circular opening 51c2.
25 The first arm portion 51d and the second arm portion 51e

extend from the forwardly-projecting lens holder portion 51c radially in opposite directions away from each other. More specifically, the first arm portion 51d extends from a corner of the forwardly-projecting lens holder portion 51c between the two side surfaces 51c3 and 51c6 radially in a lower-rightward direction as viewed from front of the AF lens frame 51, while the second arm portion 51e extends from another corner of the forwardly-projecting lens holder portion 51c between the two side surfaces 51c4 and 51c5 radially in an upper-leftward direction as viewed from front of the AF lens frame 51 as shown in Figure 130. As can be seen in Figures 128 and 129, the first arm portion 51d is fixed to the rear end of the corner of the forwardly-projecting lens holder portion 51c between the two side surfaces 51c3 and 51c6 while the second arm portion 51e is fixed to the rear end of the corner of the forwardly-projecting lens holder portion 51c between the two side surfaces 51c4 and 51c5.

As shown in Figure 9, radially outwards ends of the first arm portion 51d and the second arm portion 51e are positioned radially outside a cylindrical wall 22k of the stationary barrel 22. The pair of guide holes 51a and 52a are respectively formed on radially outer ends of the first arm portion 51d and the second arm portion 51e which are positioned outside the cylindrical wall 22k.

Accordingly, the AF guide shaft 52, which is fitted in the guide hole 51a and serves as a main guide shaft for guiding the AF lens frame 51 in the optical axis direction with a high positioning accuracy, is positioned outside
5 the cylindrical wall 22k, while the AF guide shaft 53, which is loosely fitted in the guide hole 51b to serve as an auxiliary guide shaft for secondarily guiding the AF lens frame 51 in the optical axis direction is also positioned outside the cylindrical wall 22k. As shown
10 in Figure 9, the cylindrical wall 22k is provided on the outer peripheral surface thereof with two radial projections 22t1 and 22t2 provided at different circumferential positions. A shaft-supporting hole 22v1 is formed on the rear surface of the radial projection
15 22t1. Similarly, a shaft-supporting hole 22v2 is formed on the rear surface of the radial projection 22t2. The CCD holder 21 is provided on the front surface thereof with two shaft-supporting holes 21v1 and 21v2 which oppose the shaft-supporting holes 22v1 and 22v2 in the optical
20 axis direction, respectively. The front end and the rear end of the AF guide shaft 52 are supported by (fixed to) the shaft-supporting hole 22v1 and the shaft-supporting hole 21v1, respectively. The front end and the rear end of the AF guide shaft 53 are supported by (fixed to) the
25 shaft-supporting hole 22v2 and the shaft-supporting hole

21v2, respectively.

The cylindrical wall 22k is provided with two cutout portions 22m and 22n (see Figure 11) which are cut out along the AF guide shafts 52 and 53 to prevent the second arm portion 51e and the first arm portion 51d from interfering with the cylindrical wall 22k when the AF lens frame 51 moves in the optical axis direction. As shown in Figures 122 and 130, the pair of guide holes 51a and 52a are positioned on radially opposite sides of the photographing optical axis Z1, and accordingly, the pair of AF guide shafts 52 and 53 are positioned on radially opposite sides of the photographing optical axis Z1.

The AF lens frame 51 can move rearward in the optical axis direction to a point (rear limit for the axial movement of the AF lens frame 51) at which the forwardly-projecting lens holder portion 51c comes into contact with the filter holder portion 21b (see Figure 10) formed on a front surface of the CCD holder 21. In other words, the CCD holder 21 includes a stop surface (front surface of the filter holder portion 21b) which determines rear limit for the axial movement of the AF lens frame 51. In a state where the forwardly-projecting lens holder portion 51c is in contact with the filter holder portion 21b, the front end of the position-control cam bar 21a, which projects forward from the CCD

holder 21, is positioned in front of the AF lens frame 51 in the optical axis direction (see Figures 121, 123 and 124). The cam-bar insertable hole 36c of the front second lens frame support plate 36 and the cam-bar insertable hole 37c of the rear second lens frame support plate 37 are positioned on an axis of the position-control cam bar 21a. Namely, the cam-bar insertable hole 36c, the cam-bar insertable hole 37c and the position-control cam bar 21a are aligned in the optical axis direction.

As shown in Figures 103 and 104, the position-control cam bar 21a is provided at a front end thereof with the aforementioned retracting cam surface 21c which is inclined with respect to the optical axis direction, and is further provided along an inner side edge of the position-control cam bar 21a with a removed-position holding surface 21d which extends rearward from the retracting cam surface 21c in the optical axis direction. As can be seen in Figures 118 through 120 and 122, in which the position-control cam bar 21a is viewed from front thereof, the position-control cam bar 21a has a certain width in a substantially radial direction of the photographing optical axis Z1. The retracting cam surface 21c is formed as an inclined surface which is inclined forward in a direction from the radially inner side to the radially outer side of the position-control

cam bar 21a (i.e., from a side closer to the photographing optical axis Z1 to a side farther from the photographing optical axis Z1), substantially along a widthwise direction of the retracting cam surface 21c. In other words, the retracting cam surface 21c is formed as an inclined surface which is inclined forward in a direction away from the photographing optical axis Z1. In Figures 118 through 120, the retracting cam surface 21c is hatched for the purpose of illustration. Moreover, the position-control cam bar 21a is formed so that an upper surface and a lower surface of the position-control cam bar 21a become a concave surface and a convex surface, respectively, to prevent the position-control cam bar 21a from interfering with the pivoted cylindrical portion 6b of the second lens frame 6. In other words, the position-control cam bar 21a is formed as a portion a cylinder centered about the pivot shaft 33 of the second lens group 6, and the retracting cam surface 21c is a lead surface which is formed on the periphery (edge surface) of this cylinder. . The position-control cam bar 21a is provided on a lower surface thereof with a guide key 21e which is elongated in the optical axis direction. The guide key 21e extends from the rear end of the position-control cam bar 21a to an intermediate point thereon behind the front end of the position-control cam

bar 21a. Therefore, no part of the guide key 21e is formed on the position-control cam bar 21a in the vicinity of the front end thereof. The guide key 21e is formed to have a cross section shape allowed to enter the guide key insertable recess 37g in the optical axis direction.

Operations of the second lens group LG2, the third lens group LG3 and other associated elements, which are supported by the above described accommodating structure including a structure retracting the second lens frame 6 to the radially retracted position thereof, will be hereinafter discussed. The position of the second lens group moving frame 8 with respect to the CCD holder 21 in the optical axis direction is determined by a combination of the axial movement of the cam ring 11 by the cam diagrams of the plurality of inner cam grooves 11a (11a-1 and 11a-2) and the axial movement of the cam ring 11 itself. The second lens group moving frame 8 is positioned farthest from the CCD holder 21 when the zoom lens 71 is set at about the wide-angle extremity as shown above the photographing optical axis Z1 in Figure 9, and is positioned closest to the CCD holder 21 when the zoom lens 71 is in the retracted state as shown in Figure 10. The second lens frame 6 is retracted to the radially retracted position thereof by utilizing the retracting rearward movement of the second lens group moving frame

8 from the frontmost axial position thereof (wide-angle extremity) to the rearmost axial position thereof (retracted position).

In the zooming range between the wide-angle extremity and the telephoto extremity, the second lens frame 6 is held still at a fixed position by the engagement of the tip of the engaging protrusion 6e with the eccentric pin 35b of the rotation limit shaft 35 as shown in Figure 111. At this time, the optical axis of the second lens group LG2 is coincident with the photographing optical axis Z1, so that the second lens frame 6 is in a photographing position thereof. When the second lens frame 6 is in a photographing position thereof as shown in Figure 111, a part of the position control arm 6j and the rear movable spring end 40b of the rear torsion coil spring 40 are exposed to the rear of the second lens group moving frame 8 through the cam-bar insertable hole 37c.

Upon the main switch of the digital camera 70 being turned OFF in the ready-to-photograph state of the zoom lens 71, the control circuit 140 drives the AF motor 160 in the lens barrel retracting direction to move the AF lens frame 51 rearward, toward the CCD holder 21 to a rearmost position (retracted position) thereof as shown in Figures 121, 123 and 124. The forwardly-projecting lens holder portion 51c holds the third lens group LG3

therein in the vicinity of the front end surface 51c1. The space immediately behind the third lens group LG3 is provided as an open space surrounded by the four side surfaces 51c3, 51c4, 51c5 and 51c6 so that the low-pass filter LG4 and the CCD image sensor 60, which are supported by the CCD holder 21 (the filter holder portion 21b), can enter the space immediately behind the third lens group LG3 so as to reduce the space between the third lens group LG3 and the low-pass filter LG4 when the AF lens frame 51 is retracted to the rearmost position. In a state where the AF lens frame 51 is in the rearmost position as shown in Figure 10, the front end of the position-control cam bar 21a is positioned in front of the AF lens frame 51 in the optical axis direction.

Subsequently, the control circuit 140 drives the zoom motor 150 in the lens barrel retracting direction to perform the above described lens barrel retracting operation. Keep driving the zoom motor 150 in the lens barrel retracting direction beyond the wide-angle extremity of the zoom lens 71 causes the cam ring 11 to move rearward in the optical axis direction while rotating about the lens barrel axis 20 due to engagement of the set of three roller followers 32 with the set of three through-slots 14e, respectively. As can be understood from the relationship shown in Figure 17 between the

plurality of inner cam grooves 11a and the plurality of
cam followers 8b, even though the second lens group moving
frame 8 is positioned closer to the front of the zoom lens
71 in the optical axis direction relative to the cam ring
11 when the zoom lens 71 is in the retracted position than
5 that when the zoom lens 71 is in the wide-angle extremity,
the second lens group moving frame 8 comes near the CCD
holder 21 when the zoom lens 71 is in the retracted state
because the amount of rearward movement of the cam ring
11 relative to the stationary barrel 22 is greater than
10 the amount of forward movement of the second lens group
moving frame 8 in the cam ring 11 relative to the cam ring
11 in the lens barrel retracting operation.

A further retracting movement of the second lens
15 group moving frame 8 together with the second lens frame
6 causes the front end of the position-control cam bar
21a to enter the cam-bar insertable hole 37c (see Figure
105). As described above, a part of the position control
arm 6j and the rear movable spring end 40b of the rear
20 torsion coil spring 40 are exposed to the rear of the
second lens group moving frame 8 through the cam-bar
insertable hole 37c as shown in Figure 111. Figure 118
shows the positional relationship at this time among the
position control arm 6j, the rear movable spring end 40b
25 and the position-control cam bar 21a, viewed from the

front of the zoom lens 71. The rear movable spring end 40b is positioned closer to the position-control cam bar 21a than the position control arm 6j (except for a protrusion formed thereon for the formation of the first spring engaging hole 6k) in a radial direction of the photographing optical axis Z1. On the other hand, the retracting cam surface 21c is formed as an inclined surface which is inclined forward in a direction away from the photographing optical axis Z1. A frontmost portion of the retracting cam surface 21c is positioned immediately behind the rear movable spring end 40b of the rear torsion coil spring 40 in the state shown in Figure 118. A rearward movement of the second lens frame 6 together with the second lens group moving frame 8 toward the CCD holder 21 with the positional relationship shown in Figure 118 being maintained causes the retracting cam surface 21c to come into contact with the rear movable spring end 40b, not the position control arm 6j of the second lens frame 6. Figure 123 shows the position of the second lens frame 6 at the time immediately before the rear movable spring end 40b comes into contact with the retracting cam surface 21c.

A further rearward movement of the second lens frame 6 together with the second lens group moving frame 8 with the rear movable spring end 40b remaining in contact with

the retracting cam surface 21c causes the rear movable spring end 40b to slide on the retracting cam surface 21c in a clockwise direction as viewed in Figure 118 in accordance with the shape of the retracting cam surface 21c. This clockwise rotation of the rear movable spring end 40b is transferred to the second lens group 6 via the front stationary spring end 40a. The spring force (rigidity) of the rear torsion coil spring 40 is predetermined to be capable of transferring a torque from the rear movable spring end 40b to the second lens group 6 via the front stationary spring end 40a without the front stationary spring end 40a and the rear movable spring end 40b being further pressed to move in opposite directions approaching each other than those shown in Figures 118 through 120. Namely, the resiliency of the rear torsion coil spring 40 is determined to be greater than that of the front torsion coil spring 39 at the time the front torsion coil spring 39 holds the second lens frame 6 in the photographing position.

Upon receiving a turning force from the retracting cam surface 21c via the rear torsion coil spring 40, the second lens group 6 rotates about the pivot shaft 33 against the spring force of the front torsion coil spring 39 from the photographing position shown in Figure 111 toward the radially retracted position shown in Figure

112 in accordance with the retracting movement of the second lens group moving frame 8. With this rotation of the second lens group 6, the rear movable spring end 40b of the rear torsion coil spring 40 slides on the retracting cam surface 21c from the position shown in Figure 118 to the position shown in Figure 119. Upon the second lens frame 6 rotating to the radially retracted position shown in Figure 112, the rear movable spring end 40b moves from the retracting cam surface 21c to the removed-position holding surface 21d to be engaged therewith. Thereafter, the second lens frame 6 is not rotated about the pivot shaft 33 in a direction to the radially retracted position by a retracting movement of the second lens group moving frame 8. In a state where the second lens frame 6 is held in the radially retracted position as shown in Figure 112, an outer peripheral portion of the cylindrical lens holder portion 6a enters the radial recess 8q while an outer edge of the engaging protrusion 6e enters the second radial recess 8r of the second lens group moving frame 8.

20 After the second lens frame 6 reaches the radially retracted position, the second lens group moving frame 8 continues to move rearward until reaching the retracted position shown in Figure 10. During this rearward movement of the second lens group moving frame 8, the second lens group 6 moves rearward together with the

25

second lens group moving frame 8 to the position shown in Figure 124 with the second lens group 6 held in the radially retracted position, in which the rear movable spring end 40b remains in engaged with the retracting cam surface 21c. At this time, the front end of the position-control cam bar 21a projects forward from the cam-bar insertable hole 37c through the cam-bar insertable hole 36c and the pivoted cylindrical portion receiving hole 8g.

As shown in Figures 10 and 124, in the retracted state of the zoom lens 71, the cylindrical lens holder portion 6a of the second lens frame 6 has moved into the space immediately above the forwardly-projecting lens holder portion 51c, the forwardly-projecting lens holder portion 51c has moved into that space in the second lens group moving frame 8 in which the second lens group LG2 is positioned in the ready-to-photograph state of the zoom lens 71, and the third lens group LG3 is positioned immediately behind the shutter unit 76. In addition, the low-pass filter LG4 and the CCD image sensor 60 have entered the forwardly-projecting lens holder portion 51c from the rear thereof by a rearward movement of the forwardly-projecting lens holder portion 51c, and accordingly, the space between the third lens group LG3 and the low-pass filter LG4 and also the space between

the third lens group LG3 and the CCD image sensor 60 in the optical axis direction are smaller in the retracted state of the zoom lens 71 than those in the ready-to-photograph state of the zoom lens 71 as can be seen by
5 making a comparison between Figures 9 and 10. Namely, in the retracted state of the zoom lens 71, the second lens group LG2 is positioned in the space radially outside the space in which the third lens group LG3, the low-pass filter LG4 and the CCD image sensor 60 are positioned.
10 In a conventional photographing lens barrel including a plurality of optical elements in which one or more movable optical elements thereof are moved only along a photographing optical axis, it is impossible to make the length of the photographing lens barrel smaller than the
15 sum of the thicknesses of all the plurality of optical elements. However, according to the accommodating structure of the zoom lens 71, it is substantially unnecessary to secure any space for accommodating the second lens group LG2 on the photographing optical axis
20 Z1. This makes it possible to make the length of the zoom lens 71 smaller than the sum of the thicknesses of all the plurality of optical elements of the zoom lens 71.

In the present embodiment of the zoom lens, the AF lens frame 51 has various features in its shape and
25 supporting structure that make it possible to retract the

zoom lens 71 in the camera body 72 in a highly space-saving fashion. Such features will be hereinafter discussed in detail.

The AF guide shaft 52 ,which serves as a main guide
5 shaft for guiding the AF lens frame 51 in the optical axis
direction with a high positioning accuracy, and the AF
guide shaft 53, which serves as an auxiliary guide shaft
for secondarily guiding the AF lens frame 51 in the optical
axis direction, are positioned outside cylindrical wall
10 22k of the stationary barrel 22 on radially opposite sides
of the photographing optical axis Z1 (at positions not
interfering with any of the movable lens groups of the
zoom lens 71). This structure of the AF lens frame 51
contributes to a reduction of the length of the zoom lens
15 71 when the zoom lens 71 is retracted into the camera body
72 because neither the AF guide shaft 52 nor the AF guide
shaft 53 becomes an obstruction which interferes with one
or more of the first through third lens groups LG1, LG2
and LG3 and the low-pass filter LG4.

20 In other words, according to such a structure of the
AF lens frame 51, since the pair of AF guide shafts 52
and 53 can be disposed freely without being subject to
constraints by moving parts positioned in the stationary
barrel 22 such as the second lens frame 6, the effective
25 length of each of the AF guide shafts 52 and 53 for guiding

the AF lens frame 51 in the optical axis direction can be made long enough to guide the AF lens frame 51 in the optical axis direction with a high positioning accuracy. As can be seen in Figures 9 and 10, the LCD panel 20 is
5 positioned immediately behind the zoom lens barrel 71 (on a rearward extension line of the optical axis Z1) while the pair of AF guide shafts 52 and 53 are positioned outside the LCD panel 20 in radial directions of the lens barrel axis Z0. This arrangement achieves the pair of
10 AF guide shafts 52 and 53 having long axial lengths which are largely extended even toward the rear of the camera body 72 without interfering with the LCD panel 20 that is comparatively large in dimension. In practice, the rear end of the AF guide shaft 52 is extended to a position
15 below the LCD panel 20 in the camera body 72 as shown in Figure 9.

Additionally, an annular space which is surrounded by the outer peripheral surface of the forwardly-projecting lens holder portion 51c, the first arm portion
20 51d, the second arm portion 51e and the inner peripheral surface of the stationary barrel 22 (the AF guide shafts 52 and 53) is secured due to the structure wherein the AF lens frame 51 is shaped so that the first arm portion 51d extends radially outwards from the rear end of the
25 corner of the forwardly-projecting lens holder portion

51c between the two side surfaces 51c3 and 51c6 and so that the second arm portion 51e extends radially outwards from the rear end of the corner of the forwardly-projecting lens holder portion 51c between the two side surfaces 51c4 and 51c5. This annular space is used to accommodate not only the second lens group LG2 but also rear end portions of annular members such as the first through third external barrels 12, 13 and 15 and the helicoid ring 18 to maximize the utilization of the internal space of the camera body 72. Moreover, the annular space contributes to a further retraction of the zoom lens 71 in the camera body 72 (see Figure 10). If the AF lens frame 51 does not have the above described space-saving structure, e.g., if each of the first and second arm portions 51d and 51e is formed on the forwardly-projecting lens holder portion 51c to extend radially from an axially intermediate portion or an axially front end portion thereof unlike the present embodiment of the zoom lens, such elements as the second lens group L2 cannot be retracted to their respective positions shown in Figure 10.

In addition, in the present embodiment of the zoom lens, the AF lens frame 51 is constructed so that the third lens group LG3 is supported by the forwardly-projecting lens holder portion 51c in a front end space thereof and

so that the low-pass filter LG4 and the CCD image sensor 60 are accommodated in the space in the rear of the forwardly-projecting lens holder portion 51c in the retracted state of the zoom lens 71. This further
5 maximizes the utilization of the internal space of the zoom lens 71.

Upon the main switch of the digital camera 70 being turned ON in the retracted state of the zoom lens 71, the control circuit 140 drives the AF motor 160 in the lens
10 barrel advancing direction so that the above described moving parts operate in the reverse manner to the above described retracting operations. The cam ring 11 advances while rotating relative to the first linear guide ring 14 and at the same time the second lens group moving
15 frame 8 and the first external barrel 12 advance together with the cam ring 11 without rotating relative to the first linear guide ring 14. At an initial stage of the advancement of the second lens group moving frame 8, the second lens frame 6 remains in the radially retracted
20 position since the rear movable spring end 40b is still engaged with the removed-position holding surface 21d. A further forward movement of the second lens group moving frame 8 causes the rear movable spring end 40b to firstly reach the front end of the position-control cam bar 21a
25 and subsequently be disengaged from the removed-position

holding surface 21d to be engaged with the retracting cam surface 21c as shown in Figure 120. At this stage, the cylindrical lens holder portion 6a of the second lens frame 6 has moved ahead of the forwardly-projecting lens holder portion 51c in the optical axis direction, so that the cylindrical lens holder portion 6a does not interfere with the forwardly-projecting lens holder portion 51c even if the second lens frame 6 commences to rotate about the pivot shaft 33 in a direction to the photographing position. A further forward movement of the second lens group moving frame 8 causes the rear movable spring end 40b to slide on the retracting cam surface 21c so that the second lens frame 6 starts rotating from the radially retracted position to the photographing position by the spring force of the front torsion coil spring 39.

A further forward movement of the second lens group moving frame 8 firstly causes the rear movable spring end 40b to keep sliding on the retracting cam surface 21c in a direction away from the removed-position holding surface 21d (left to right as viewed in Figure 118), and subsequently causes the rear movable spring end 40b to be disengaged from the retracting cam surface 21c upon the rear movable spring end 40b moving to a predetermined point on the retracting cam surface 21c. At this time, the relative position between the rear movable spring end

40b and the retracting cam surface 21c as viewed from front of the second lens frame 6 corresponds to that shown in Figure 118. As a result, the second lens frame 6 becomes totally free from the constraint of the position-control
5 cam bar 21a. Consequently, the second lens frame 6 is held in the photographing position as shown in Figure 111 with the tip of the engaging protrusion 6e being in pressing contact with the eccentric pin 35b of the rotation limit shaft 35 by the spring force of the front
10 torsion coil spring 39. Namely, the optical axis of the second lens group LG2 coincides with the photographing optical axis Z1. The second lens frame 6 finishes rotating from the radially retracted position to the photographing position by the time the zoom lens 71 has
15 been extended to the wide-angle extremity when the main switch of the digital camera 70 is turned ON.

Although the AF lens frame 51 moves forward from its rearmost position when the zoom lens 71 changes from the retracted state shown in Figure 10 to the ready-to-
20 photograph state shown in Figure 9, the forwardly-projecting lens holder portion 51c still covers the front of the low-pass filter LG4 and the CCD image sensor 60 even in the ready-to-photograph state shown in Figure 9 so that the front end surface 51c1 and the four side
25 surfaces 51c3, 51c4, 51c5 and 51c6 can prevent unnecessary

light such as stray light from being incident on the low-pass filter LG4 and the CCD image sensor 60 through any part other than the third lens group LG3. Accordingly, the forwardly-projecting lens holder portion 51c of the AF lens frame 51 serves as not only a member for supporting the third lens group LG3 but also a member for accommodating the low-pass filter LG4 and the CCD 60 in the retracted state of the zoom lens 71, and also a light shield member for preventing unnecessary light such as stray light from being incident on the low-pass filter LG4 and the CCD image sensor 60 in the ready-to-photograph state of the zoom lens 71.

In general, a structure supporting a movable lens group of a photographing lens system must be precise so as not to deteriorate the optical performance of the photographing lens system. In the present embodiment of the zoom lens, each of the second lens frame 6 and the pivot shaft 33, in particular, is required to have high dimensional accuracy which is several orders of magnitude higher than those of simple movable elements since the second lens group LG2 is driven to not only move along the photographing optical axis Z1 but also rotate to retract to the radially retracted position. For instance, with the shutter unit 76 (having exposure control devices such as the shutter S and the diaphragm A) provided inside

the second lens group moving frame 8, if a pivot shaft corresponding to the pivot shaft 33 is provided in front of or behind the shutter unit 76, the length of the pivot shaft would be limited, or would make the pivot shaft act
5 as a cantilever type pivot shaft. Nevertheless, since it is necessary to secure a minimum clearance allowing the pivot shaft (such as the pivot shaft 33) and a through hole (such as the through hole 6d) into which the pivot shaft is fitted to rotate relative to each other, such
10 a clearance may cause the axis of the through hole to tilt relative to the axis of the pivot shaft if the pivot shaft is a short shaft or a cantilever pivot shaft. Even if within tolerance in a conventional lens supporting structure, such a tilt must be prevented from occurring
15 in the present embodiment of the zoom lens because each of the second lens frame 6 and the pivot shaft 33 is required to have a very high dimensional accuracy.

In the above described retracting structure for the second lens frame 6, since it can be seen in Figures 108,
20 109 and 113 that the front second lens frame support plate 36 and the rear second lens frame support plate 37 are respectively fixed to the front fixing surface 8c and the rear fixing surface 8e, which are respectively positioned on front and rear of the shutter unit 76 in the optical
25 axis direction, and that the pivot shaft 33 is disposed

to extend between the front second lens frame support plate 36 and the rear second lens frame support plate 37, both the front end and the rear end of the pivot shaft 33 are supported by the front second lens frame support plate 36 and the rear second lens frame support plate 37, respectively. Accordingly, the axis of the pivot shaft 33 does not easily tilt with respect to the axis of the through hole 6d of the second lens frame 6. Moreover, the pivot shaft 33 can be lengthened regardless of the shutter unit 76 (without interfering with the shutter unit 76) since the front second lens frame support plate 36, the rear second lens frame support plate 37 and the pivoted cylindrical portion receiving hole 8g, which serve as elements of the structure supporting the pivot shaft 33, are positioned not to overlap the shutter unit 76. In fact, the pivot shaft 33 is elongated so that the length thereof becomes close to the length of the second lens group moving frame 8 in the optical axis direction. In accordance with the length of the pivot shaft 33, the pivoted cylindrical portion 6b is elongated in the optical axis direction. Namely, a wide range of engagement in the axial direction is secured between the pivoted cylindrical portion 6b and the pivot shaft 33. With this structure, there is little possibility of the second lens frame 6 from tilting with respect to the pivot shaft 33,

which makes it possible to rotate the second lens frame 6 about the pivot shaft 33 with a high degree of positioning accuracy.

The front boss 8j and the rear boss 8k that project from the front fixing surface 8c and the rear fixing surface 8e determine the position of the front second lens frame support plate 36 and the position of the rear second lens frame support plate 37, respectively, and the front and rear second lens frame support plates 36 and 37 are firmly fixed to the second lens group moving frame 8 by the common set screw 66. With this structure, the front and rear second lens frame support plates 36 and 37 are positioned relative to the second lens group moving frame 8 with a high degree of positioning accuracy. Therefore, the pivot pin 33 is also positioned relative to the second lens group moving frame 8 with a high degree of positioning accuracy.

In the present embodiment of the zoom lens, the set of three extensions 8d are formed on the front end surface of the second lens group moving frame 8 in front of the front fixing surface 8c, whereas the rear fixing surface 8e is flush with the rear end surface of the second lens group moving frame 8. Namely, the front fixing surface 8c is not formed on the frontmost end surface of the second lens group moving frame 8. However, if the second lens

group moving frame 8 is formed as a simple cylindrical member having no projections such as the set of three extensions 8d, the front and rear second lens frame support plates 36 and 37 can be fixed to frontmost and
5 rearmost end surfaces of the simple cylindrical member, respectively.

In the above described retracting structure for the second lens frame 6, if the range of movement of the second lens group moving frame 8 in the optical axis direction
10 from the position corresponding to the wide-angle extremity to the retracted position is fully used to rotate the second lens frame 6 about the pivot shaft 33 from the photographing position to the radially retracted position, the second lens frame 6 will interfere with the
15 forwardly-projecting lens holder portion 51c of the AF lens frame 51 on the way to the radially retracted position. To prevent this problem from occurring, in the above described retracting structure for the second lens frame 6, the second lens frame 6 finishes rotating to the
20 radially retracted position within an axial range of movement sufficiently shorter than the range of movement of the second lens group moving frame 8 in the optical axis direction, and subsequently the cylindrical lens holder portion 6a of the second lens frame 6 moves rearward
25 in parallel in the optical axis direction to the space

immediately above the forwardly-projecting lens holder
portion 51c. Therefore, the space for the parallel
displacement of the cylindrical lens holder portion 6a
to the space immediately above the forwardly-projecting
5 lens holder portion 51c must be secured in the zoom lens
71. In order for the second lens frame 8 to secure a
sufficient range of rotation from the photographing
position to the radially retracted position within a short
range of movement in the optical axis direction, it is
10 necessary to increase the inclination of the retracting
cam surface 21c, that is formed on the front end of the
position-control cam bar 21a of the CCD holder 21, with
respect to the direction of movement of the second lens
group moving frame 8, i.e., with respect to the optical
15 axis direction. While the retracting cam surface 21c
that is formed in such a manner presses the rear movable
spring end 40b during the rearward movement of the second
lens group 8, a great reaction force is exerted on the
position-control cam bar 21a and the second lens group
20 moving frame 8; such a reaction force is greater than that
in the case where a cam surface (which corresponds to the
cam surface 21c) the inclination of which with respect
to the direction of movement of the second lens group
moving frame 8 is small presses the rear movable spring
25 end 40b during the rearward movement of the second lens

group 8.

The position-control cam bar 21a is a fixed member just like the stationary barrel 22, whereas the second lens group moving frame 8 is a linearly movable member; 5 the second lens group moving frame 8 is guided linearly without rotating about the lens barrel axis Z0 indirectly by the stationary barrel 22 via such intermediate members as the first and second linear guide rings 14 and 10, not directly by the stationary barrel 22. A clearance exists 10 in each of the following two engagements: the engagement of the second lens group moving frame 8 with the second linear guide ring 10 and the engagement of the second linear guide ring 10 with the second linear guide ring 14. Due to this reason, it has to be taken into account 15 that such clearances may cause the second lens group moving frame 8 and the CCD holder 21 to become misaligned in the plane orthogonal to the lens barrel axis Z0 to thereby exert an averse effect on the retracting operation for the second lens frame 6 from the photographing 20 position to the radially retracted position if a great reaction force is exerted on the position-control cam bar 21a and the second lens group moving frame 8. For instance, if the second lens frame 6 rotates beyond an original radial-outer limit thereof (see Figure 112) for 25 the rotational movement of the second lens frame 6 about

the pivot shaft 33 when rotated from the photographing position to the radially retracted position, the cylindrical lens holder portion 6a may interfere with an inner peripheral surface of the second lens group moving frame 8. Likewise, if the second lens frame 6 stops rotating before the original radial-outer limit when rotated from the photographing position to the radially retracted position, i.e., if the second lens frame 6 does not rotate to the original radial-outer limit when rotated from the photographing position to the radially retracted position, the cylindrical lens holder portion 6a may interfere with the AF lens frame 51 and others.

The position-control cam bar 21a and the second lens group moving frame 8 are prevented from being misaligned by inserting the guide key 21e into the guide key insertable recess 37g to hold the second lens frame 6 precisely in the radially retracted position when the second lens frame 6 rotates from the photographing position to the radially retracted position (see Figure 106). Specifically, when the second lens group moving frame 8 is in the process of retracting toward the retracted position with the second lens frame 6 having been held in the radially retracted position by the engagement of the rear movable spring end 40b of the rear torsion coil spring 40 with the removed-position holding

surface 21d, the guide key 21e enters the key way 8p of the second lens group moving frame 8 from the rear end thereof through the guide key insertable recess 37g. Since the guide key 21e and the key way 8p are an elongated
5 projection and an elongated groove which extend in the optical axis direction, the guide key 21e is freely movable relative to the key way 8p in the optical axis direction and prevented from moving in a widthwise direction of the key way 8p when the guide key 21e is
10 engaged in the key way 8p. Due to this structure, even if a comparatively great reaction force is exerted on the second lens group moving frame 8 while the retracting cam surface 21c presses the rear movable spring end 40b, the engagement of the guide key 21e with the key way 8p
15 prevents the second lens group moving frame 8 and the position-control cam bar 21a from being misaligned in the plane orthogonal to the lens barrel axis Z0. Consequently, the second lens frame 6 is held precisely in the radially retracted position when the second lens
20 frame 6 rotates from the photographing position to the radially retracted position.

Although the guide key 21e commences to be engaged in the key way 8p after the second lens frame 6 has been rotated to the radially retracted position in the present
25 embodiment of the zoom lens, the guide key 21e can commence

to be engaged in the key way 8p before the second lens frame 6 has been rotated to the radially retracted position or during the retracting movement of the second lens frame 6 toward the radially retracted position. In short, the second lens group moving frame 8 and the position-control cam bar 21a have only to be precisely aligned at the time when the second lens frame 6 is held in the radially retracted position after all. The timing of commencement of the engagement between the guide key 21e with the key way 8p can be freely determined by, e.g., changing the axial range of formation of the guide key 21e in the optical axis direction.

It is possible that the guide key 21e and the key way 8p be replaced by a key way corresponding to the key way 8p and a guide key corresponding to the guide key 21e, respectively.

Although the guide key 21e is formed on the position-control cam bar 21a which includes the retracting cam surface 21c in the above illustrated embodiment, an element corresponding to the guide key 21e can be formed on any portion on the CCD holder 21 other than the position-control cam bar 21a. However, from a structural point of view, it is desirable that the guide key 21e be formed together with the retracting cam surface 21c on the position-control cam bar 21a. In addition,

to align the second lens group moving frame 8 and the position-control cam bar 21a precisely, it is desirable that the guide key 21e be formed on the position-control cam bar 21a which serves as an engaging portion which is engageable with the second lens frame 6 through the side second lens group moving frame 8.

Not only the aforementioned reaction force which is exerted on the second lens group moving frame 8 while the retracting cam surface 21c presses the rear movable spring end 40b, but also the positioning accuracy of each element of the retracting structure for the second lens frame 6 exert an adverse influence on the operating accuracy of the second lens frame 6. As described above, it is undesirable if the range of rotation of the second lens frame 6 about the pivot shaft 33 from the photographing position to the radially retracted position is either excessive or insufficient. However, if a force which may retract the second lens frame 6 beyond the radially retracted position shown in Figure 112 is applied to the second lens frame 6, a mechanical stress is applied to the retracting structure for the second lens frame 6 because cylindrical lens holder portion 6a and the engaging protrusion 6e are brought very close to an inner peripheral surface of the second lens group moving frame 8 in the retracted state of the zoom lens 71 to achieve

a space-saving retracting structure for the second lens frame 6 (see Figure 112). Accordingly, it is required to prevent such a mechanical stress from being applied to the retracting structure for the second lens frame 6.

5 To prevent such mechanical stress from being applied to the retracting structure for the second lens frame 6, rather than the position control arm 6j of the pivoted cylindrical portion, the rear movable spring end 40b of the rear torsion coil spring 40 serves as a portion which
10 is to be engageable with the retracting cam surface 21c and the removed-position holding surface 21d when the second lens frame 6 retracts from the photographing position to the radially retracted position so that a slight error in movement of the second lens group 6 is
15 absorbed by a resilient deformation of the rear torsion coil spring 40. Although the rear torsion coil spring 40 transfers a torque from the rear movable spring end 40b to the second lens group 6 via the front stationary spring end 40a without the front stationary spring end
20 40a and the rear movable spring end 40b being further pressed to move in opposite directions approaching each other than those shown in Figures 118 through 120 as mentioned above in a normal retracting operation of the zoom lens 71, the rear movable spring end 40b is further
25 pressed to move in a direction approaching the front

stationary spring end 40a than the rear movable spring end 40b shown in Figures 118 through 120 within the range q1 shown in Figure 120 if the position-control cam bar 21a slightly deviates leftward, as viewed in Figure 120
5 from the original position shown in Figure 120, since the rear movable spring end 40b is allowed to move in the first spring engaging hole 6k in the range q1 as mentioned above. Accordingly, such a movement of the rear movable spring end 40b within the range NR1 can absorb the deviation of
10 the position-control cam bar 21a from the original position thereof. Namely, even if the position-control cam bar 21a further presses the rear movable spring end 40b in a state where the cylindrical lens holder portion 6a and the engaging protrusion 6e are in contact with an
15 inner peripheral surface of the second lens frame moving frame 8 (in a state where an outer peripheral portion of the cylindrical lens holder portion 6a and an outer edge of the engaging protrusion 6e have entered the radial recess 8q and the second radial recess 8r, respectively),
20 an excessive mechanical stress is prevented from being applied to the retracting structure for the second lens frame 6 by a resilient deformation of the rear torsion coil spring 40.

In the retracting structure for the second lens
25 frame 6, when the second lens frame 6 is in the radially

retracted position as shown in Figure 112, a radially outside surface of the swing arm portion 6c is positioned to adjoin the bottom of the wide guide groove 8a-W to partly close the bottom of the wide guide groove 8a-W.

5 In other words, the bottom of the wide guide groove 8a-W is formed on the radially outside of an intermediate point of a line extending between the axis of the pivot shaft 33 and the retracted optical axis Z2 of the second lens group LG2, and a part of the flexible PWB 77 is positioned

10 in the wide guide groove 8a-W. Due to this structure, the swing arm portion 6c supports this part of the flexible PWB 77 from inside the second lens group moving frame 8 as shown in Figure 112 when the second lens frame 6 is positioned in the radially retracted position. Figure

15 126 shows the flexible PWB 77 and the second lens frame 6 by solid lines when the second lens frame 6 is positioned in the radially retracted position, and shows the second lens frame 6 by two-dot chain lines when the second lens frame 6 is positioned in the photographing position. It

20 can be understood from Figure 126 that the swing arm portion 6c prevents the flexible PWB 77 from curving radially inwards by pushing the first straight portion 77a and the loop-shaped turning portion 77b of the flexible PWB 77 radially outwards

25 Specifically, the swing arm portion 6c is provided

on a radially outer surface thereof with a straight flat surface 6q, and is further provided immediately behind the straight flat surface 6q with an oblique surface 6r. The rear projecting portion 6m projects rearward in the optical axis direction from a portion of the swing arm portion 6c immediately behind the straight flat surface 6q (see Figure 105). In the retracted state of the zoom lens 71, the straight flat surface 6q pushes the first straight portion 77a radially outwards while the oblique surface 6r and the rear projecting portion 6m push the loop-shaped turning portion 77b radially outwards. The oblique surface 6r is inclined to correspond to a curve of the loop-shaped turning portion 77b.

In typical retractable lenses, in the case where a flexible PWB extends between a movable element guided in an optical axis direction and a fixed element, the flexible PWB needs to be sufficiently long to cover the full range of movement of the movable element. Therefore, the flexible PWB tends to sag when the amount of advancement of the movable element is minimum, i.e., when the retractable lens is in the retracted state. Such a tendency of the flexible PWB is especially strong in the present embodiment of the zoom lens because the length of the zoom lens 71 is greatly reduced in the retracted state thereof by retracting the second lens group so that

it is positioned on the retracted optical axis Z2 and also by adopting a three-stage telescoping structure for the zoom lens 71. Since interference of any sag of the flexible PWB with internal elements of the retractable lens or jamming of a sagging portion of the flexible PWB into internal elements of the retractable lens may cause a failure of the retractable lens, it is necessary for the retractable lens to be provided with a structure preventing such problems associated with the flexible PWB from occurring. However, this preventing structure is generally complicated in conventional retractable lenses. In the present embodiment of the zoom lens 71, in the view of the fact that the flexible PWB 77 tends to sag when the zoom lens 71 is in the retracted state, the loop-shaped turning portion 77b is pushed radially outwards by the second lens frame 6 positioned in the radially retracted position, which reliably prevents the flexible PWB 77 from sagging with a simple structure.

In the retracting structure for the second lens frame 6 in the present embodiment of the zoom lens, the moving path of the second lens frame 6 from the photographing position to the radially retracted position extends obliquely from a point (front point) on the photographing optical axis Z1 to a point (rear point) behind the front point and above the photographing optical

axis Z1 because the second lens frame 6 moves rearward in the optical axis direction while rotating about the pivot shaft 33. On the other hand, the AF lens frame 51 is provided thereon between the front end surface 51c1 and the side surface 51c5 with a recessed oblique surface 51h. The recessed oblique surface 51h is inclined in a radially outward direction from the photographing optical axis Z1 from front to rear of the optical axis direction. The edge of the forwardly-projecting lens holder portion 51c between the front end surface 51c1 and the side surface 51c5 is cut out along a moving path of the cylindrical lens holder portion 6a so as to form the recessed oblique surface 51h. Moreover, the recessed oblique surface 51h is formed as a concave surface which corresponds to the shape of an associated outer surface of the cylindrical lens holder portion 6a.

As described above, the AF lens frame 51 moves rearward to the rear limit for the axial movement thereof (i.e., the retracted position), at which the AF lens frame 51 (forwardly-projecting lens holder portion 51c) comes into contact with the filter holder portion 21b (stop surface), before the commencement of retracting movement of the second lens frame 6 from the photographing position to the radially retracted position. In the state shown in Figure 123 in which the AF lens frame 51 is in contact

with the filter holder portion 21b while the second lens
frame 6 has not commenced to retract from the
photographing position to the radially retracted
position, if the second lens frame 6 starts moving
5 rearward in the optical axis direction while rotating
about the pivot shaft 33 to retract to the radially
retracted position, the rear end of the cylindrical lens
holder portion 6a firstly moves obliquely rearward while
approaching the recessed oblique surface 51h, and
10 subsequently further moves obliquely rearward while just
missing (passing closely across) the recessed oblique
surface 51h to finally reach a fully retracted position
shown in Figure 124. Namely, the retracting operation
for the second lens frame 6 from the photographing
15 position to the radially retracted position can be
performed at a closer point to the AF lens frame 51 in
the optical axis direction substantially by the amount
by which the oblique surface 51h is recessed.

If the recessed oblique surface 51h or a similar
20 surface is not formed on the AF lens frame 51, the
retracting operation for the second lens frame 6 from the
photographing position to the radially retracted
position has to be completed at an earlier stage than that
in the illustrated embodiment to prevent the cylindrical
25 lens holder portion 6a from interfering with the AF lens

frame 51. To this end, it is necessary to increase the amount of rearward movement of the second lens group moving frame 8 or the amount of projection of the position-control cam bar 21a from the CCD holder 22; this runs counter to further miniaturization of the zoom lens 71. If the amount of rearward movement of the second lens group moving frame 8 is fixed, the inclination of the retracting cam surface 21c with respect to the photographing axis direction has to be increased. However, if this inclination is excessively large, the reaction force which is exerted on the position-control cam bar 21a and the second lens group moving frame 8 while the retracting cam surface 21c presses the rear movable spring end 40b is increased. Accordingly, it is undesirable that the inclination of the retracting cam surface 21c be increased to prevent a jerky motion from occurring in the retracting operation for the second lens frame 6. In contrast, in the present embodiment of the zoom lens, the retracting movement of the second lens frame 6 from the photographing position to the radially retracted position can be performed even after the AF lens frame 51 has retracted at a point very close to the AF lens frame 51 due to the formation of the recessed oblique surface 51h. Therefore, even if the amount of rearward movement of the second lens group moving frame 8 is limited,

the retracting cam surface 21c does not have to be shaped to be inclined largely with respect to the optical axis direction. This makes it possible to achieve further miniaturization of the zoom lens 71 with a smoothing of the retracting movement of the second lens group moving frame 8. Similar to the AF lens frame 51, the CCD holder 21 is provided on a top surface thereof behind the recessed oblique surface 51h with a recessed oblique surface 21f the shape of which is similar to the shape of the recessed oblique surface 51h. The recessed oblique surface 51h and the recessed oblique surface 21f are successively formed along a moving path of the cylindrical lens holder portion 6a to be shaped like a single oblique surface. Although the AF lens frame 51 serves as a movable member guided in the optical axis direction in the illustrated embodiment, a lens frame similar to the AF lens frame 51 can be provided with a recessed oblique surface corresponding to the recessed oblique surface 51h to incorporate features similar to the above described features of the recessed oblique surface 51h even if the lens frame similar to the AF lens frame 51 is of a type which is not guided in an optical axis direction.

As can be understood from the above descriptions, the retracting structure for the second lens frame 6 is designed so that the second lens frame 6 does not interfere

with the AF lens frame 51 when moving rearwards while retracting radially outwards to the radially retracted position in a state where the AF lens frame 51 has retracted to the rear limit (the retracted position) for the axial movement of the AF lens frame 51 as shown in Figures 123 and 124. In this state, upon the main switch being turned OFF, the control circuit 140 drives the AF motor 160 in the lens barrel retracting direction to move the AF lens frame 51 rearward the retracted position thereof. However, if the AF lens frame 51 does not retract to the retracted position accidentally for some reason upon the main switch being turned OFF, the AF lens frame 51 may interfere with the moving path of the second lens group 6 which is in the middle of moving rearward together with the second lens group moving frame 8 while rotating to the radially retracted position (see Figures 127 and 129).

To prevent such a problem from occurring, the zoom lens 71 is provided with a fail-safe structure. Namely, the second lens frame 6 is provided on the swing arm portion 6c with the rear projecting portion 6m that projects rearward, beyond the rear end of the second lens group LG2, in the optical axis direction, while the AF lens frame 51 is provided, on that portion of the front end surface 51c1 of the forwardly-projecting lens holder

portion 51c which faces the rear projecting portion 6m, with a rib-like elongated protrusion 51f which projects forward from the front end surface 51c1 (see Figures 123, 124 and 127 through 130). As shown in Figure 130, the elongated protrusion 51f is elongated vertically, and is formed to lie in a plane orthogonal to the photographing optical axis Z1 to correspond to the range of rotation of the rear projecting portion 6m (the contacting surface 6n) about the pivot shaft 33 at the rotation of the second lens frame 6 from the photographing position to the radially retracted position. The rear projecting portion 6m and the rib-like elongated protrusion 51f are elements of the aforementioned fail-safe structure.

With the fail-safe structure, even if the second lens frame 6 starts retracting to the radially retracted position in a state where the AF lens frame 51 does not retract to the retracted position and stops short of the retracted position accidentally upon the main switch being turned OFF, the contacting surface 6n of the rear projecting portion 6m surely comes into contact with the rib-like elongated protrusion 51f of the AF lens frame 51 first. This prevents the second lens group LG2 from coming into collision with the AF lens frame 51 to get scratched and damaged thereby even if such a malfunction occurs. In other words, since the moving path of the rear

projecting portion 6m does not overlap the third lens group LG3 in the optical axis direction at any angular positions of the second lens frame 6, there is no possibility of any portions of the second lens group 6 other than the rear projecting portion 6m coming into contact with the third lens group LG3 to scratch the third lens group LG3. Accordingly, since the rear projecting portion 6m and the elongated protrusion 5lf are only the portions at which the second lens group LG2 and the AF lens frame 51 can contact with each other, the optical performances of the second lens group LG2 and the third lens group LG3 are prevented from deteriorating even if the AF lens frame 51 stops short of the retracted position accidentally upon the main switch being turned OFF. If such a malfunction occurs, it is possible for the second lens frame 6 in the process of moving rearward while rotating to the radially retracted position to push back the AF lens frame 51 forcefully, via the rear projecting portion 6m, which stops short of the retracted position.

Note that although in the illustrated embodiment, the contacting surface 6n and the rib-like elongated protrusion 5lf are (possible) contact surfaces, an alternative embodiment can be applied wherein (possible) contact surfaces of the second lens group frame 6 and the AF lens frame 51 differ from that of the illustrated

embodiment. For example, a projection like that of the rear projecting portion 6m can be provided on the AF lens frame 51. Namely, an appropriate position can be provided whereby the above-mentioned projection and
5 another member contact each other before the second lens group LG2 and the third lens group L3 contact any other members.

The contacting surface 6n lies in a plane orthogonal to the photographing optical axis Z1, whereas the front
10 surface of the elongated protrusion 51f is formed as an inclined contacting surface 51g which is inclined to a plane orthogonal to the optical axis of the photographing optical axis Z1 by an angle of NR2 as shown in Figure 128. The inclined contacting surface 51g is inclined toward
15 the rear of the optical axis direction in the direction of movement of the rear projecting portion 6m from a position when the second lens frame 6 is in the photographing position to a position when the second lens frame 6 is in the radially retracted position (upwards
20 as viewed in Figures 128 through 130). Unlike the illustrated embodiment, if the front surface of the elongated protrusion 51f is formed as a mere flat surface parallel to the contacting surface 6n, the frictional resistance produced between the elongated protrusion 51f
25 and the contacting surface 6n becomes great to impede a

smooth movement of the second lens frame 6 in the event that the contacting surface 6n comes into contact with the elongated protrusion 51f when the second lens frame 6 is in the process of moving rearward while rotating to the radially retracted position. In contrast, according to the present embodiment of the fail-safe structure, even if the contacting surface 6n comes into contact with the elongated protrusion 51f when the second lens frame 6 is in the middle of moving rearward while rotating to the radially retracted position, a great frictional resistance is not produced between the elongated protrusion 51f and the contacting surface 6n because of the inclination of the elongated protrusion 51f with respect to the contacting surface 6n. This makes it possible to retract the zoom lens 71 with reliability with less frictional force produced between the elongated protrusion 51f and the contacting surface 6n even if the aforementioned malfunction occurs. In the present embodiment of the fail-safe structure, the angle of inclination NR 2 shown in Figure 128 is set at three degrees as a desirable angle of inclination.

It is possible that the elongated protrusion 51f be formed so that the recessed oblique surface 51h can come into contact with the light shield ring 9, that is fixed to the rear end of the cylindrical lens holder portion

6a, to serve just like the inclined contacting surface 51g of the above illustrated embodiment of the fail-safe structure in the case where the AF lens frame 51 stops short of the retracted position accidentally to a lesser extent than the rear projecting portion 6m comes into contact with the elongated protrusion 51f.

In the retracted position for the second lens frame 6, the position of the optical axis of the second lens group LG2 can be adjusted in directions lying in a plane orthogonal to the photographing optical axis Z1 in such a case where the optical axis of the second lens group LG2 is not precisely coincident with the photographing optical axis Z1 even though the second lens group LG2 is in the photographing position. Such an adjustment is carried out by two positioning devices: a first positioning device for adjusting the positions of the front and rear second lens frame support plates 36 and 37 relative to the second lens group moving frame 8, and a second positioning device for adjusting the point of engagement of the eccentric pin 35b of the rotation limit shaft 35 with the engaging protrusion 6e of the second lens frame 6. The first eccentric shaft 34X and the second eccentric shaft 34Y are elements of the first positioning device; the positions of the front and rear second lens frame support plates 36 and 37 relative to

the second lens group moving frame 8 are adjusted by rotating the first eccentric shaft 34X and the second eccentric shaft 34Y. The rotation limit shaft 35 is a element of the second positioning device; the point of engagement of the eccentric pin 35b with the engaging protrusion 6e is adjusted by rotating the rotation limit shaft 35.

First, the first positioning device for adjusting the positions of the front and rear second lens frame support plates 36 and 37 relative to the second lens group moving frame 8 will be discussed hereinafter. As described above, the front eccentric pin 34X-b of the first eccentric shaft 34X is inserted into the first vertically-elongated hole 36a to be movable and immovable in the first vertically-elongated hole 36a in the lengthwise direction and the widthwise direction thereof, respectively, while the rear eccentric pin 34Y-b of the second eccentric shaft 34Y is inserted into the horizontally-elongated hole 36e to be movable and immovable in the horizontally-elongated hole 36e in the lengthwise direction and the widthwise direction thereof, respectively, as shown in Figures 110, 114 and 115. The lengthwise direction of the first vertically-elongated hole 36a, which corresponds to the vertical direction of the digital camera 70, is orthogonal to the lengthwise

direction of the horizontally-elongated hole 36e, which corresponds to the horizontal direction of the digital camera 70 as shown in Figures 110, 114 and 115. In the following descriptions, the lengthwise direction of the first vertically-elongated hole 36a is referred to as "Y-direction" while the lengthwise direction of the horizontally-elongated hole 36e is referred to as "X-direction".

The lengthwise direction of the first vertically-elongated hole 37a is parallel to the lengthwise direction of the first vertically-elongated hole 36a. Namely, the first vertically-elongated hole 37a is elongated in the Y-direction. The first vertically-elongated hole 36a and the first vertically-elongated hole 37a are formed at opposed positions on the front and rear second lens frame support plates 36 and 37 in the optical axis direction. The lengthwise direction of the horizontally-elongated hole 37e is parallel to the lengthwise direction of the horizontally-elongated hole 36e. Namely, the horizontally-elongated hole 37e is elongated in the X-direction. The horizontally-elongated hole 36e and the horizontally-elongated hole 37e are formed at opposed positions on the front and rear second lens frame support plates 36 and 37 in the optical axis direction. Similar

to the front eccentric pin 34X-b, the rear eccentric pin 34X-c is movable and immovable in the first vertically-elongated hole 37a in the Y-direction and X-direction, respectively. The front eccentric pin 5 34Y-b is movable and immovable in the horizontally-elongated hole 37e in the X-direction and Y-direction, respectively.

Similar to the pair of first vertically-elongated holes 36a and 37a and the pair of horizontally-elongated 10 holes 36e and 37e, the lengthwise direction of the second vertically-elongated hole 36f is parallel to the lengthwise direction of the second vertically-elongated hole 37f, while the second vertically-elongated hole 36f and the second vertically-elongated hole 37f are formed 15 at opposed positions on the front and rear second lens frame support plates 36 and 37 in the optical axis direction. The pair of the second vertically-elongated holes 36f and 37f are each elongated in the Y-direction to extend parallel to the pair of first vertically- 20 elongated holes 36a and 37a. The front boss 8j, which is engaged in the second vertically-elongated hole 36f, is movable and immovable in the second vertically-elongated hole 36f in the Y-direction and X-direction, respectively. Similar to the front boss 8j, the rear boss 25 8k, which is engaged in the second vertically-elongated

hole 37f, is movable and immovable in the second vertically-elongated hole 37f in the Y-direction and X-direction, respectively.

As shown in Figure 113, the large diameter portion 34X-a is inserted into the first eccentric shaft support hole 8f so as not to move in radial directions thereof, and is accordingly rotatable about the axis (adjustment axis PX) of the large diameter portion 34X-a. Likewise, the large diameter portion 34Y-a is inserted into the second eccentric shaft support hole 8i so as not to move in radial directions thereof, and is accordingly rotatable on the axis (adjustment axis PY1) of the large diameter portion 34Y-a.

The front eccentric pin 34Y-b and the rear eccentric pin 34Y-c have the common axis eccentric to the axis of the large diameter portion 34Y-a as mentioned above. Therefore, a rotation of the second eccentric shaft 34Y on the adjustment axis PY1 causes the front and rear eccentric pins 34Y-b and 34b-c to revolve about the adjustment axis PY1, i.e., rotate in a circle about the adjustment axis PY1, thus causing the front eccentric pin 34Y-b to push the front second lens frame support plate 36 in the Y-direction while moving in the X-direction and at the same time causing the rear eccentric pin 34Y-c to push the rear second lens frame support plate 37 in the

Y-direction while moving in the X-direction. At this time, the front second lens frame support plate 36 moves linearly in the Y-direction while guided in the same direction by the front eccentric pin 34Y-b and the front boss 8j since both the first vertically-elongated hole 36a and the second vertically-elongated hole 36f are elongated in the Y-direction, and at the same time, the rear second lens frame support plate 37 moves linearly in the Y-direction while guided in the same direction by the rear eccentric pin 34Y-c and the rear boss 8k since both the first vertically-elongated hole 37a and the second vertically-elongated hole 37f are elongated in the Y-direction. Consequently, the position of the second lens frame 6 relative to the second lens group moving frame 8 on the front fixing surface 8c thereof varies to adjust the position of the optical axis of the second lens group LG2 in the Y-direction.

The front eccentric pin 34X-b and the rear eccentric pin 34X-c have the common axis eccentric to the axis of the large diameter portion 34X-a as mentioned above. Therefore, a rotation of the first eccentric shaft 34X on the adjustment axis PX causes the front and rear eccentric pins 34X-b and 34X-c to revolve about the adjustment axis PX, i.e., rotate in a circle about the adjustment axis PX, thus causing the front eccentric pin

34X-b to push the front second lens frame support plate 36 in the X-direction while moving in the Y-direction and at the same time causing the rear eccentric pin 34X-c to push the rear second lens frame support plate 37 in the X-direction while moving in the Y-direction. At this time, although the front eccentric pin 34Y-b and the rear eccentric pin 34Y-c are respectively movable in the horizontally-elongated hole 36e and the horizontally-elongated hole 37e in the X-direction, the front second lens frame support plate 36 swings about a fluctuating axis (not shown) extending substantially parallel to the common axis of the front and rear bosses 8j and 8k in the vicinity of this common axis since the second vertically-elongated hole 36f is immovable in the X-direction relative to the front boss 8j and at the same time the rear second lens frame support plate 37 swings about the fluctuating axis since the second vertically-elongated hole 37f is immovable in the X-direction relative to the rear boss 8k. The position of the fluctuating axis corresponds to the following two resultant positions: a front resultant position between the position of the horizontally-elongated hole 36e relative to the front eccentric pin 34Y-b and the position of the second vertically-elongated hole 36f relative to the front boss 8j, and a rear resultant position between

the position of the horizontally-elongated hole 37e relative to the rear eccentric pin 34Y-b and the position of the second vertically-elongated hole 37f relative to the rear boss 8k. Therefore, the fluctuating axis
5 fluctuates in parallel to itself by a swing of the front and rear second lens frame support plates 36 and 37 about the fluctuating axis. A swing of the front and rear second lens frame support plates 36 and 37 about the fluctuating axis causes the pivot shaft 33 to move
10 substantially linearly in the X-direction. Therefore, the second lens group LG2 moves in the X-direction by a rotation of the first eccentric shaft 34X on the adjustment axis PX.

Figure 116 shows another embodiment of the first
15 positioning device for adjusting the positions of the front and rear second lens frame support plates 36 and 37 relative to the second lens group moving frame 8. This embodiment of the first positioning device is different from the above described first positioning device in that
20 a front obliquely-elongated hole 36f' and a rear obliquely-elongated hole 37f' in which the front boss 8j and the rear boss 8k are engaged are formed on the front and rear second lens frame support plates 36 and 37 instead of the second vertically-elongated hole 36f and the second
25 vertically-elongated hole 37f, respectively. The front

obliquely-elongated hole 36f' and the rear obliquely-elongated hole 37f' extend parallel to each other obliquely to both X-direction and Y-direction, and are aligned in the optical axis direction. Since each of the
5 front obliquely-elongated hole 36f' and the rear obliquely-elongated hole 37f' includes both a component in the X-direction and a component in the Y-direction, a rotation of the second eccentric shaft 34Y on the adjustment axis PY1 causes the front obliquely-elongated
10 hole 36f' and the rear obliquely-elongated hole 37f' to move in the Y-direction while moving in the X-direction slightly relative to the front boss 8j and the rear boss 8k, respectively. Consequently, the front and rear second lens frame support plates 36 and 37 move in the
15 Y-direction while the respective lower end portions thereof swing slightly in the X-direction. On the other hand, a rotation of the first eccentric shaft 34X on the adjustment axis PX causes the front and rear second lens frame support plates 36 and 37 to move in the X-direction
20 while moving (swinging) slightly in the Y-direction. Accordingly, the position of the optical axis of the second lens group LG2 can be adjusted in directions lying in a plane orthogonal to the photographing optical axis Z1 by a combination of an operation of the first eccentric
25 shaft 34X and an operation of the second eccentric shaft

34Y.

The set screw 66 needs to be loosened before the position of the optical axis of the second lens group LG2 is adjusted by operating the first eccentric shaft 34X and the second eccentric shaft 34Y. The set screw 66 is tightened after the adjustment operation is completed. Thereafter, the front and rear second lens frame support plates 36 and 37 are tightly fixed to the front fixing surface 8c and the rear fixing surface 8e to be held at their respective adjusted positions. Therefore, the pivot shaft 33 is also held at its adjusted position. Consequently, the position of the optical axis of the second lens group LG2 is held at its adjusted position since the position of the optical axis of the second lens group LG2 depends on the position of the pivot shaft 33. As a result of the optical axis position adjustment operation, the set screw 66 has been moved radially from the previous position thereof; however, this presents no problem because the set screw 66 does not move radially to such an extent so as to interfere with the second lens group moving frame 8 by the optical axis position adjustment operation since the threaded shaft portion 66a is loosely fitted in the screw insertion hole 8h as shown in Figure 113.

A two-dimensional positioning device which

incorporates a first movable stage movable linearly along a first direction and a second movable stage movable linearly along a second direction perpendicular to the first direction, wherein an object the position of which is to be adjusted is mounted on the second movable stage, is known in the art. The structure of this conventional two-dimensional positioning device is generally complicated. In contrast, the above illustrated first positioning device for adjusting the positions of the front and rear second lens frame support plates 36 and 37 relative to the second lens group moving frame 8 is simple because each of the front second lens frame support plate 36 and the rear second lens frame support plate 37 is supported on a corresponding single flat surface (the front fixing surface 8c or the rear fixing surface 8e) to be movable thereon in both X-direction and Y-direction, which makes it possible to achieve a simple two-dimensional positioning device.

Although the above illustrated first positioning device includes two support plates (the pair of second lens frame support plates 36 and 37) for supporting the second lens frame 6, which are positioned separately from each other in the optical axis direction to increase a stability of the structure supporting the second lens frame 6, it is possible for the second lens frame 6 to

be supported with only one of the two support plates. In this case, the first positioning device has only to be provided on the one support plate.

Nevertheless, in the above illustrated embodiment
5 of the first positioning device, the front second lens frame support plate 36 and the rear second lens frame support plate 37 are arranged on front and rear sides of the second lens group moving frame 8, each of the first and second eccentric shafts 34X is provided at the front
10 and rear ends thereof with a pair of eccentric pins (34X-b and 34X-c), respectively, and the second lens group moving frame 8 is provided on front and rear sides thereof with a pair of bosses (8j and 8k), respectively. With this arrangement, a rotation of either eccentric shafts 34X
15 or 34Y causes the pair of second lens frame support plates 36 and 37 to move in parallel as one-piece member. Specifically, rotating the first eccentric shaft 34X with a screwdriver engaged in the recess 34X-d causes the front and rear eccentric pins 34X-b and 34X-c to rotate together
20 by the same amount of rotation in the same rotational direction, thus causing the pair of second lens frame support plates 36 and 37 to move in parallel as an integral member in the X-direction. Likewise, rotating the second eccentric shaft 34Y with a screwdriver engaged in the
25 recess 34Y-d causes the front and rear eccentric pins

34Y-b and 34Y-c to rotate together by the same amount of rotation in the same rotational direction, thus causing the pair of second lens frame support plates 36 and 37 to move in parallel as an integral member in the Y-direction. When the first and second eccentric shafts 34X and 34Y are each rotated with a screwdriver engaged in the recesses 34X-d and 34Y-d, respectively, the rear second lens frame support plate 37 properly follows the movement of the front second lens frame support plate 36 without being warped. Accordingly, the optical axis of the second lens group LG2 does not tilt by an operation of the first positioning device, which makes it possible to adjust the position of the optical axis of the second lens group LG2 two-dimensionally in directions lying in a plane orthogonal to the photographing optical axis Z1 with a high degree of precision.

Since the first and second eccentric shafts 34X and 34Y are supported and held between the front second lens frame support plate 36 and the rear second lens frame support plate 37 disposed on front and rear sides of the shutter unit 76, each of the first and second eccentric shafts 34X and 34Y is elongated so that the length thereof becomes close to the length of the second lens group moving frame 8 in the optical axis direction, just as the length of the pivot shaft 33. This prevents the second lens

group moving frame 8 from tilting, which accordingly makes it possible to adjust the position of the optical axis of the second lens group LG2 two-dimensionally in directions lying in a plane orthogonal to the photographing optical axis Z1 with a higher degree of precision.

The second positioning device for adjusting the point of engagement of the eccentric pin 35b of the rotation limit shaft 35 with the engaging protrusion 6e of the second lens frame 6 will be hereinafter discussed. As shown in Figures 111 and 112, the large diameter portion 35a of the rotation limit shaft 35 is rotatably fitted in the through hole 8m with the eccentric pin 35b projecting rearward from the rear end of the through hole 8m. Note that the large diameter portion 35a of the rotation limit shaft 35 does not rotate by itself with respect to the through hole 8m, however, if a predetermined amount of force is applied, it is possible for the large diameter portion 35a to be rotated.

As shown in Figure 109, the eccentric pin 35b is positioned at one end of the moving path of the tip of the engaging protrusion 6e of the second lens frame 6. The eccentric pin 35b projects rearward from the rear end of the large diameter portion 35a so that the axis of the eccentric pin 35b is eccentric from the axis of the large

diameter portion 35a as shown in Figure 117. Therefore,
a rotation of the eccentric pin 35b on an axis thereof
(adjustment axis PY2) causes the eccentric pin 35b to
revolve about the adjustment axis PY2, thus causing the
5 eccentric pin 35b to move in the Y-direction. Since the
eccentric pin 35b of the rotation limit shaft 35 serves
as an element for determining the photographing position
of the second lens frame 6, a displacement of the eccentric
pin 35b in the Y-direction causes the second lens group
10 LG2 to move in the Y-direction. Therefore, the position
of the optical axis of the second lens group LG2 can be
adjusted in the Y-direction by an operation of the
rotation limit shaft 35. Accordingly, the position of
the optical axis of the second lens group LG2 can be
15 adjusted in the Y-direction by the combined use of the
rotation limit shaft 35 and the second eccentric shaft
34Y. It is desirable that the rotation limit shaft 35
be operated secondarily in a particular case where the
range of adjustment of the second eccentric shaft 34Y is
20 insufficient.

As shown in Figure 110, the recess 34X-d of the first
eccentric shaft 34X, the recess 34Y-d of the second
eccentric shaft 34Y and the recess 35c of the rotation
limit shaft 35 are all exposed to the front of the second
25 lens group moving frame 8. In addition, the head of the

set screw 66 that is provided with the cross slot 66b is exposed to the front of the second lens group moving frame 8. Due to this structure, the position of the optical axis of the second lens group LG2 can be adjusted two-dimensionally with the above described first and second positioning devices from the front of the second lens group moving frame 8, i.e., all the operating members of the first and second positioning devices are accessible from the front of the second lens group moving frame 8. On the other hand, the first external barrel 12, that is positioned radially outside the second lens group moving frame 8, is provided on an inner peripheral surface thereof with the inner flange 12c which projects radially inwards to close the front of the second lens group moving frame 8 in cooperation with the fixing ring 3.

As shown in Figures 131 and 132, the first external barrel 12 is provided on the inner flange 12c with four screwdriver insertion holes 12g1, 12g2, 12g3 and 12g4 which penetrate the inner flange 12c in the optical axis direction so that the recess 34X-d, the recess 34Y-d, the recess 35c and the cross slot 66b are exposed to the front of the first external barrel 12, respectively. A screwdriver can be brought into engagement with the recess 34X-d, the recess 34Y-d, the recess 35c and the cross slot 66b from the front of the second lens group moving frame

8 through the four screwdriver insertion holes 12g1, 12g2, 12g3 and 12g4, respectively, without removing the first external barrel 12 from the front of the second lens group moving frame 8. As shown in Figures 2, 131 and 132, portions of the fixing ring 3 which are aligned with the screwdriver insertion holes 12g2, 12g3 and 12g4 are cut out so as not to interfere with the screwdriver. The respective front ends of the four screwdriver insertion holes 12g1, 12g2, 12g3 and 12g4 are exposed to the front of the zoom lens 71 by removing the lens barrier cover 101 and the aforementioned lens barrier mechanism positioned immediately behind the lens barrier cover 101. Due to this structure, the position of the optical axis of the second lens group LG2 can be adjusted two-dimensionally with the above described first and second positioning devices from the front of the second lens group moving frame 8 without dismounting components of the zoom lens 71 except for substantially the lens barrier mechanism, i.e., in substantially finished form. Accordingly, the position of the optical axis of the second lens group LG2 can be easily adjusted two-dimensionally with the first and second positioning devices in a final assembling process even if the degree of deviation of the second lens group LG2 is out of tolerance during assembly. This results in an

improvement in workability of the assembly process.

The structure accommodating the second lens group LG2 and other optical elements behind the second lens group LG2 in the camera body 72 upon the main switch of the digital camera 70 being turned OFF has mainly been
5 discussed above. Improvements in the structure of the zoom lens 71 which accommodates the first lens group LG1 upon the main switch of the digital camera 70 being turned OFF will be hereinafter discussed in detail.

10 As shown in Figure 2, the inner flange 12c of the first external barrel 12 is provided at radially opposite positions thereon with respect to the photographing optical axis Z1 with a pair of first guide grooves 12b, respectively, while the first lens group adjustment ring
15 2 is provided on an outer peripheral surface thereof with a corresponding pair of guide projections 2b which project radially outwards in opposite directions away from each other to be slidably fitted in the pair of first guide grooves 12b, respectively. Only one guide projection 2b
20 and the associated first guide groove 12b appear in Figures 9, 141 and 142. The pair of first guide grooves 12b extend parallel to the photographing optical axis Z1 so that the combination of the first lens frame 1 and the first lens group adjustment ring 2 is movable in the
25 optical axis direction with respect to the first external

barrel 12 by engagement of the pair of guide projections 2b with the pair of first guide grooves 12b.

The fixing ring 3 is fixed to the first external barrel 12 by the two set screws 64 to close the front of the pair of guide projections 2b. The fixing ring 3 is provided at radially opposite positions thereon with respect to the photographing optical axis Z1 with a pair of spring receiving portions 3a, so that a pair of compression coil springs 24 are installed in a compressed manner between the pair of spring receiving portions 3a and the pair of guide projections 2b, respectively. Therefore, the first lens group adjustment ring 2 is biased rearward in the optical axis direction with respect to the first external barrel 12 by the spring force of the pair of compression coil springs 24.

In an assembly process of the digital camera 70, the position of the first lens frame 1 relative to the first lens group adjustment ring 2 in the optical axis direction can be adjusted by changing the position of engagement of the male screw thread 1a relative to the female screw thread 2a of the first lens group adjustment ring 2. This adjusting operation can be carried out in a state where the zoom lens 71 is set at the ready-to-photograph state as shown in Figure 141. Two-dot chain lines shown in Figure 141 show movements of the first lens frame 1

together with the first lens group LG1 with respect to the first external barrel 12 in the optical axis direction. On the other hand, when the zoom lens 71 is retracted to the retracted position as shown in Figure 10, the first external barrel 12, together with the fixing ring 3, can further move rearward relative to the first lens frame 1 and the first lens group adjustment ring 2 while compressing the pair of compression coil springs 24 even after the first lens frame 1 has fully retracted to a point at which the first lens frame 1 contacts with a front surface of the shutter unit 76 to thereby be prevented from further moving rearward (see Figure 142). Namely, when the zoom lens 71 is retracted to the retracted position, the first external barrel 12 is retracted to be accommodated in such a manner as to reduce an axial margin (axial space) for positional adjustment of the first lens frame 1 in the optical axis direction. This structure makes it possible for the zoom lens 71 to be fully retracted deeper into the camera body 72. Conventional telescoping lens barrels in which a lens frame (which corresponds to the first lens frame 1) is directly fixed to an external lens barrel (which corresponds to the first external barrel 12) by screw threads (similar to the female screw thread 2a and the male screw thread 1a) without any intermediate member

(which corresponds to the first lens group adjustment ring 2) interposed between the lens frame and the external lens barrel are known in the art. In this type of telescoping lens barrels, since the amount of retracting movement of the external lens barrel into a camera body is the same as that of the lens frame, the external lens barrel cannot be further moved rearward relative to the lens frame, unlike the first external barrel 12 of the present embodiment of the zoom lens.

10 The first lens frame 1 is provided at the rear end thereof with an annular end protrusion 1b (see Figures 133, 134, 141 and 142), the rear end of which is position behind the rearmost point on the rear surface of the first lens group LG1 in the optical axis direction, so that the rear end of the annular end protrusion 1b comes into contact with a front surface of the shutter unit 76 to prevent the rear surface of the first lens group LG1 from contacting with the shutter unit 76 and being damaged thereby when the zoom lens 71 is retracted to the retracted position.

25 More than two guide projections, each corresponding to each of the two guide projections 2b, can be formed on the first lens group adjustment ring 2 at any positions on an outer peripheral surface thereof, and also the shape of each guide projection is optional. According to the

number of the guide projections of the first lens group
adjustment ring 2, the fixing ring 3 can be provided with
more than two spring receiving portions each
corresponding to each of the two spring receiving portions
5 3a, and also the shape of each spring receiving portion
is optional. In addition, the pair of spring receiving
portions 3a is not essential; the pair of compression coil
springs 24 can be installed in a compressed manner between
corresponding two areas on a rear surface of the fixing
10 ring 3 and the pair of guide projections 2b, respectively.

The first lens group adjustment ring 2 is provided
on an outer peripheral surface thereof, at the front end
of the outer peripheral surface at substantially
equi-angular intervals about the photographing optical
15 axis Z1, with a set of four engaging projections 2c (see
Figure 2) which are engageable with a front surface 3c
of the fixing ring 3. The rear limit for the axial
movement of the first lens group adjustment ring 2 with
respect to the fixing ring 3 (i.e., with respect to the
20 first external barrel 12) is determined by engagement
(bayonet engagement) of the set of four engaging
projections 2c with the front surface 3c of the fixing
ring 3 (see Figures 9 and 141). The set of four engaging
projections 2c serve as a set of bayonets.

25 Specifically, the fixing ring 3 is provided on an

inner edge thereof with a set of four recesses 3b (see Figure 2) to correspond to the set of four engaging projections 2c, respectively. The set of four engaging projections 2c can be inserted into the set of four recesses 3b from behind, respectively, and are engaged with the front surface 3c of the fixing ring 3 by rotating one of the first lens group adjustment ring 2 and the fixing ring 3 relative to the other clockwise or counterclockwise after the set of four engaging projections 2c are inserted into the set of four recesses 3b from behind. After this operation rotating one of the first lens group adjustment ring 2 and the fixing ring 3 relative to the other, a rear end surface 2c1 of each engaging projection 2c is pressed against the front surface 3c (a surface of the fixing ring 3 which can be seen in Figure 2) of the fixing ring 3 by the spring force of the pair of compression coil springs 24. This firm engagement of the set of four engaging projections 2c with the front surface 3c of the fixing ring 3 prevents the combination of the first lens frame 1 and the first lens group adjustment ring 2 from coming off the first external barrel 12 from the rear thereof, and accordingly determines the rear limit for the axial movement of the first lens group adjustment ring 2 with respect to the first external barrel 12.

When the zoom lens 71 is fully retracted into the camera body 72 as shown in Figures 10 and 142, the rear surfaces 2c1 of the set of four engaging projections 2c are disengaged from the front surface 3c of the fixing ring 3 because the first lens group adjustment ring 2 has moved forward slightly with respect to the first external barrel 12 from the position of the first lens group adjustment ring 2 shown in Figure 141 by further compressing the pair of compression coil springs 24. However, once the zoom lens 71 enters the ready-to-photograph state as shown in Figure 141, the rear surfaces 2c1 are re-engaged with the front surface 3c. Accordingly, the rear surfaces 2c1 of the four engaging projections 2c and the front surface 3c serve as reference surfaces for determining the position of the first lens group LG1 with respect to the first external barrel 12 in the optical axis direction in the ready-to-photograph state of the zoom lens barrel 71. With this structure, even if the axial position of the first lens group LG1 with respect to the first external barrel 12 changes when the zoom lens 71 is retracted into the camera body 72, the first lens group LG1 automatically returns to its original position by the action of the pair of compression coil springs 24 as soon as the zoom lens 71 is ready to photograph.

At least two and any number other than four engaging projections each corresponding to each of the four engaging projections 2c can be formed on the first lens group adjustment ring 2 at any position on an outer peripheral surface thereof. According to the number of the engaging projections of the first lens group adjustment ring 2, the fixing ring 3 can be provided with at least two and any number other than four recesses each corresponding to each of the four recesses 3b. Moreover, the shape of each engaging projection of the first lens group adjustment ring 2 and also the shape of each spring receiving portion of the fixing ring 3 are optional as long as each engaging projection of the first lens group adjustment ring 2 is insertable into the corresponding recess of the fixing ring 3.

As has been described above, when the zoom lens 71 changes from the ready-to-photograph state to the retracted state, the cylindrical lens holder portion 6a of the second lens frame 6, which holds the second lens group LG2, rotates about the pivot pin 33 in a direction away from the photographing optical axis Z1 inside the second lens group moving frame 8, while the AF lens frame 51 which holds the third lens group LG3 enters the space in the second lens group moving frame 8 from which the lens holder portion 6a has retracted (see Figures 134,

136 and 137). In addition, when the zoom lens 71 changes from the ready-to-photograph state to the retracted state, the first lens frame 1 that holds the first lens group LG1 enters the second lens group moving frame 8 from the front thereof (see Figures 133 and 135). Accordingly, the second lens group moving frame 8 has to be provided with two internal spaces: a front internal space immediately in front of the central inner flange 8s in which the first lens frame 1 is allowed to move in the optical axis direction, and a rear internal space immediately behind the central inner flange 8s in which the second lens frame 6 is allowed to retract along a plane orthogonal to the photographing optical axis Z1 and in which the AF lens frame 51 is allowed to move in the optical axis direction. In the present embodiment of the zoom lens, the shutter unit 76, specifically an actuator thereof, is disposed inside the second lens group moving frame 8, which accommodates more than one lens group therein, in a space-saving manner to maximize the internal space of the second lens group moving frame 8.

Figure 140 shows the elements of the shutter unit 76. The shutter unit 76 is provided with a base plate 120 having a central circular aperture 120a with its center on the photographing optical axis Z1. The base plate 120 is provided on a front surface thereof (a surface

which can be seen in Figure 140) above the circular aperture 120a with a shutter-actuator support portion 120b formed integral with the base plate 120. The shutter-actuator support portion 120b is provided with
5 a substantially cylindrical accommodation recess 120b1 in which the shutter actuator 131 is accommodated. After the shutter actuator 131 is embedded in the accommodation recess 120b1, a holding plate 121 is fixed to the shutter-actuator support portion 120b so that the shutter
10 actuator 131 is supported by the base plate 120 on the front thereof.

The shutter unit 76 is provided with a diaphragm-actuator support member 120c which is fixed to the back of the base plate 120 on the right side of the
15 cylindrical recess 120b1 as viewed from the rear of the base plate 120. The shutter unit 76 is provided with a diaphragm-actuator support cover 122 having a substantially cylindrical accommodation recess 122a in which the diaphragm actuator 132 is accommodated. The
20 diaphragm-actuator support cover 122 is fixed to the back of the diaphragm-actuator support member 120c. After the diaphragm actuator 132 is embedded in the accommodation recess 122a, the diaphragm-actuator support cover 122 is fixed to the back of the diaphragm-actuator support member
25 120c so that the diaphragm actuator 132 is supported by

the diaphragm-actuator support member 120c on the back thereof. The shutter unit 76 is provided with a cover ring 123 which is fixed to the diaphragm-actuator support cover 122 to cover an outer peripheral surface thereof.

5 The holding plate 121 is fixed to the shutter-actuator support portion 120b by a set screw 129a. The diaphragm-actuator support member 120c is fixed to the back of the base plate 120 by set screw 129b. Furthermore, the diaphragm-actuator support member 120c is fixed to
10 the holding plate 121 by a set screw 129c. A lower end portion of the diaphragm-actuator support member 120c which is provided with a screw hole into which the set screw 129b is screwed is formed as a rearward-projecting portion 120c1.

15 The shutter S and the adjustable diaphragm A are mounted to the rear of the base plate 120 immediately beside the diaphragm-actuator support member 120c. The shutter S is provided with a pair of shutter blades S1 and S2, and the adjustable diaphragm A is provided with
20 a pair of diaphragm blades A1 and A2. The pair of shutter blades S1 and S2 are pivoted on a first pair of pins (not shown) projecting rearward from the back of the base plate 120, respectively, and the pair of diaphragm blades A1 and A2 are pivoted on a second pair of pins (not shown)
25 projecting rearward from the back of the base plate 120,

respectively. These first and second pairs of pints do
no appear in Figure 140. The shutter unit 76 is provided
between the shutter S and the adjustable diaphragm A with
a partition plate 125 which prevents the shutter S and
5 the adjustable diaphragm A from interfering with each
other. The shutter S, the partition plate 125 and the
adjustable diaphragm A are fixed to the back of the base
plate 120 in this order from front to rear in the optical
axis direction, and thereafter a blade-holding plate 126
10 is fixed to the back of the base plate 120 to hold the
shutter S, the partition plate 125 and the adjustable
diaphragm A between the base plate 120 and the blade-
holding plate 126. The partition plate 125 and the
blade-holding plate 126 are provided with a circular
15 aperture 125a and a circular aperture 126a, respectively,
through which rays of light of an object image which is
to be photographed pass to be incident on the CCD image
sensor 60 through the third lens group LG3 and the low-pass
filter LG4. The circular apertures 125a and 126a are
20 aligned with the central circular aperture 120a of the
base plate 120.

The shutter actuator 131 is provided with a rotor
131a, a rotor magnet (permanent magnet) 131b, a stator
131c made of steel, and a bobbin 131d. The rotor 131a
25 is provided with a radial arm portion, and an eccentric

pin 131e which projects rearwards from the tip of the radial arm portion to be inserted into cam grooves S1a and S2a of the pair of shutter blades S1 and S2. Strands (not shown) through which electric current is passed via the flexible PWB 77 to control rotation of the rotor 131a are wound on the bobbin 131d. Passing a current through the strands wound on the bobbin 131d causes the rotor 131a to rotate forward or reverse depending on the magnetic field which varies in accordance with the direction of the passage of the current. Rotations of the rotor 131a forward and reverse cause the eccentric pin 131e to swing in forward and reverse directions, thus causing the pair of shutter blades S1 and S2 to open and close, respectively, by engagement of the eccentric pin 131e with the cam grooves S1a and S2a.

The diaphragm actuator 132 is provided with a rotor 132a and a rotor magnet (permanent magnet) 132b. The rotor 132a is provided with a radial arm portion having two ninety-degree bends, and an eccentric pin 132c which projects rearwards from the tip of the radial arm portion to be inserted into cam grooves A1a and A2a of the pair of diaphragm blades A1 and A2. Strands (not shown) through which electric current is passed via the flexible PWB 77 to control rotation of the rotor 132a are wound on the diaphragm-actuator support member 120c and the

diaphragm-actuator support cover 122. Passing a current through the strands wound on the diaphragm-actuator support member 120c and the diaphragm-actuator support cover 122 causes the rotor 132a to rotate forward or
5 reverse depending on the magnetic field which varies in accordance with the direction of the passage of the current. Rotations of the rotor 132a forward and reverse cause the eccentric pin 132c to swing in forward and reverse directions, thus causing the pair of diaphragm blades A1
10 and A2 to open and close, respectively, by engagement of the eccentric pin 132c with the cam grooves A1a and A2a.

The shutter unit 76 is prepared as a subassembly in advance, and fitted into the second lens group moving frame 8 to be fixed thereto. As shown in Figures 108 and
15 110, the shutter unit 76 is supported by the second lens group moving frame 8 therein so that the base plate 120 is positioned immediately in front of the central inner flange 8s. A terminal end 77e of the flexible PWB 77 is fixed to a front surface of the holding plate 121 (see
20 Figures 108, 110, 133 and 135).

The second lens group moving frame 8 has a cylindrical shape coaxial to other rotatable rings such as the cam ring 11. The axis of the second lens group moving frame 8 coincides with the lens barrel axis Z0 of
25 the zoom lens 71. The photographing optical axis Z1 is

eccentric downward from the lens barrel axis Z0 to secure some space in the second lens group moving frame 8 into which the second lens group LG2 is retracted to the radially-retracted position (see Figures 110 through 112). On the other hand, the first lens frame 1, which supports the first lens group LG1, is in the shape of a cylinder with its center on the photographing optical axis Z1, and is guided along the photographing optical axis Z1. Due to this structure, the space in the second lens group moving frame 8 which is occupied by the first lens group LG1 is secured in the second lens group moving frame 8 below the lens barrel axis Z0. Accordingly, sufficient space (upper front space) is easily secured in the second lens group moving frame 8 in front of the central inner flange 8s on the opposite side of the lens barrel axis Z0 from the photographing optical axis Z1 (i.e., above the lens barrel axis Z0) so that the shutter actuator 131 and supporting members therefor (the shutter-actuator support portion 120b and the holding plate 121) are positioned in the upper front space along an inner peripheral surface of the second lens group moving frame 8. With this structure, the first lens frame 1 does not interfere with either the shutter actuator 131 or the holding plate 121 even if the first lens frame 1 enters the second lens group moving frame 8 from the front thereof

as shown in Figure 135. Specifically, in the retracted state of the zoom lens 71, the holding plate 121 and the shutter actuator 131, which is positioned behind the holding plate 121, are positioned in an axial range in which the first lens group LG1 is positioned in the optical axis direction; namely, the holding plate 121 and the shutter actuator 131 are positioned radially outside the first lens group LG1. This maximizes the utilization of the internal space of the second lens group moving frame 8, thus contributing to a further reduction of the length of the zoom lens 71.

The first lens frame 1 that holds the first lens group LG1 is positioned in the first external barrel 12 to be supported thereby via the first lens group adjustment ring 2 as shown in Figure 138 to be movable together with the first external barrel 12 in the optical axis direction though the first lens group adjustment ring 2 is not shown in Figures 133 and 135 around the first lens frame 1 for the purpose of illustration. The inner flange 12c of the first external barrel 12 is provided, above the portion thereof which holds the first lens frame 1 and the first lens group adjustment ring 2, with a through hole 12c1 which has a substantially arm shape as viewed from or rear of the first external barrel 12 and which penetrates the first external barrel 12 in the

optical axis direction. The through hole 12c1 is shaped so that the holding plate 121 can enter the through hole 12c1 from behind. The holding plate 121 enters the through hole 12c1 as shown in Figure 138 when the zoom
5 lens 71 is in the retracted position.

In the rear internal space of the second lens group moving frame 8 behind the central inner flange 8s, not only the forwardly-projecting lens holder portion 51c (the third lens group LG3) of the AF lens frame 51 moves
10 in and out in the optical axis direction above the photographing optical axis Z1 that is positioned below the lens barrel axis Z0, but also the cylindrical lens holder portion 6a retracts into the space on the opposite side of the lens barrel axis Z0 from the photographing
15 optical axis Z1 when the zoom lens 71 is retracted into the camera body 72. Accordingly, there is substantially no extra space in the second lens group moving frame 8 behind the central inner flange 8s in a direction (vertical direction) of a straight line M1 orthogonally
20 intersecting both the lens barrel axis Z0 and the photographing optical axis Z1 (see Figure 112). Whereas, two side spaces not interfering with either the second lens group LG2 or the third lens group LG3 are successfully secured on respective sides (right and left sides) of the
25 line M1 in the second lens group moving frame 8 until an

inner peripheral surface thereof behind the central inner flange 8s in a direction (see Figure 112) of a straight line M2 which is orthogonal to the straight line M1 and intersecting the photographing optical axis Z1. As can
5 be seen in Figures 111 and 112, the left side space of the two side spaces which is positioned on the left side as viewed in Figure 112 (on the left side of the lens barrel axis Z0 and the photographing optical axis Z1 as viewed from the rear of the second lens frame 8) is utilized
10 partly as the space for the swing arm portion 6c of the swingable second lens frame 6 to swing therein and partly as the space for accommodating the above described first positioning device, with which the positions of the front and rear second lens frame support plates 36 and 37
15 relative to the second lens group moving frame 8 can be adjusted. The right side space of the aforementioned two side spaces which is positioned on the right side as viewed in Figure 112 is utilized as the space for accommodating the diaphragm actuator 132 and supporting members
20 therefor (the diaphragm-actuator support cover 122 and the cover ring 123) so that the diaphragm actuator 132 and the supporting members are positioned along an inner peripheral surface of the second lens group moving frame 8. More specifically, the diaphragm actuator 132 and the
25 supporting members (the diaphragm-actuator support cover

122 and the cover ring 123) lie on the straight line M2. Accordingly, as can be understood from Figures 111, 112 and 137, the diaphragm actuator 132, the diaphragm-actuator support cover 122 and the cover ring 123 do not
5 interfere with either the range of movement of the second lens group LG2 or the range of movement of the third lens group LG3.

Specifically, in the inside of the second lens group moving frame 8 behind the central inner flange 8s, the
10 second lens group LG2 (the cylindrical lens holder portion 6a) and the third lens group LG3 (forwardly-projecting lens holder portion 51c) are accommodated on upper and lower sides of the lens barrel axis Z0, respectively, while the above described first positioning device and
15 diaphragm actuator 132 are positioned on right and left sides of the lens barrel axis Z0 when the zoom lens 71 is in the retracted state. This maximizes the utilization of the internal space of the second lens group moving frame 8 in the retracted state of the zoom lens
20 71. In this state, the diaphragm-actuator support cover 122, the cover ring 123 and the diaphragm actuator 132 are positioned in the space radially outside the space in which the second lens group LG2 and the third lens group LG3 are accommodated. This contributes to a further
25 reduction of the length of the zoom lens 71.

In the present embodiment of the zoom lens, the base plate 120 of the shutter unit 120 is positioned in front of the central inner flange 8s, whereas the diaphragm actuator 132, the diaphragm-actuator support cover 122 and the cover ring 123 are positioned behind the central inner flange 8s. In order to allow the diaphragm actuator 132, the diaphragm-actuator support cover 122 and the cover ring 123 extend behind the central inner flange 8s, the central inner flange 8s is provided with a substantially circular through hole 8s1 in which the cover ring 123 is fitted (see Figures 110 through 112). The central inner flange 8s is further provided below the through hole 8s1 with an accommodation recess 8s2 in which the rearward-projecting portion 120c1 of the diaphragm-actuator support member 120c is accommodated.

The forwardly-projecting lens holder portion 51c of the AF lens frame 51 is provided, on the side surface 51c4 among the four side surfaces 51c3, 51c4, 51c5 and 51c6 around the forwardly-projecting lens holder portion 51c, with a recess 51i which is formed by cutting out a part of the forwardly-projecting lens holder portion 51c. The recess 51i is formed to correspond to the shapes of outer peripheral surfaces of the ring cover 123 and the accommodation recess 8s2 of the second lens group moving frame 8 so that the forwardly-projecting lens holder

portion 51c does not interfere with the ring cover 123 and the accommodation recess 8s2 in the retracted state of the zoom lens 71. Namely, the outer peripheral portions of the ring cover 123 and the accommodation
5 recess 8s2 partly enter the recess 51i when the zoom lens 71 is fully retracted into the camera body 72 (see Figures 122, 130 and 137). This further maximizes the utilization of the internal space of the second lens group moving frame 8 to minimize the length of the zoom lens
10 71.

In the present embodiment of the zoom lens, even the shutter actuator 131 and the diaphragm actuator 132 are structured in consideration of the utilization of the internal space of the zoom lens 71.

15 The space in front of the base plate 120 is narrow in the optical axis direction since the shutter unit 76 is supported by the second lens group moving frame 8 therein toward the front thereof as can be seen in Figures 9 and 10. Due to the limitation of the space in front
20 of the base plate 120, the shutter actuator 131 adopts the structure, in which the rotor magnet 131b and the bobbin 131d do not adjoin each other in the optical axis direction but are positioned separately from each other in a direction perpendicular to the optical axis direction,
25 so that variations of the magnetic field generated on the

side of the bobbin 131d are transferred to the side of the rotor magnet 131d via the stator 131c. This structure reduces the thickness of the shutter actuator 131 in the optical axis direction, thus making it possible for the shutter actuator 131 to be positioned in the limited space in front of the base plate 120 without problems.

On the other hand, the space behind the base plate 120 is also limited in a direction perpendicular to the optical axis direction because the second lens group LG2 and other retractable parts are positioned behind the base plate 120. Due to the limitation of the space behind the base plate 120, the diaphragm actuator 132 adopts the structure in which strands are wound directly on the diaphragm-actuator support member 120c and the diaphragm-actuator support cover 122 which cover the rotor magnet 132b. This structure reduces the height of the diaphragm actuator 132 in a direction perpendicular to the optical axis direction, thus making it possible for the diaphragm actuator 132 to be positioned in the limited space behind the base plate 120 without problems.

The digital camera 70 is provided above the zoom lens 71 with a zoom viewfinder, the focal length of which varies to correspond to the focal length of the zoom lens 71. As shown in Figures 9, 10 and 143, the zoom viewfinder is provided with a zoom type viewing optical system

including an objective window plate 81a (not shown in Figure 143), a first movable power-varying lens 81b, a second movable power-varying lens 81c, a mirror 81d, a fixed lens 81e, a prism (erecting system) 81f, an eyepiece 81g and an eyepiece window plate 81h, in that order from the object side along a viewfinder optical axis. The objective window plate 81a and the eyepiece window plate 81h are fixed to the camera body 72, and the remaining optical elements (81b through 81g) are supported by a viewfinder support frame 82. Among the optical elements 81b through 81g supported by the viewfinder support frame 82, the mirror 81d, the fixed lens 81e, the prism 81f and the eyepiece 81g are fixed to the viewfinder support frame 82 at their respective predetermined positions thereon. The zoom viewfinder is provided with a first movable frame 83 and a second movable frame 84 which hold the first movable power-varying lens 81b and the second movable power-varying lens 81c, respectively. The first movable frame 83 and the second movable frame 84 are guided in the optical axis direction by a first guide shaft 85 and a second guide shaft 86 which extend in a direction parallel to the photographing optical axis Z1, respectively. The first movable power-varying lens 81b and the second movable power-varying lens 81c have a common optical axis Z3 which remains in parallel to the

photographing optical axis Z1 regardless of variations of the relative position between the first movable power-varying lens 81b and the second movable power-varying lens 81c. The first movable frame 83 and the
5 second movable frame 84 are biased forward, toward the objective side, by a first compression coil spring 87 and a second compression coil spring 88, respectively. The zoom viewfinder is provided with a cam-incorporated gear 90 having a substantially cylindrical shape. The
10 cam-incorporated gear 90 is fitted on a rotational shaft 89 to be supported thereon. The rotational shaft 89 is fixed to the viewfinder support frame 82 to extend parallel to the optical axis Z3 (the photographing optical axis Z1).

15 The cam-incorporated gear 90 is provided at the front end thereof with a spur gear portion 90a. The cam-incorporated gear 90 is provided immediately behind the spur gear portion 90a with a first cam surface 90b, and is provided between the first cam surface 90b and the
20 rear end of the cam-incorporated gear 90 with a second cam surface 90c. The cam-incorporated gear 90 is biased forward by a compression coil spring 90d to remove backlash. A first follower pin 83a (see Figure 148) projected from the first movable frame 83 is pressed
25 against the first cam surface 90b by the spring force of

the first compression coil spring 87, while a second follower pin 84a (see Figures 143, 146 and 148) projected from the second movable frame 84 is pressed against the second cam surface 90c by the spring force of the second compression coil spring 88. A rotation of the cam-incorporated gear 90 causes the first movable frame 83 and the second movable frame 84 that respectively hold the first movable power-varying lens 81b and the second movable power-varying lens 81c to move in the optical axis direction in a predetermined moving manner while changing the space therebetween in accordance with the contours of the first cam surface 90b and the second cam surface 90c to vary the focal length of the zoom viewfinder in synchronization with the focal length of the zoom lens 71. Figure 156 is a developed view of an outer peripheral surface of the cam-incorporated gear 90, showing the positional relationship between the first follower pin 83a and the first cam surface 90b and the positional relationship between the second follower pin 84a and the second cam surface 90c in each of three different states, i.e., at the wide-angle extremity, the telephoto extremity and the retracted position of the zoom lens 71. All the elements of the zoom viewfinder except for the objective window plate 81a and the eyepiece window plate 81h are put together to be prepared as a viewfinder unit

(subassembly) 80 as shown in Figure 143. The viewfinder unit 80 is mounted on top of the stationary barrel 22 via set screws 80a as shown in Figure 5.

The digital camera 70 is provided between the
5 helicoid ring 18 and the cam-incorporated gear 90 with a viewfinder drive gear 30 and a gear train (reduction gear train) 91. The viewfinder drive gear 30 is provided with a spur gear portion 30a which is in mesh with the annular gear 18c of the helicoid ring 18. Rotation of
10 the zoom motor 150 is transferred from the annular gear 18c to the cam-incorporated gear 90 via the viewfinder drive gear 30 and the gear train 91 (see Figures 146 and 147). The viewfinder drive gear 30 is provided behind the spur gear portion 30a with a semi-cylindrical portion
15 30b, and is further provided with a front rotational pin 30c and a rear rotational pin 30d which project from the front end of the spur gear portion 30a and the rear end of the semi-cylindrical portion 30b, respectively so that the front rotational pin 30c and the rear rotational pin
20 30d are positioned on a common rotational axis of the viewfinder drive gear 30. The front rotational pin 30c is rotatably fitted into a bearing hole 22p (see Figure 6) formed on the stationary barrel 22 while the rear rotational pin 30d is rotatably fitted into a bearing hole
25 21g (see Figure 8) formed on the CCD holder 21. Due to

this structure, the viewfinder drive gear 30 is rotatable about its rotational axis (the rotational pins 30c and 30d) extending parallel to the lens barrel axis Z0 (the rotational axis of the helicoid ring 18), and is immovable in the optical axis direction. The gear train 91 is composed of a plurality of gears: a first gear 91a, a second gear 91b, a third gear 91c and a fourth gear 91d. Each of the first through third gears 91a, 91b and 91c is a double gear consisting of a large gear and a small gear, and the fourth gear 91d is a simple spur gear as shown in Figures 5 and 146. The first through fourth gears 91a, 91b, 91c and 91d are respectively rotatably fitted on four rotational pins projecting from the stationary barrel 22 in parallel to the photographing optical axis Z1. As shown in Figures 5 through 7, a gear hold plate 22 is fixed to the stationary barrel 22 by set screws 92a to be positioned immediately in front of the first through fourth gears 91a, 91b, 91c and 91d to prevent the first through fourth gears 91a, 91b, 91c and 91d from coming off their respective rotational pins. With the gear train 91 fixed properly at their respective fixing positions as shown in Figures 146 through 148, rotation of the viewfinder drive gear 30 is imparted to the cam-incorporated gear 90 via the gear train 91. Figure 6 through 8 show the zoom lens 71 in a state where the

viewfinder drive gear 30, the viewfinder unit 80 and the gear train 91 are all fixed to the stationary barrel 22.

As described above, the helicoid ring 18 continues to be driven to move forward along the lens barrel axis Z0 (the photographing optical axis Z1) while rotating about the lens barrel axis Z0 with respect to the stationary barrel 22 and the first linear guide ring 14 until the zoom lens 71 reaches the wide-angle extremity (zooming range) from the retracted position. Thereafter, the helicoid ring 18 rotates about the lens barrel axis Z0 at a fixed position with respect to the stationary barrel 22 and the first linear guide ring 14, i.e., without moving along the lens barrel axis Z0 (the photographing optical axis Z1). Figures 23 through 25, 144 and 145 show different operational states of the helicoid ring 18. Specifically, Figures 23 and 144 show the helicoid ring 18 in the retracted state of the zoom lens 71, Figures 24 and 145 show the helicoid ring 18 at the wide-angle extremity of the zoom lens 71, and Figure 25 shows the telephoto extremity of the zoom lens 71. In Figures 144 and 145, the stationary barrel 22 is not shown for the purpose of making the relationship between the viewfinder drive gear 30 and the helicoid ring 18 easier to understand.

The viewfinder drive gear 30 does not rotate about

the lens barrel axis Z0 during the time the helicoid ring 18 rotates about the lens barrel axis Z0 while moving in the optical axis direction, i.e., during the time the zoom lens 71 is extended forward from the retracted position to a position immediately behind the wide-angle extremity (i.e., immediately behind the zooming range). The viewfinder drive gear 30 rotates about the lens barrel axis Z0 at a fixed position only when the zoom lens 71 is in the zoom ranging between the wide-angle extremity and the telephoto extremity. Namely, in the viewfinder drive gear 30, the spur gear portion 30a is formed thereon to occupy only a front small part of the viewfinder drive gear 30, so that the spur gear portion 30a is not in mesh with the annular gear 18c of the helicoid ring 18 in the retracted state of the zoom lens 71 because the annular gear 18c is positioned behind the front rotational pin 30c the retracted state of the zoom lens 71. The annular gear 18c reaches the spur gear portion 30a to mesh therewith immediately before the zoom lens 71 reaches the wide-angle extremity. Thereafter, from the wide-angle extremity to the telephoto extremity, the annular gear 18c remains in mesh with the spur gear portion 30a because the helicoid ring 18 does not move in the optical axis direction (horizontal direction as viewed in Figures 23 through 25, 144 and 145).

As can be understood from Figures 153 through 155, the semi-cylindrical portion 30b of the viewfinder drive gear 30 is provided with an incomplete cylindrical portion 30b1 and a flat surface portion 30b2 which is formed as a cut-away portion of the incomplete cylindrical portion 30b1 so that the flat surface portion 30b2 extends along the rotational axis of the viewfinder drive gear 30. Accordingly, the semi-cylindrical portion 30b has a non-circular cross section, i.e., a substantially D-shaped cross section. As can be seen in Figures 153 through 155, some specific teeth of the spur gear portion 30a adjacent to the flat surface portion 30b2 project radially outwards beyond the position of the flat surface portion 30b2 in a direction of engagement of the some specific teeth of the spur gear portion 30a with the annular gear 18c (i.e., horizontal direction as viewed in Figure 153). When the zoom lens 71 is in the retracted state, the viewfinder drive gear 30 is in its specific angular position in which the flat surface portion 30b2 faces the annular gear 18c of the helicoid ring 18 as shown in Figure 153. In this state shown in Figure 153, the viewfinder drive gear 30 cannot rotate even if driven to rotate because the flat surface portion 30b2 is in close vicinity of the addendum circle of the annular gear 18c. Namely, even if the viewfinder drive gear 30 tries to

rotate in the state shown in Figure 153, the flat surface portion 30b2 would hit some teeth of the annular gear 18c, so that the viewfinder drive gear 30 cannot rotate.

If the helicoid ring 18 moves forward until the
5 annular gear 18c of the helicoid ring 18 is properly engaged with the spur gear portion 30a of the viewfinder drive gear 30 as shown in Figure 145, the portion of the helicoid ring 18 which includes the entire part of the annular gear 18c is positioned in front of the semi-
10 cylindrical portion 30b in the optical axis direction. In this state, the viewfinder drive gear 30 rotates by rotation of the helicoid ring 18 since the semi-cylindrical portion 30b does not overlap the annular gear 18c in radial directions of the zoom lens 71.

15 Although the helicoid ring 18 is provided in front of the annular gear 18c with the set of three rotational sliding projections 18b each having a radial height greater than the radial height (tooth depth) of the annular gear 18c, the set of three rotational sliding
20 projections 18b do not interfere with the viewfinder drive gear 30 during the time the helicoid ring 18 moves between the position thereof at the wide-angle extremity and the position thereof at the telephoto extremity while rotating about the lens barrel axis Z0 because the
25 rotation of the helicoid ring 18 for driving the zoom lens

71 from the retracted position to the wide-angle extremity
is completed while the viewfinder drive gear 30 is
positioned in between two of the three rotational sliding
projections 18b in a circumferential direction of the
5 helicoid ring 18. Thereafter, the set of three
rotational sliding projections 18b and the spur gear
portion 30a do not interfere with each other since the
set of three rotational sliding projections 18b are
positioned in front of the spur gear portion 30a in the
10 optical axis direction in a state where the annular gear
18c is engaged with the spur gear portion 30a.

In the above illustrated embodiment, with respect
to the helicoid ring 18 which rotates about the lens barrel
axis Z0 while moving in the optical axis direction in one
15 state and which rotates at a fixed position on the lens
barrel axis Z0 in another state, the spur gear portion
30a is formed on the specific portion of the viewfinder
drive gear 30 which is engageable with the annular gear
18c only when the helicoid ring 18 rotates at its
20 predetermined axial fixed position. Moreover, the
semi-cylindrical portion 30b is formed on the viewfinder
drive gear 30 behind the spur gear portion 30a thereof,
so that the viewfinder drive gear 30 is prohibited from
rotating by interference of the semi-cylindrical portion
25 30b with the annular gear 18c during the time the helicoid

ring 18 rotates about the lens barrel axis 20 while moving in the optical axis direction. Due to this structure, although the viewfinder drive gear 30 does not rotate while the zoom lens 71 is extended or retracted between the retracted position and a position immediately behind the wide-angle extremity, the viewfinder drive gear 30 rotates only when the zoom lens 71 is driven to change its focal length between the wide-angle extremity and the telephoto extremity. In short, the viewfinder drive gear 30 is driven only when the viewfinder drive gear 30 needs to be associated with the photographing optical system of the zoom lens 71.

Assuming the viewfinder drive gear 30 rotates whenever the helicoid ring 18 rotates, a drive transfer system extending from the viewfinder drive gear to a movable lens of the zoom viewfinder has to be provided with an idle running section for disengaging the movable lens from the viewfinder drive gear, because the viewfinder drive gear 30 rotates even when it is not necessary to drive the zoom viewfinder, i.e., when the zoom lens 71 is extended forward to the wide-angle extremity from the retracted state. Figure 157 is a developed view, similar to that of Figure 156, of an outer peripheral surface of a cam-incorporated gear 90' (which corresponds to the cam-incorporated gear 90 of the zoom

lens 71) which is provided with such an idle running section. In each of Figures 156 and 157, the spur gear portion 90a is not shown for clarity.

A first cam surface 90b' of the cam-incorporated gear 90', which correspond to the first cam surface 90b of the cam-incorporated gear 90, is provided with a long linear surface 90b1' for preventing a follower pin 83a' (which corresponds to the follower pin 83a) from moving in an optical axis direction Z3' (which corresponds to the optical axis Z3) even if the cam-incorporated gear 90 rotates. Likewise, a second cam surface 90c' of the cam-incorporated gear 90', which correspond to the second cam surface 90c of the cam-incorporated gear 90, is provided with a long linear surface 90c1' for preventing a follower pin 84a' (which corresponds to the follower pin 84a) from moving in the optical axis direction Z3' even if the cam-incorporated gear 90 rotates. As can be understood by a comparison between Figures 156 and 157, the long linear surface 90b1' consumes a large circumferential range of the first cam surface 90b' to thereby shorten the remaining circumferential range of the first cam surface 90b' which is used as a cam surface for moving the follower pin 83a' in the optical axis direction; this inevitably increases the degree of inclination of the cam surface. Likewise, the long

linear surface 90c1' consumes a large circumferential range of the second cam surface 90c' to thereby shorten the remaining circumferential range of the second cam surface 90c' which is used as a cam surface for moving
5 the follower pin 84a' in the optical axis direction; this inevitably increases the degree of inclination of the cam surface. If the degree of inclination of each of the first cam surface 90b' and the second cam surface 90c' is great, the amount of movement of each follower pin 83' and 84' along the rotational axis of the cam-incorporated
10 gear 90' (i.e., along the optical axis Z3) per unit of rotation of the cam-incorporated gear 90' becomes great, which makes it difficult to move each follower pin 83' and 84' with a high degree of positioning accuracy. If
15 the degree of inclination of each of the first cam surface 90b' and the second cam surface 90c' is reduced to prevent this problem from occurring, the diameter of the cam-incorporated gear 90' has to be increased, which is detrimental to miniaturization of the zoom lens. This
20 problem is also true for the case of adopting a cam plate instead of a cylindrical cam member such as the cam-incorporated gear 90.

In contrast, in the present embodiment of the zoom lens, in which the viewfinder drive gear 30 is not driven
25 when not necessary to rotate, the cam-incorporated gear

90 does not have to be provided on each of the first and second cam surfaces 90b and 90c with an idle running section. Therefore, an effective circumferential range of a cam surface for moving the follower pin 83a or 84a in the optical axis direction can be secured on each of the first and second cam surfaces 90b and 90c without increasing either the degree of inclination of the cam surfaces or the diameter of the cam-incorporated gear 90. In other words, miniaturizing the drive system for the zoom viewfinder and driving the movable lenses of the viewfinder optical system with high accuracy can be both achieved. In the present embodiment of the zoom lens, the first and second cam surfaces 90b and 90c of the cam-incorporated gear 90 are provided with linear surfaces 90b1 and 90c1 which look like the aforementioned linear surfaces 90b1' and 90c1', respectively, due to the fact that the annular gear 18c is brought into engagement with the spur gear portion 30a intentionally at the moment immediately before the zoom lens 71 reaches the zooming range (the wide-angle extremity) when the zoom lens 71 is extended forward from the retracted position in consideration of backlash and play among gears shown in Figures 146 through 148. Nevertheless, the circumferential lengths of the linear surfaces 90b1 and 90c1 are much smaller than those of the linear surfaces

90b1' and 90c1' of the comparative embodiment.

In the present embodiment of the zoom lens, the annular gear 18c is formed so that the spur gear portion 30a of the viewfinder drive gear 30 can smoothly mesh with the annular gear 18c. Specifically, one of a plurality of gear teeth of the annular gear 18c, i.e., a short gear tooth 18c1 is formed to have a shorter tooth depth than those of other normal gear teeth 18b2 of the annular gear 18c.

Figures 149 through 152 show the positional relationship between the annular gear 18c of the helicoid ring 18 and the spur gear portion 30a of the viewfinder drive gear 30 in different states in time sequence in the course of variation in state of the zoom lens from the state shown in Figure 144 in which the zoom lens 71 is in the retracted state to the state as shown in Figure 145 in which the zoom lens 71 is set at wide-angle extremity. The positional relationship between the annular gear 18c and the spur gear portion 30a is obtained in the middle of rotation of the helicoid ring 18 in a direction from the retracted position to the wide-angle extremity.

Subsequently, the short gear teeth 18c1 approaches the spur gear portion 30a and is positioned in the immediate vicinity of the spur gear portion 30a as shown

in Figure 150. Figure 153 shows this state shown in Figure 150, viewed from the front of the viewfinder drive gear 30. It can be seen from Figure 153 that the short gear teeth 18c1 is not yet engaged with the spur gear portion 30a. The normal gear teeth 18c2 are positioned farther from the spur gear portion 30a than the short gear tooth 18c1, and therefore are not yet engaged with the spur gear portion 30a either. No gear teeth serving as gear teeth of the annular gear 18c is formed on a specific portion of the outer peripheral surface of the helicoid ring 18; the specific portion is right next to the short gear tooth 18c1 on one of the opposite sides thereof in the circumferential direction of the helicoid ring 18. Accordingly, at the stage shown in Figures 150 and 153, the annular gear 18c is not yet engaged with the spur gear portion 30a, so that rotation of the helicoid rig 18 is not yet transferred to the viewfinder drive gear 30. In this connection, at the stage shown in Figures 150 and 153, a part of the annular gear 18c still faces the flat surface portion 30b2 to prohibit the viewfinder drive gear 30 from rotating.

A further rotation of the helicoid ring 18 in the lens barrel advancing direction causes to the short gear tooth 18c1 to reach its position shown in Figure 151. At this stage shown in Figure 151, the short gear tooth 18c1

comes into contact with one of the teeth of the spur gear portion 30a and subsequently presses the same in the lens barrel advancing direction (upwards as viewed in Figures 151) to start rotating the viewfinder drive gear 30.

5 A further rotation of the helicoid ring 18 in the lens barrel advancing direction causes a gear tooth of the normal tooth gear 18c2, which is adjacent to the short gear tooth 18c1 on one of the opposite sides thereof in the circumferential direction of the helicoid ring 18, 10 to press the subsequent gear teeth of the spur gear portion 30a to keep rotating the viewfinder drive gear 30. Thereafter, the annular gear 18c imparts a further rotation of the helicoid ring 18 to the viewfinder drive gear 30 via the engagement of the normal tooth gear 18c2 15 with the gear teeth of the spur gear portion 30a. At the stage shown in Figure 145 at which the helicoid ring 18 reaches the position thereof at the wide-angle extremity, the short gear teeth 18c1 is not used for the subsequent rotation of the helicoid ring 18 in the zooming range 20 between the wide-angle extremity and the telephoto extremity since the short gear teeth 18c1 has already passed the point of engagement with the spur gear portion 30a.

 Accordingly, in the present embodiment of the zoom 25 lens, a portion of the annular gear 18c, which is firstly

engaged with the spur gear portion 30a of the viewfinder drive gear 30, is formed as at least one short gear tooth (18c1), the teeth depth of which is smaller than those of the other gear teeth of the annular gear 18c.

5 According to this construction, the annular gear 18c can be reliably and surely engaged with the spur gear portion 30a upon commencement of engagement therewith. Namely, in the case of tall (normal) gear teeth, since the tips of mutually neighboring tall gear teeth having very

10 different relative angles, the engagement thereof is shallow (the initial engagement range is narrow) so that there is a chance of engagement therebetween failing (miss engagement). Whereas, since the short gear teeth 18c1 moves until the relative angle between the short gear

15 teeth 18c1 and the tall gear teeth (the spur gear portion 30a of the viewfinder drive gear 30) becomes substantially the same before engaging, a deeper engagement is achieved (the initial engagement range is wide), so that there is no chance of engagement therebetween failing (missing

20 engagement). Furthermore, this structure reduces the shock at the movement of engagement of the annular gear 18c with the spur gear portion 30a, thus making it possible to smoothly start operations of the zoom viewfinder drive system including the viewfinder drive gear 30 and to

25 reduce the noise produced by the zoom viewfinder drive

system.

Although the above descriptions have been directed mainly to the features found in operations of the zoom lens 71 when the zoom lens 71 advances from the retracted position toward the zooming range, similar features can surely be expected in operations of the zoom lens 71 when the zoom lens 71 retracts to the retracted position.

As can be understood from the above descriptions, in the present embodiment of the zoom lens, the helicoid ring 18 can be driven to perform the above-described rotating-advancing/rotating-retracting operation, in which the helicoid ring 18 rotates while moving in the optical axis direction, and the above-described fixed-position rotating operation, in which the helicoid ring 18 rotates at a predetermined axial fixed position without moving in the optical axis direction, with a simple mechanism (drive mechanism) having the male and female helicoids 18a and 22a (that have male threads and female threads which are formed on radially-opposed outer and inner peripheral surfaces of the helicoid ring 18 and the stationary barrel 22, respectively), the set of three rotational sliding projections 18b, the set of three inclined grooves 22c and the set of three rotational sliding grooves 22d. This drive mechanism is simpler, smaller and lower-cost than similar conventional drive

mechanisms. In addition, providing the stationary barrel 22 with the set of three inclined grooves 22c makes it possible to prevent the set of three rotational sliding projections 18b from interfering with the stationary barrel 22 when the set of three rotational sliding projections 18b are disengaged from the set of three rotational sliding grooves 22d, i.e., when the male helicoid 18a and the female helicoid 22a are engaged with each other.

10 In the above described embodiment of the zoom lens, the zoom gear 28 is positioned between two of the set of three inclined grooves (plurality of inclined grooves) 22c in a circumferential direction of the stationary barrel 22, while the zoom gear 28 is installed on the stationary barrel 22 at a position different from the position of the set of three rotational sliding grooves 22d in the optical axis direction. Namely, the zoom gear 28 is supported by the stationary barrel 22 at a position not overlapping the moving paths of the set of three rotational sliding projections 18b. Therefore, the set of three rotational sliding projections 18b do not interfere with the zoom gear 28. Accordingly, the set of three rotational sliding projections 18b do not interfere with the zoom gear 28 in either the above-described rotating-advancing/rotating-retracting

operation or the above-described fixed-position rotating operation. Conversely, each of the three rotational sliding projections 18b can have a sufficient amount of projection in a radial direction of the helicoid ring 18 because the set of three rotational sliding projections 18b do not interfere with the zoom gear 28. As mentioned above, if each rotational sliding projection 18b has a sufficient amount of projection in a radial direction of the helicoid ring 18, the helicoid ring 18 and the stationary barrel 22 do not have to be increased in diameter, and the helicoid ring 18 can be driven with a high degree of precision in the fixed-position rotating operation.

The present invention is not limited solely to the particular embodiment described above. For instance, although the helicoid ring 18 and the stationary barrel 22 are provided with the set of rotational sliding projections 18b and the set of rotational sliding grooves 22d in the present embodiment of the zoom lens, respectively, the helicoid ring 18 can be provided with a set of rotational sliding grooves corresponding to the set of rotational sliding grooves 22d and the stationary barrel 22 can be provided with a set of rotational sliding projections corresponding to the set of rotational sliding projections 18b.

Although the set of rotational sliding projections 18b are positioned in front of the male helicoid 18a on the helicoid ring 18 in the optical axis direction, while the set of rotational sliding grooves 22d are positioned in front of the female helicoid 22a on the stationary barrel 22 in the optical axis direction in the above illustrated embodiment of the zoom lens, it is possible that a male helicoid (which corresponds to the male helicoid 18a but is opposite in lead direction to the male helicoid 18a) and a female helicoid (which corresponds to the female helicoid 22a but is opposite in lead direction to the female helicoid 22a) be formed on the helicoid ring 18 and the stationary barrel 22 in front of the set of rotational sliding projections 18b and the set of rotational sliding grooves 22d, respectively.

As can be understood from the above descriptions, the helicoid ring 18 can rotate at its predetermined axial fixed position more stably and precisely as the amount of projection of each rotational sliding projection 18b in a radially outward direction is great. Due to this reason, the amount of projection of each rotational sliding projection 18b is greater than the tooth depth of the male helicoid 18a in the above illustrated embodiment of the zoom lens. However, the amount of projection of each rotational sliding projection 18b can

be smaller than its actual amount of projection shown in the above-described embodiment to the extent of being equal to or even smaller than the tooth depth of the male helicoid 18a within a range ensuing the minimum positional accuracy of the helicoid ring 18. In this case, the set of rotational sliding projections 18b and the stationary barrel 22 can be prevented from interfering with each other even if a set of clearance grooves such as the set of three inclined grooves 22c for preventing the set of three rotational sliding projections 18b and the stationary barrel 22 from interfering with each other do not have to be formed on the stationary barrel 22. Namely, it is only necessary that the stationary barrel 22 be provided, on the inner peripheral surface thereof on which the female helicoid 22a is formed, with a set of three non-threaded portions instead of the set of three inclined grooves 22c, wherein the width and the direction of extension of each non-threaded portion are the same as the width and the direction of each inclined groove 22c. Specifically, each non-threaded portion of such a set of three non-threaded portions can be made by enlarging the space among two adjacent threads of the female helicoid 22a. In other words, each inclined groove 22c can be said to serve as a non-threaded portion formed on the stationary barrel 22.

The set of three inclined grooves 22c can be used not only as clearance grooves but also as auxiliary grooves for providing assistance to the engagement of the female helicoid 22a with the male helicoid 18a. Specifically, the two circumferential end surfaces 18b-A and 18b-B of each rotational sliding projection 18b are not engaged with the two opposed inclined surfaces 22c-A and 22c-B in the associated inclined groove 22c, respectively, so that the set of rotational sliding projections 18b and the set of inclined grooves 22c do not interfere with the feed function of the male helicoid 18a and the female helicoid 22a when the helicoid ring 18 moves in the optical axis direction while rotating about the lens barrel axis Z0. Nevertheless, the two circumferential end surfaces 18b-A and 18b-B of each rotational sliding projection 18b and the two opposed inclined surfaces 22c-A and 22c-B in the associated inclined groove 22c can be brought into engagement with each other, respectively, to be used as guiding surfaces for the rotating-advancing/rotating-retracting operation of the helicoid ring 18 if formed with a high degree of precision to a degree not interfering with the feed function of the male helicoid 18a and the female helicoid 22a.

Although each set of the set of rotational sliding

projections 18b, the set of inclined grooves 22c and the set of rotational sliding grooves 22d is provided as a set of three projections or grooves formed at different circumferential positions, the number of projections or grooves of each set of the set of rotational sliding
5 projections 18b, the set of inclined grooves 22c and the set of rotational sliding grooves 22d is not limited solely to three but can be any other number.

In the above described embodiment of the zoom lens,
10 the first, second and third lens groups LG1, LG2 and LG3 can be driven in a different manner. For instance, in the above described embodiment of the zoom lens, in addition to the above described mechanism between the helicoid ring 18 and the stationary barrel 22, the zoom
15 lens 71 is further provided between the first linear guide ring 14 and the cam ring 11 with a mechanism (composed of the set of three through-slots 14e and the set of three roller followers 32) for making the cam ring 11 selectively perform a rotating-advancing/rotating-retracting operation (similar to the rotating-advancing/rotating-retracting operation of the helicoid
20 ring 18) in which the cam ring 11 rotates while moving in the optical axis direction, and a fixed-position rotating operation (similar to the fixed-position
25 rotating operation of the helicoid ring 18) in which the

cam ring 11 rotates at a predetermined axial fixed position without moving in the optical axis direction. With the two mechanisms, the cam ring 11 moves forward in the optical axis direction by an amount of movement
5 corresponding to the sum of the amount of forward movement of the cam ring 11 via a rotation of the helicoid ring 18 and the amount of forward movement of the cam ring 11 via a rotation of the cam ring 11 relative to the first linear guide ring 14. This makes it possible to increase
10 the amount of forward movement of the cam ring 11 from its fully retracted position to its operating position. However, the drive mechanism for driving the helicoid ring 18 so that it selectively performs the rotating-advancing/rotating-retracting operation and the
15 fixed-position rotating operation according to the present invention can also be applied even to the case where the rotating-advancing/rotating-retracting mechanism provided between the first linear guide ring 14 and the cam ring 11 is omitted so that the cam ring
20 11 advances and retracts only by a rotation of the helicoid ring 18.

Although the above illustrated embodiment of the zoom lens according to the present invention is a zoom lens in which the helicoid ring performs the fixed-
25 position rotating operation to carry out a zooming

operation, the present invention can also be applied to
a fixed-focal-length lens in which a helicoid ring
corresponding to the helicoid ring 18 is made to perform
the fixed-position rotating operation to carry out a
5 focusing operation or a similar operation, not a zooming
operation.

Obvious changes may be made in the specific
embodiments of the present invention described herein,
such modifications being within the spirit and scope of
10 the invention claimed. It is indicated that all matter
contained herein is illustrative and does not limit the
scope of the present invention.